
PyFilesystem Documentation

Release 2.4.11

Will McGugan

May 17, 2020

Contents

1	Introduction	3
1.1	Installing	3
2	Guide	5
2.1	Why use PyFilesystem?	5
2.2	Opening Filesystems	5
2.3	Tree Printing	6
2.4	Closing	7
2.5	Directory Information	7
2.6	Sub Directories	8
2.7	Working with Files	8
2.8	Walking	9
2.9	Globbering	9
2.10	Moving and Copying	9
3	Concepts	11
3.1	Paths	11
3.2	System Paths	12
3.3	Sandboxing	12
3.4	Errors	13
4	Resource Info	15
4.1	Info Objects	15
4.2	Namespaces	15
4.3	Missing Namespaces	17
4.4	Raw Info	18
5	FS URLs	19
5.1	Format	19
5.2	URL Parameters	20
5.3	Opening FS URLs	20
6	Walking	21
6.1	Walk Methods	21
6.2	Search Algorithms	22
7	Globbering	23

7.1	Matching Files and Directories	23
7.2	Interface	24
7.3	Batch Methods	24
8	Builtin Filesystems	25
8.1	App Filesystems	25
8.2	FTP Filesystem	27
8.3	Memory Filesystem	32
8.4	Mount Filesystem	34
8.5	Multi Filesystem	43
8.6	OS Filesystem	52
8.7	Sub Filesystem	57
8.8	Tar Filesystem	57
8.9	Temporary Filesystem	62
8.10	Zip Filesystem	63
9	Implementing Filesystems	69
9.1	Constructor	69
9.2	Thread Safety	69
9.3	Python Versions	70
9.4	Testing Filesystems	70
9.5	Essential Methods	71
9.6	Non - Essential Methods	71
9.7	Helper Methods	73
10	Creating an extension	75
10.1	Naming Convention	75
10.2	Opener	75
10.3	The setup.py file	76
10.4	Good Practices	76
10.5	Let us Know	77
10.6	Live Example	77
11	External Filesystems	79
12	PyFilesystem API	81
13	Reference	83
13.1	fs.base	83
13.2	fs.compress	101
13.3	fs.copy	101
13.4	fs.enums	104
13.5	fs.errors	104
13.6	fs.glob	107
13.7	fs.info	109
13.8	fs.filesize	113
13.9	fs.mirror	114
13.10	fs.move	115
13.11	fs.mode	116
13.12	fs.opener	117
13.13	fs.path	121
13.14	fs.permissions	128
13.15	fs.tools	130
13.16	fs.tree	131
13.17	fs.walk	131

13.18 fs.wildcard	139
13.19 fs.wrap	140
13.20 fs.wrapfs	147
14 Indices and tables	161
Python Module Index	163
Index	165

Contents:

PyFilesystem is a Python module that provides a common interface to any filesystem.

Think of PyFilesystem `FS` objects as the next logical step to Python's `file` objects. In the same way that file objects abstract a single file, FS objects abstract an entire filesystem.

1.1 Installing

You can install PyFilesystem with `pip` as follows:

```
pip install fs
```

Or to upgrade to the most recent version:

```
pip install fs --upgrade
```

PyFilesystem is also available on `conda`:

```
conda install fs -c conda-forge
```

Alternatively, if you would like to install from source, you can check out [the code from Github](#).

The PyFilesystem interface simplifies most aspects of working with files and directories. This guide covers what you need to know about working with FS objects.

2.1 Why use PyFilesystem?

If you are comfortable using the Python standard library, you may be wondering; *why learn another API for working with files?*

The *PyFilesystem API* is generally simpler than the `os` and `io` modules – there are fewer edge cases and less ways to shoot yourself in the foot. This may be reason alone to use it, but there are other compelling reasons you should use `import fs` for even straightforward filesystem code.

The abstraction offered by FS objects means that you can write code that is agnostic to where your files are physically located. For instance, if you wrote a function that searches a directory for duplicates files, it will work unaltered with a directory on your hard-drive, or in a zip file, on an FTP server, on Amazon S3, etc.

As long as an FS object exists for your chosen filesystem (or any data store that resembles a filesystem), you can use the same API. This means that you can defer the decision regarding where you store data to later. If you decide to store configuration in the *cloud*, it could be a single line change and not a major refactor.

PyFilesystem can also be beneficial for unit-testing; by swapping the OS filesystem with an in-memory filesystem, you can write tests without having to manage (or mock) file IO. And you can be sure that your code will work on Linux, MacOS, and Windows.

2.2 Opening Filesystems

There are two ways you can open a filesystem. The first and most natural way is to import the appropriate filesystem class and construct it.

Here's how you would open a *OSFS* (Operating System File System), which maps to the files and directories of your hard-drive:

```
>>> from fs.osfs import OSFS
>>> home_fs = OSFS("~/")
```

This constructs an FS object which manages the files and directories under a given system path. In this case, `'~/'`, which is a shortcut for your home directory.

Here's how you would list the files/directories in your home directory:

```
>>> home_fs.listdir('/')
['world domination.doc', 'paella-recipe.txt', 'jokes.txt', 'projects']
```

Notice that the parameter to `listdir` is a single forward slash, indicating that we want to list the *root* of the filesystem. This is because from the point of view of `home_fs`, the root is the directory we used to construct the OSFS.

Also note that it is a forward slash, even on Windows. This is because FS paths are in a consistent format regardless of the platform. Details such as the separator and encoding are abstracted away. See [Paths](#) for details.

Other filesystems interfaces may have other requirements for their constructor. For instance, here is how you would open a FTP filesystem:

```
>>> from ftpfs import FTPFS
>>> debian_fs = FTPFS('ftp.mirror.nl')
>>> debian_fs.listdir('/')
['debian-archive', 'debian-backports', 'debian', 'pub', 'robots.txt']
```

The second, and more general way of opening filesystems objects, is via an *opener* which opens a filesystem from a URL-like syntax. Here's an alternative way of opening your home directory:

```
>>> from fs import open_fs
>>> home_fs = open_fs('osfs://~/')
>>> home_fs.listdir('/')
['world domination.doc', 'paella-recipe.txt', 'jokes.txt', 'projects']
```

The opener system is particularly useful when you want to store the physical location of your application's files in a configuration file.

If you don't specify the protocol in the FS URL, then PyFilesystem will assume you want a OSFS relative from the current working directory. So the following would be an equivalent way of opening your home directory:

```
>>> from fs import open_fs
>>> home_fs = open_fs('.')
>>> home_fs.listdir('/')
['world domination.doc', 'paella-recipe.txt', 'jokes.txt', 'projects']
```

2.3 Tree Printing

Calling `tree()` on a FS object will print an ascii tree view of your filesystem. Here's an example:

```
>>> from fs import open_fs
>>> my_fs = open_fs('.')
>>> my_fs.tree()
├── locale
│   └── readme.txt
├── logic
│   └── content.xml
```

(continues on next page)

(continued from previous page)

```

├── data.xml
├── mountpoints.xml
├── readme.txt
├── lib.ini
└── readme.txt

```

This can be a useful debugging aid!

2.4 Closing

FS objects have a `close()` method which will perform any required clean-up actions. For many filesystems (notably *OSFS*), the `close` method does very little. Other filesystems may only finalize files or release resources once `close()` is called.

You can call `close` explicitly once you are finished using a filesystem. For example:

```

>>> home_fs = open_fs('osfs://~/')
>>> home_fs.writetext('reminder.txt', 'buy coffee')
>>> home_fs.close()

```

If you use FS objects as a context manager, `close` will be called automatically. The following is equivalent to the previous example:

```

>>> with open_fs('osfs://~/') as home_fs:
...     home_fs.writetext('reminder.txt', 'buy coffee')

```

Using FS objects as a context manager is recommended as it will ensure every FS is closed.

2.5 Directory Information

Filesystem objects have a `listdir()` method which is similar to `os.listdir`; it takes a path to a directory and returns a list of file names. Here's an example:

```

>>> home_fs.listdir('/projects')
['fs', 'moya', 'README.md']

```

An alternative method exists for listing directories; `scandir()` returns an *iterable* of *Resource Info* objects. Here's an example:

```

>>> directory = list(home_fs.scandir('/projects'))
>>> directory
[<dir 'fs'>, <dir 'moya'>, <file 'README.md'>]

```

Info objects have a number of advantages over just a filename. For instance you can tell if an info object references a file or a directory with the `is_dir` attribute, without an additional system call. Info objects may also contain information such as size, modified time, etc. if you request it in the `namespaces` parameter.

Note: The reason that `scandir` returns an iterable rather than a list, is that it can be more efficient to retrieve directory information in chunks if the directory is very large, or if the information must be retrieved over a network.

Additionally, FS objects have a `filterdir()` method which extends `scandir` with the ability to filter directory contents by wildcard(s). Here's how you might find all the Python files in a directory:

```
>>> code_fs = OSFS('~/projects/src')
>>> directory = list(code_fs.filterdir('/', files=['*.py']))
```

By default, the resource information objects returned by `scandir` and `listdir` will contain only the file name and the `is_dir` flag. You can request additional information with the `namespaces` parameter. Here's how you can request additional details (such as file size and file modified times):

```
>>> directory = code_fs.filterdir('/', files=['*.py'], namespaces=['details'])
```

This will add a `size` and `modified` property (and others) to the resource info objects. Which makes code such as this work:

```
>>> sum(info.size for info in directory)
```

See *Resource Info* for more information.

2.6 Sub Directories

PyFilesystem has no notion of a *current working directory*, so you won't find a `chdir` method on FS objects. Fortunately you won't miss it; working with sub-directories is a breeze with PyFilesystem.

You can always specify a directory with methods which accept a path. For instance, `home_fs.listdir('/projects')` would get the directory listing for the `projects` directory. Alternatively, you can call `opendir()` which returns a new FS object for the sub-directory.

For example, here's how you could list the directory contents of a `projects` folder in your home directory:

```
>>> home_fs = open_fs('~/')
>>> projects_fs = home_fs.opendir('/projects')
>>> projects_fs.listdir('/')
['fs', 'moya', 'README.md']
```

When you call `opendir`, the FS object returns an instance of a *SubFS*. If you call any of the methods on a *SubFS* object, it will be as though you called the same method on the parent filesystem with a path relative to the sub-directory.

The `makedir` and `makedirs` methods also return *SubFS* objects for the newly create directory. Here's how you might create a new directory in `~/projects` and initialize it with a couple of files:

```
>>> home_fs = open_fs('~/')
>>> game_fs = home_fs.makedirs('projects/game')
>>> game_fs.touch('__init__.py')
>>> game_fs.writetext('README.md', "Tetris clone")
>>> game_fs.listdir('/')
['__init__.py', 'README.md']
```

Working with *SubFS* objects means that you can generally avoid writing much path manipulation code, which tends to be error prone.

2.7 Working with Files

You can open a file from a FS object with `open()`, which is very similar to `io.open` in the standard library. Here's how you might open a file called "reminder.txt" in your home directory:

```
>>> with open_fs('~/') as home_fs:
...     with home_fs.open('reminder.txt') as reminder_file:
...         print(reminder_file.read())
buy coffee
```

In the case of a OSFS, a standard file-like object will be returned. Other filesystems may return a different object supporting the same methods. For instance, *MemoryFS* will return a `io.BytesIO` object.

PyFilesystem also offers a number of shortcuts for common file related operations. For instance, `readbytes()` will return the file contents as a bytes, and `readtext()` will read unicode text. These methods is generally preferable to explicitly opening files, as the FS object may have an optimized implementation.

Other *shortcut* methods are `download()`, `upload()`, `writebytes()`, `writetext()`.

2.8 Walking

Often you will need to scan the files in a given directory, and any sub-directories. This is known as *walking* the filesystem.

Here's how you would print the paths to all your Python files in your home directory:

```
>>> from fs import open_fs
>>> home_fs = open_fs('~/')
>>> for path in home_fs.walk.files(filter=['*.py']):
...     print(path)
```

The `walk` attribute on FS objects is instance of a *BoundWalker*, which should be able to handle most directory walking requirements.

See *Walking* for more information on walking directories.

2.9 Globbing

Closely related to walking a filesystem is *globbing*, which is a slightly higher level way of scanning filesystems. Paths can be filtered by a *glob* pattern, which is similar to a wildcard (such as `*.py`), but can match multiple levels of a directory structure.

Here's an example of globbing, which removes all the `.pyc` files in your project directory:

```
>>> from fs import open_fs
>>> open_fs('~/.project').glob('**/*.pyc').remove()
62
```

See *Globbing* for more information.

2.10 Moving and Copying

You can move and copy file contents with `move()` and `copy()` methods, and the equivalent `movedir()` and `copydir()` methods which operate on directories rather than files.

These move and copy methods are optimized where possible, and depending on the implementation, they may be more performant than reading and writing files.

To move and/or copy files *between* filesystems (as apposed to within the same filesystem), use the *move* and *copy* modules. The methods in these modules accept both FS objects and FS URLs. For instance, the following will compress the contents of your projects folder:

```
>>> from fs.copy import copy_fs
>>> copy_fs('~/projects', 'zip://projects.zip')
```

Which is the equivalent to this, more verbose, code:

```
>>> from fs.copy import copy_fs
>>> from fs.osfs import OSFS
>>> from fs.zipfs import ZipFS
>>> copy_fs(OSFS('~/projects'), ZipFS('projects.zip'))
```

The *copy_fs()* and *copy_dir()* functions also accept a *Walker* parameter, which can you use to filter the files that will be copied. For instance, if you only wanted back up your python files, you could use something like this:

```
>>> from fs.copy import copy_fs
>>> from fs.walk import Walker
>>> copy_fs('~/projects', 'zip://projects.zip', walker=Walker(filter=['*.py']))
```

An alternative to copying is *mirroring*, which will copy a filesystem then keep it up to date by copying only changed files / directories. See *mirror()*.

The following describes some core concepts when working with PyFilesystem. If you are skimming this documentation, pay particular attention to the first section on paths.

3.1 Paths

With the possible exception of the constructor, all paths in a filesystem are *PyFilesystem paths*, which have the following properties:

- Paths are `str` type in Python3, and `unicode` in Python2
- Path components are separated by a forward slash (/)
- Paths beginning with a / are *absolute*
- Paths not beginning with a forward slash are *relative*
- A single dot (.) means ‘current directory’
- A double dot (..) means ‘previous directory’

Note that paths used by the FS interface will use this format, but the constructor may not. Notably the *OSFS* constructor which requires an OS path – the format of which is platform-dependent.

Note: There are many helpful functions for working with paths in the *path* module.

PyFilesystem paths are platform-independent, and will be automatically converted to the format expected by your operating system – so you won’t need to make any modifications to your filesystem code to make it run on other platforms.

3.2 System Paths

Not all Python modules can use file-like objects, especially those which interface with C libraries. For these situations you will need to retrieve the *system path*. You can do this with the `getsyspath()` method which converts a valid path in the context of the FS object to an absolute path that would be understood by your OS.

For example:

```
>>> from fs.osfs import OSFS
>>> home_fs = OSFS('~/')
>>> home_fs.getsyspath('test.txt')
'/home/will/test.txt'
```

Not all filesystems map to a system path (for example, files in a *MemoryFS* will only ever exist in memory).

If you call `getsyspath` on a filesystem which doesn't map to a system path, it will raise a *NoSysPath* exception. If you prefer a *look before you leap* approach, you can check if a resource has a system path by calling `hassyspath()`

3.3 Sandboxing

FS objects are not permitted to work with any files outside of their *root*. If you attempt to open a file or directory outside the filesystem instance (with a backref such as `"../foo.txt"`), a *IllegalBackReference* exception will be thrown. This ensures that any code using a FS object won't be able to read or modify anything you didn't intend it to, thus limiting the scope of any bugs.

Unlike your OS, there is no concept of a current working directory in PyFilesystem. If you want to work with a sub-directory of an FS object, you can use the `opendir()` method which returns another FS object representing the contents of that sub-directory.

For example, consider the following directory structure. The directory `foo` contains two sub-directories; `bar` and `baz`:

```
--foo
 |--bar
 |  |--readme.txt
 |  `--photo.jpg
 `--baz
     |--private.txt
     `--dontopen.jpg
```

We can open the `foo` directory with the following code:

```
from fs.osfs import OSFS
foo_fs = OSFS('foo')
```

The `foo_fs` object can work with any of the contents of `bar` and `baz`, which may not be desirable if we are passing `foo_fs` to a function that has the potential to delete files. Fortunately we can isolate a single sub-directory with the `opendir()` method:

```
bar_fs = foo_fs.opendir('bar')
```

This creates a completely new FS object that represents everything in the `foo/bar` directory. The root directory of `bar_fs` has been re-positioned, so that from `bar_fs`'s point of view, the `readme.txt` and `photo.jpg` files are in the root:

```
--bar
|--readme.txt
`--photo.jpg
```

Note: This *sandboxing* only works if your code uses the filesystem interface exclusively. It won't prevent code using standard OS level file manipulation.

3.4 Errors

PyFilesystem converts errors in to a common exception hierarchy. This ensures that error handling code can be written once, regardless of the filesystem being used. See [errors](#) for details.

Resource information (or *info*) describes standard file details such as name, type, size, etc., and potentially other less-common information associated with a file or directory.

You can retrieve resource info for a single resource by calling `getinfo()`, or by calling `scandir()` which returns an iterator of resource information for the contents of a directory. Additionally, `filterdir()` can filter the resources in a directory by type and wildcard.

Here's an example of retrieving file information:

```
>>> from fs.osfs import OSFS
>>> fs = OSFS('.')
>>> fs.writetext('example.txt', 'Hello, World!')
>>> info = fs.getinfo('example.txt', namespaces=['details'])
>>> info.name
'example.txt'
>>> info.is_dir
False
>>> info.size
13
```

4.1 Info Objects

PyFilesystem exposes the resource information via properties of *Info* objects.

4.2 Namespaces

All resource information is contained within one of a number of potential *namespaces*, which are logical key/value groups.

You can specify which namespace(s) you are interested in with the `namespaces` argument to `getinfo()`. For example, the following retrieves the `details` and `access` namespaces for a file:

```
resource_info = fs.getinfo('myfile.txt', namespaces=['details', 'access'])
```

In addition to the specified namespaces, the filesystem will also return the `basic` namespace, which contains the name of the resource, and a flag which indicates if the resource is a directory.

4.2.1 Basic Namespace

The `basic` namespace is always returned. It contains the following keys:

Name	Type	Description
<code>name</code>	<code>str</code>	Name of the resource.
<code>is_dir</code>	<code>bool</code>	A boolean that indicates if the resource is a directory.

The keys in this namespace can generally be retrieved very quickly. In the case of *OSFS* the namespace can be retrieved without a potentially expensive system call.

4.2.2 Details Namespace

The `details` namespace contains the following keys.

Name	type	Description
<code>accessed</code>	<code>date-time</code>	The time the file was last accessed.
<code>created</code>	<code>date-time</code>	The time the file was created.
<code>meta-data_change_time</code>	<code>date-time</code>	The time of the last <i>metadata</i> (e.g. owner, group) change.
<code>modified</code>	<code>date-time</code>	The time file data was last changed.
<code>size</code>	<code>int</code>	Number of bytes used to store the resource. In the case of files, this is the number of bytes in the file. For directories, the <i>size</i> is the overhead (in bytes) used to store the directory entry.
<code>type</code>	<code>ResourceType</code>	Resource type, one of the values defined in <i>ResourceType</i> .

The time values (`accessed_time`, `created_time` etc.) may be `None` if the filesystem doesn't store that information. The `size` and `type` keys are guaranteed to be available, although `type` may be *unknown* if the filesystem is unable to retrieve the resource type.

4.2.3 Access Namespace

The `access` namespace reports permission and ownership information, and contains the following keys.

Name	type	Description
<code>gid</code>	<code>int</code>	The group ID.
<code>group</code>	<code>str</code>	The group name.
<code>permissions</code>	<code>Permissions</code>	An instance of <i>Permissions</i> , which contains the permissions for the resource.
<code>uid</code>	<code>int</code>	The user ID.
<code>user</code>	<code>str</code>	The user name of the owner.

This namespace is optional, as not all filesystems have a concept of ownership or permissions. It is supported by *OSFS*. Some values may be `None` if they aren't supported by the filesystem.

4.2.4 Stat Namespace

The `stat` namespace contains information reported by a call to `os.stat`. This namespace is supported by *OSFS* and potentially other filesystems which map directly to the OS filesystem. Most other filesystems will not support this namespace.

4.2.5 LStat Namespace

The `lstat` namespace contains information reported by a call to `os.lstat`. This namespace is supported by *OSFS* and potentially other filesystems which map directly to the OS filesystem. Most other filesystems will not support this namespace.

4.2.6 Link Namespace

The `link` namespace contains information about a symlink.

Name	type	Description
<code>target</code>	<code>str</code>	A path to the symlink target, or <code>None</code> if this path is not a symlink. Note, the meaning of this target is somewhat filesystem dependent, and may not be a valid path on the FS object.

4.2.7 Other Namespaces

Some filesystems may support other namespaces not covered here. See the documentation for the specific filesystem for information on what namespaces are supported.

You can retrieve such implementation specific resource information with the `get()` method.

Note: It is not an error to request a namespace (or namespaces) that the filesystem does *not* support. Any unknown namespaces will be ignored.

4.3 Missing Namespaces

Some attributes on the `Info` objects require that a given namespace be present. If you attempt to reference them without the namespace being present (because you didn't request it, or the filesystem doesn't support it) then a `MissingInfoNamespace` exception will be thrown. Here's how you might handle such exceptions:

```
try:
    print('user is {}'.format(info.user))
except errors.MissingInfoNamespace:
    # No 'access' namespace
    pass
```

If you prefer a *look before you leap* approach, you can use the `has_namespace()` method. Here's an example:

```
if info.has_namespace('access'):
    print('user is {}'.format(info.user))
```

See *Info* for details regarding info attributes.

4.4 Raw Info

The *Info* class is a wrapper around a simple data structure containing the *raw* info. You can access this raw info with the `info.raw` property.

Note: The following is probably only of interest if you intend to implement a filesystem yourself.

Raw info data consists of a dictionary that maps the namespace name on to a dictionary of information. Here's an example:

```
{
  'access': {
    'group': 'staff',
    'permissions': ['g_r', 'o_r', 'u_r', 'u_w'],
    'user': 'will'
  },
  'basic': {
    'is_dir': False,
    'name': 'README.txt'
  },
  'details': {
    'accessed': 1474979730.0,
    'created': 1462266356.0,
    'metadata_changed': 1473071537.0,
    'modified': 1462266356.0,
    'size': 79,
    'type': 2
  }
}
```

Raw resource information contains basic types only (strings, numbers, lists, dict, None). This makes the resource information simple to send over a network as it can be trivially serialized as JSON or other data format.

Because of this requirement, times are stored as *epoch times*. The Info object will convert these to datetime objects from the standard library. Additionally, the Info object will convert permissions from a list of strings in to a *Permissions* objects.

PyFilesystem can open a filesystem via an *FS URL*, which is similar to a URL you might enter in to a browser. FS URLs are useful if you want to specify a filesystem dynamically, such as in a conf file or from the command line.

5.1 Format

FS URLs are formatted in the following way:

```
<protocol>://<username>:<password>@<resource>
```

The components are as follows:

- `<protocol>` Identifies the type of filesystem to create. e.g. `osfs`, `ftp`.
- `<username>` Optional username.
- `<password>` Optional password.
- `<resource>` A *resource*, which may be a domain, path, or both.

Here are a few examples:

```
osfs://~/projects
osfs://c://system32
ftp://ftp.example.org/pub
mem://
ftp://will:daffodil@ftp.example.org/private
```

If `<type>` is not specified then it is assumed to be an *OSFS*, i.e. the following FS URLs are equivalent:

```
osfs://~/projects
~/projects
```

Note: The `username` and `passwords` fields may not contain a colon (`:`) or an `@` symbol. If you need these symbols they may be [percent encoded](#).

5.2 URL Parameters

FS URLs may also be appended with a `?` symbol followed by a url-encoded query string. For example:

```
myprotocol://example.org?key1=value1&key2
```

The query string would be decoded as `{"key1": "value1", "key2": ""}`.

Query strings are used to provide additional filesystem-specific information used when opening. See the filesystem documentation for information on what query string parameters are supported.

5.3 Opening FS URLs

To open a filesystem with a FS URL, you can use `open_fs()`, which may be imported and used as follows:

```
from fs import open_fs
projects_fs = open_fs('osfs://~/projects')
```

Walking a filesystem means recursively visiting a directory and any sub-directories. It is a fairly common requirement for copying, searching etc.

To walk a filesystem (or directory) you can construct a *Walker* object and use its methods to do the walking. Here's an example that prints the path to every Python file in your projects directory:

```
>>> from fs import open_fs
>>> from fs.walk import Walker
>>> home_fs = open_fs('~/projects')
>>> walker = Walker(filter=['*.py'])
>>> for path in walker.files(home_fs):
...     print(path)
```

Generally speaking, however, you will only need to construct a Walker object if you want to customize some behavior of the walking algorithm. This is because you can access the functionality of a Walker object via the `walk` attribute on FS objects. Here's an example:

```
>>> from fs import open_fs
>>> home_fs = open_fs('~/projects')
>>> for path in home_fs.walk.files(filter=['*.py']):
...     print(path)
```

Note that the `files` method above doesn't require a `fs` parameter. This is because the `walk` attribute is a property which returns a *BoundWalker* object, which associates the filesystem with a walker.

6.1 Walk Methods

If you call the `walk` attribute on a *BoundWalker* it will return an iterable of *Step* named tuples with three values; a path to the directory, a list of *Info* objects for directories, and a list of *Info* objects for the files. Here's an example:

```
for step in home_fs.walk(filter=['*.py']):
    print('In dir {}'.format(step.path))
```

(continues on next page)

(continued from previous page)

```
print('sub-directories: {!r}'.format(step.dirs))
print('files: {!r}'.format(step.files))
```

Note: Methods of *BoundWalker* invoke a corresponding method on a *Walker* object, with the *bound* filesystem.

The `walk` attribute may appear to be a method, but is in fact a callable object. It supports other convenient methods that supply different information from the walk. For instance, `files()`, which returns an iterable of file paths. Here's an example:

```
for path in home_fs.walk.files(filter=['*.py']):
    print('Python file: {}'.format(path))
```

The complement to `files` is `dirs()` which returns paths to just the directories (and ignoring the files). Here's an example:

```
for dir_path in home_fs.walk.dirs():
    print("{} contains sub-directory {}".format(home_fs, dir_path))
```

The `info()` method returns a generator of tuples containing a path and an *Info* object. You can use the `is_dir` attribute to know if the path refers to a directory or file. Here's an example:

```
for path, info in home_fs.walk.info():
    if info.is_dir:
        print("[dir] {}".format(path))
    else:
        print("[file] {}".format(path))
```

Finally, here's a nice example that counts the number of bytes of Python code in your home directory:

```
bytes_of_python = sum(
    info.size
    for info in home_fs.walk.info(namespaces=['details'])
    if not info.is_dir
)
```

6.2 Search Algorithms

There are two general algorithms for searching a directory tree. The first method is "breadth", which yields resources in the top of the directory tree first, before moving on to sub-directories. The second is "depth" which yields the most deeply nested resources, and works backwards to the top-most directory.

Generally speaking, you will only need the a *depth* search if you will be deleting resources as you walk through them. The default *breadth* search is a generally more efficient way of looking through a filesystem. You can specify which method you want with the `search` parameter on most *Walker* methods.

Globbering is the process of matching paths according to the rules used by the Unix shell.

Generally speaking, you can think of a glob pattern as a path containing one or more wildcard patterns, separated by forward slashes.

7.1 Matching Files and Directories

In a glob pattern, A `*` means match anything text in a filename. A `?` matches any single character. A `**` matches any number of subdirectories, making the glob *recursive*. If the glob pattern ends in a `/`, it will only match directory paths, otherwise it will match files and directories.

Note: A recursive glob requires that PyFilesystem scan a lot of files, and can potentially be slow for large (or network based) filesystems.

Here's a summary of glob patterns:

- * Matches all files in the current directory.
- * **.py** Matches all .py file in the current directory.
- * **.py?** Matches all .py files and .pyi, .pyc etc in the current directory.
- project/*.py** Matches all .py files in a directory called `project`.
- /**/*.py** Matches all .py files in any sub directory.
- **/*.py** Recursively matches all .py files.
- **/.git/** Recursively matches all the git directories.

7.2 Interface

PyFilesystem supports globbing via the `glob` attribute on every FS instance, which is an instance of *BoundGlobber*. Here's how you might use it to find all the Python files in your filesystem:

```
for match in my_fs.glob("**/*.py"):
    print(f"{match.path} is {match.info.size} bytes long")
```

Calling `.glob` with a pattern will return an iterator of *GlobMatch* named tuples for each matching file or directory. A glob match contains two attributes; `path` which is the full path in the filesystem, and `info` which is an *fs.info.Info* info object for the matched resource.

7.3 Batch Methods

In addition to iterating over the results, you can also call methods on the *Globber* which apply to every matched path.

For instance, here is how you can use `glob` to remove all `.pyc` files from a project directory:

```
>>> import fs
>>> fs.open_fs('~/projects/my_project').glob('**/*.pyc').remove()
29
```

8.1 App Filesystems

Manage filesystems in platform-specific application directories.

These classes abstract away the different requirements for user data across platforms, which vary in their conventions. They are all subclasses of *OSFS*.

class `fs.appfs.UserDataFS` (*appname*, *author=None*, *version=None*, *roaming=False*, *create=True*)
A filesystem for per-user application data.

May also be opened with `open_fs('userdata://appname:author:version')`.

Parameters

- **appname** (*str*) – The name of the application.
- **author** (*str*) – The name of the author (used on Windows).
- **version** (*str*) – Optional version string, if a unique location per version of the application is required.
- **roaming** (*bool*) – If `True`, use a *roaming* profile on Windows.
- **create** (*bool*) – If `True` (the default) the directory will be created if it does not exist.

class `fs.appfs.UserConfigFS` (*appname*, *author=None*, *version=None*, *roaming=False*, *create=True*)
A filesystem for per-user config data.

May also be opened with `open_fs('userconf://appname:author:version')`.

Parameters

- **appname** (*str*) – The name of the application.
- **author** (*str*) – The name of the author (used on Windows).
- **version** (*str*) – Optional version string, if a unique location per version of the application is required.

- **roaming** (*bool*) – If `True`, use a *roaming* profile on Windows.
- **create** (*bool*) – If `True` (the default) the directory will be created if it does not exist.

class `fs.appfs.SiteDataFS` (*appname*, *author=None*, *version=None*, *roaming=False*, *create=True*)
A filesystem for application site data.

May also be opened with `open_fs('sitedata://appname:author:version')`.

Parameters

- **appname** (*str*) – The name of the application.
- **author** (*str*) – The name of the author (used on Windows).
- **version** (*str*) – Optional version string, if a unique location per version of the application is required.
- **roaming** (*bool*) – If `True`, use a *roaming* profile on Windows.
- **create** (*bool*) – If `True` (the default) the directory will be created if it does not exist.

class `fs.appfs.SiteConfigFS` (*appname*, *author=None*, *version=None*, *roaming=False*, *create=True*)
A filesystem for application config data.

May also be opened with `open_fs('siteconf://appname:author:version')`.

Parameters

- **appname** (*str*) – The name of the application.
- **author** (*str*) – The name of the author (used on Windows).
- **version** (*str*) – Optional version string, if a unique location per version of the application is required.
- **roaming** (*bool*) – If `True`, use a *roaming* profile on Windows.
- **create** (*bool*) – If `True` (the default) the directory will be created if it does not exist.

class `fs.appfs.UserCacheFS` (*appname*, *author=None*, *version=None*, *roaming=False*, *create=True*)
A filesystem for per-user application cache data.

May also be opened with `open_fs('usercache://appname:author:version')`.

Parameters

- **appname** (*str*) – The name of the application.
- **author** (*str*) – The name of the author (used on Windows).
- **version** (*str*) – Optional version string, if a unique location per version of the application is required.
- **roaming** (*bool*) – If `True`, use a *roaming* profile on Windows.
- **create** (*bool*) – If `True` (the default) the directory will be created if it does not exist.

class `fs.appfs.UserLogFS` (*appname*, *author=None*, *version=None*, *roaming=False*, *create=True*)
A filesystem for per-user application log data.

May also be opened with `open_fs('userlog://appname:author:version')`.

Parameters

- **appname** (*str*) – The name of the application.

- **author** (*str*) – The name of the author (used on Windows).
- **version** (*str*) – Optional version string, if a unique location per version of the application is required.
- **roaming** (*bool*) – If `True`, use a *roaming* profile on Windows.
- **create** (*bool*) – If `True` (the default) the directory will be created if it does not exist.

8.2 FTP Filesystem

Manage filesystems on remote FTP servers.

```
class fs.ftpfs.FTPFS(host, user='anonymous', passwd="", acct="", timeout=10, port=21,
                    proxy=None)
```

A FTP (File Transport Protocol) Filesystem.

Parameters

- **host** (*str*) – A FTP host, e.g. 'ftp.mirror.nl'.
- **user** (*str*) – A username (default is 'anonymous').
- **passwd** (*str*) – Password for the server, or `None` for anon.
- **acct** (*str*) – FTP account.
- **timeout** (*int*) – Timeout for contacting server (in seconds, defaults to 10).
- **port** (*int*) – FTP port number (default 21).
- **proxy** (*str*, *optional*) – An FTP proxy, or `None` (default) for no proxy.

close()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call `close` multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a `FilesystemClosed` exception will be thrown.

create(*path*, *wipe*=False)

Create an empty file.

The default behavior is to create a new file if one doesn't already exist. If `wipe` is `True`, any existing file will be truncated.

Parameters

- **path** (*str*) – Path to a new file in the filesystem.

- **wipe** (*bool*) – If `True`, truncate any existing file to 0 bytes (defaults to `False`).

Returns `True` if a new file had to be created.

Return type `bool`

features

features of the remote FTP server.

Type `dict`

ftp

the underlying FTP client.

Type `FTP`

ftp_url

Get the FTP url this filesystem will open.

getinfo (*path, namespaces=None*)

Get information about a resource on a filesystem.

Parameters

- **path** (*str*) – A path to a resource on the filesystem.
- **namespaces** (*list, optional*) – Info namespaces to query (defaults to `[basic]`).

Returns resource information object.

Return type `Info`

For more information regarding resource information, see [Resource Info](#).

getmeta (*namespace='standard'*)

Get meta information regarding a filesystem.

Parameters **namespace** (*str*) – The meta namespace (defaults to `"standard"`).

Returns the meta information.

Return type `dict`

Meta information is associated with a *namespace* which may be specified with the `namespace` parameter. The default namespace, `"standard"`, contains common information regarding the filesystem's capabilities. Some filesystems may provide other namespaces which expose less common or implementation specific information. If a requested namespace is not supported by a filesystem, then an empty dictionary will be returned.

The `"standard"` namespace supports the following keys:

key	Description
<code>case_insensitive</code>	<code>True</code> if this filesystem is case insensitive.
<code>invalid_path_chars</code>	A string containing the characters that may not be used on this filesystem.
<code>max_path_length</code>	Maximum number of characters permitted in a path, or <code>None</code> for no limit.
<code>max_sys_path_length</code>	Maximum number of characters permitted in a sys path, or <code>None</code> for no limit.
<code>network</code>	<code>True</code> if this filesystem requires a network.
<code>read_only</code>	<code>True</code> if this filesystem is read only.
<code>supports_rename</code>	<code>True</code> if this filesystem supports an <code>os.rename</code> operation.

Most builtin filesystems will provide all these keys, and third- party filesystems should do so whenever possible, but a key may not be present if there is no way to know the value.

Note: Meta information is constant for the lifetime of the filesystem, and may be cached.

geturl (*path*, *purpose='download'*)
Get FTP url for resource.

listdir (*path*)
Get a list of the resource names in a directory.

This method will return a list of the resources in a directory. A *resource* is a file, directory, or one of the other types defined in *ResourceType*.

Parameters *path* (*str*) – A path to a directory on the filesystem

Returns list of names, relative to *path*.

Return type *list*

Raises

- *fs.errors.DirectoryExpected* – If *path* is not a directory.
- *fs.errors.ResourceNotFound* – If *path* does not exist.

makedir (*path*, *permissions=None*, *recreate=False*)
Make a directory.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (*Permissions*, *optional*) – a *Permissions* instance, or *None* to use default.
- **recreate** (*bool*) – Set to *True* to avoid raising an error if the directory already exists (defaults to *False*).

Returns a filesystem whose root is the new directory.

Return type *SubFS*

Raises

- *fs.errors.DirectoryExists* – If the path already exists.
- *fs.errors.ResourceNotFound* – If the path is not found.

openbin (*path*, *mode='r'*, *buffering=-1*, ***options*)
Open a binary file-like object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **mode** (*str*) – Mode to open file (must be a valid non-text mode, defaults to *r*). Since this method only opens binary files, the *b* in the mode string is implied.
- **buffering** (*int*) – Buffering policy (*-1* to use default buffering, *0* to disable buffering, or any positive integer to indicate a buffer size).
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type *io.IOBase*

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (x in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

readbytes (*path*)

Get the contents of a file as bytes.

Parameters `path` (*str*) – A path to a readable file on the filesystem.

Returns the file contents.

Return type `bytes`

Raises `fs.errors.ResourceNotFound` – if `path` does not exist.

remove (*path*)

Remove a file from the filesystem.

Parameters `path` (*str*) – Path of the file to remove.

Raises

- `fs.errors.FileExpected` – If the path is a directory.
- `fs.errors.ResourceNotFound` – If the path does not exist.

removedir (*path*)

Remove a directory from the filesystem.

Parameters `path` (*str*) – Path of the directory to remove.

Raises

- `fs.errors.DirectoryNotEmpty` – If the directory is not empty (see *removetree* for a way to remove the directory contents.).
- `fs.errors.DirectoryExpected` – If the path does not refer to a directory.
- `fs.errors.ResourceNotFound` – If no resource exists at the given path.
- `fs.errors.RemoveRootError` – If an attempt is made to remove the root directory (i.e. '/')

scandir (*path*, *namespaces=None*, *page=None*)

Get an iterator of resource info.

Parameters

- `path` (*str*) – A path to a directory on the filesystem.
- `namespaces` (*list*, *optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'].
- `page` (*tuple*, *optional*) – May be a tuple of (<start>, <end>) indexes to return an iterator of a subset of the resource info, or `None` to iterate over the entire directory. Paging a directory scan may be necessary for very large directories.

Returns an iterator of `Info` objects.

Return type `Iterator`

Raises

- `fs.errors.DirectoryExpected` – If `path` is not a directory.
- `fs.errors.ResourceNotFound` – If `path` does not exist.

setinfo (*path*, *info*)

Set info on a resource.

This method is the complement to `getinfo` and is used to set info values on a resource.

Parameters

- **path** (*str*) – Path to a resource on the filesystem.
- **info** (*dict*) – Dictionary of resource info.

Raises `fs.errors.ResourceNotFound` – If `path` does not exist on the filesystem

The `info` dict should be in the same format as the raw info returned by `getinfo(file).raw`.

Example

```
>>> details_info = {"details": {
...     "modified": time.time()
... }}
>>> my_fs.setinfo('file.txt', details_info)
```

supports_mlst

whether the server supports MLST feature.

Type `bool`

upload (*path*, *file*, *chunk_size=None*, ***options*)

Set a file to the contents of a binary file object.

This method copies bytes from an open binary file to a file on the filesystem. If the destination exists, it will first be truncated.

Parameters

- **path** (*str*) – A path on the filesystem.
- **file** (*io.IOBase*) – a file object open for reading in binary mode.
- **chunk_size** (*int*, *optional*) – Number of bytes to read at a time, if a simple copy is used, or `None` to use sensible default.
- ****options** – Implementation specific options required to open the source file.

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('~/.movies/starwars.mov', 'rb') as read_file:
...     my_fs.upload('starwars.mov', read_file)
```

writebytes (*path*, *contents*)

Copy binary data to a file.

Parameters

- **path** (*str*) – Destination path on the filesystem.

- **contents** (*bytes*) – Data to be written.

Raises `TypeError` – if contents is not bytes.

8.3 Memory Filesystem

Manage a volatile in-memory filesystem.

class `fs.memoryfs.MemoryFS`

A filesystem that stored in memory.

Memory filesystems are useful for caches, temporary data stores, unit testing, etc. Since all the data is in memory, they are very fast, but non-permanent. The `MemoryFS` constructor takes no arguments.

Example

```
>>> mem_fs = MemoryFS()
```

Or via an FS URL:

```
>>> import fs
>>> mem_fs = fs.open_fs('mem://')
```

close ()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call close multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a `FilesystemClosed` exception will be thrown.

getinfo (*path*, *namespaces=None*)

Get information about a resource on a filesystem.

Parameters

- **path** (*str*) – A path to a resource on the filesystem.
- **namespaces** (*list*, *optional*) – Info namespaces to query (defaults to `[basic]`).

Returns resource information object.

Return type `Info`

For more information regarding resource information, see [Resource Info](#).

listdir (*path*)

Get a list of the resource names in a directory.

This method will return a list of the resources in a directory. A *resource* is a file, directory, or one of the other types defined in *ResourceType*.

Parameters *path* (*str*) – A path to a directory on the filesystem

Returns list of names, relative to *path*.

Return type *list*

Raises

- *fs.errors.DirectoryExpected* – If *path* is not a directory.
- *fs.errors.ResourceNotFound* – If *path* does not exist.

makedir (*path*, *permissions=None*, *recreate=False*)

Make a directory.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (*Permissions*, *optional*) – a *Permissions* instance, or *None* to use default.
- **recreate** (*bool*) – Set to *True* to avoid raising an error if the directory already exists (defaults to *False*).

Returns a filesystem whose root is the new directory.

Return type *SubFS*

Raises

- *fs.errors.DirectoryExists* – If the path already exists.
- *fs.errors.ResourceNotFound* – If the path is not found.

openbin (*path*, *mode='r'*, *buffering=-1*, ***options*)

Open a binary file-like object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **mode** (*str*) – Mode to open file (must be a valid non-text mode, defaults to *r*). Since this method only opens binary files, the *b* in the mode string is implied.
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, or any positive integer to indicate a buffer size).
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type *io.IOBase*

Raises

- *fs.errors.FileExpected* – If the path is not a file.
- *fs.errors.FileExists* – If the file exists, and *exclusive mode* is specified (*x* in the mode).

- `fs.errors.ResourceNotFound` – If the path does not exist.

remove (*path*)

Remove a file from the filesystem.

Parameters `path` (*str*) – Path of the file to remove.

Raises

- `fs.errors.FileExpected` – If the path is a directory.
- `fs.errors.ResourceNotFound` – If the path does not exist.

removedir (*path*)

Remove a directory from the filesystem.

Parameters `path` (*str*) – Path of the directory to remove.

Raises

- `fs.errors.DirectoryNotEmpty` – If the directory is not empty (see `removetree` for a way to remove the directory contents.).
- `fs.errors.DirectoryExpected` – If the path does not refer to a directory.
- `fs.errors.ResourceNotFound` – If no resource exists at the given path.
- `fs.errors.RemoveRootError` – If an attempt is made to remove the root directory (i.e. '/')

setinfo (*path*, *info*)

Set info on a resource.

This method is the complement to `getinfo` and is used to set info values on a resource.

Parameters

- `path` (*str*) – Path to a resource on the filesystem.
- `info` (*dict*) – Dictionary of resource info.

Raises `fs.errors.ResourceNotFound` – If `path` does not exist on the filesystem

The `info` dict should be in the same format as the raw info returned by `getinfo(file).raw`.

Example

```
>>> details_info = {"details": {
...     "modified": time.time()
... }}
>>> my_fs.setinfo('file.txt', details_info)
```

8.4 Mount Filesystem

A Mount FS is a *virtual* filesystem which can seamlessly map sub-directories on to other filesystems.

For example, lets say we have two filesystems containing config files and resources respectively:


```
[config_fs]
|-- config.cfg
`-- defaults.cfg

[resources_fs]
|-- images
|   |-- logo.jpg
|   `-- photo.jpg
`-- data.dat
```

We can combine these filesystems in to a single filesystem with the following code:

```
from fs.mountfs import MountFS
combined_fs = MountFS()
combined_fs.mount('config', config_fs)
combined_fs.mount('resources', resources_fs)
```

This will create a filesystem where paths under `config/` map to `config_fs`, and paths under `resources/` map to `resources_fs`:

```
[combined_fs]
|-- config
|   |-- config.cfg
|   `-- defaults.cfg
`-- resources
    |-- images
    |   |-- logo.jpg
    |   `-- photo.jpg
    `-- data.dat
```

Now both filesystems may be accessed with the same path structure:

```
print(combined_fs.gettext('/config/defaults.cfg'))
read_jpg(combined_fs.open('/resources/images/logo.jpg', 'rb'))
```

class `fs.mountfs.MountFS` (*auto_close=True*)

A virtual filesystem that maps directories on to other file-systems.

Parameters `auto_close` (*bool*) – If `True` (the default), the child filesystems will be closed when `MountFS` is closed.

close ()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call `close` multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a `FilesystemClosed` exception will be thrown.

desc (*path*)

Return a short descriptive text regarding a path.

Parameters `path` (*str*) – A path to a resource on the filesystem.

Returns a short description of the path.

Return type `str`

download (*path*, *file*, *chunk_size=None*, ***options*)

Copies a file from the filesystem to a file-like object.

This may be more efficient than opening and copying files manually if the filesystem supplies an optimized method.

Parameters

- **path** (*str*) – Path to a resource.
- **file** (*file-like*) – A file-like object open for writing in binary mode.
- **chunk_size** (*int*, *optional*) – Number of bytes to read at a time, if a simple copy is used, or `None` to use sensible default.
- ****options** – Implementation specific options required to open the source file.

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('starwars.mov', 'wb') as write_file:
...     my_fs.download('/movies/starwars.mov', write_file)
```

getinfo (*path*, *namespaces=None*)

Get information about a resource on a filesystem.

Parameters

- **path** (*str*) – A path to a resource on the filesystem.
- **namespaces** (*list*, *optional*) – Info namespaces to query (defaults to `[basic]`).

Returns resource information object.

Return type `Info`

For more information regarding resource information, see [Resource Info](#).

getsize (*path*)

Get the size (in bytes) of a resource.

Parameters `path` (*str*) – A path to a resource.

Returns the *size* of the resource.

Return type `int`

The *size* of a file is the total number of readable bytes, which may not reflect the exact number of bytes of reserved disk space (or other storage medium).

The size of a directory is the number of bytes of overhead use to store the directory entry.

getsyspath (*path*)

Get the *system path* of a resource.

Parameters **path** (*str*) – A path on the filesystem.

Returns the *system path* of the resource, if any.

Return type *str*

Raises *fs.errors.NoSysPath* – If there is no corresponding system path.

A system path is one recognized by the OS, that may be used outside of PyFilesystem (in an application or a shell for example). This method will get the corresponding system path that would be referenced by *path*.

Not all filesystems have associated system paths. Network and memory based filesystems, for example, may not physically store data anywhere the OS knows about. It is also possible for some paths to have a system path, whereas others don't.

This method will always return a *str* on Py3.* and *unicode* on Py2.7. See *getospath* if you need to encode the path as bytes.

If *path* doesn't have a system path, a *NoSysPath* exception will be thrown.

Note: A filesystem may return a system path even if no resource is referenced by that path – as long as it can be certain what that system path would be.

gettype (*path*)

Get the type of a resource.

Parameters **path** (*str*) – A path on the filesystem.

Returns the type of the resource.

Return type *ResourceType*

A type of a resource is an integer that identifies the what the resource references. The standard type integers may be one of the values in the *ResourceType* enumerations.

The most common resource types, supported by virtually all filesystems are *directory* (1) and *file* (2), but the following types are also possible:

ResourceType	value
unknown	0
directory	1
file	2
character	3
block_special_file	4
fifo	5
socket	6
symlink	7

Standard resource types are positive integers, negative values are reserved for implementation specific resource types.

geturl (*path*, *purpose='download'*)

Get the URL to a given resource.

Parameters

- **path** (*str*) – A path on the filesystem
- **purpose** (*str*) – A short string that indicates which URL to retrieve for the given path (if there is more than one). The default is 'download', which should return a URL that serves the file. Other filesystems may support other values for purpose.

Returns a URL.

Return type *str*

Raises *fs.errors.NoURL* – If the path does not map to a URL.

hasurl (*path*, *purpose='download'*)

Check if a path has a corresponding URL.

Parameters

- **path** (*str*) – A path on the filesystem.
- **purpose** (*str*) – A purpose parameter, as given in *geturl*.

Returns *True* if an URL for the given purpose exists.

Return type *bool*

isdir (*path*)

Check if a path maps to an existing directory.

Parameters **path** (*str*) – A path on the filesystem.

Returns *True* if *path* maps to a directory.

Return type *bool*

isfile (*path*)

Check if a path maps to an existing file.

Parameters **path** (*str*) – A path on the filesystem.

Returns *True* if *path* maps to a file.

Return type *bool*

listdir (*path*)

Get a list of the resource names in a directory.

This method will return a list of the resources in a directory. A *resource* is a file, directory, or one of the other types defined in *ResourceType*.

Parameters **path** (*str*) – A path to a directory on the filesystem

Returns list of names, relative to *path*.

Return type *list*

Raises

- *fs.errors.DirectoryExpected* – If *path* is not a directory.
- *fs.errors.ResourceNotFound* – If *path* does not exist.

makedir (*path*, *permissions=None*, *recreate=False*)

Make a directory.

Parameters

- **path** (*str*) – Path to directory from root.

- **permissions** (*Permissions*, *optional*) – a *Permissions* instance, or *None* to use default.
- **recreate** (*bool*) – Set to *True* to avoid raising an error if the directory already exists (defaults to *False*).

Returns a filesystem whose root is the new directory.

Return type *SubFS*

Raises

- *fs.errors.DirectoryExists* – If the path already exists.
- *fs.errors.ResourceNotFound* – If the path is not found.

mount (*path*, *fs*)

Mounts a host FS object on a given path.

Parameters

- **path** (*str*) – A path within the MountFS.
- **fs** (*FS or str*) – A filesystem (instance or URL) to mount.

open (*path*, *mode='r'*, *buffering=-1*, *encoding=None*, *errors=None*, *newline=""*, ***options*)

Open a file.

Parameters

- **path** (*str*) – A path to a file on the filesystem.
- **mode** (*str*) – Mode to open the file object with (defaults to *r*).
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, 1 to select line buffering, of any positive integer to indicate a buffer size).
- **encoding** (*str*) – Encoding for text files (defaults to *utf-8*)
- **errors** (*str*, *optional*) – What to do with unicode decode errors (see *codecs* module for more information).
- **newline** (*str*) – Newline parameter.
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type *io.IOBase*

Raises

- *fs.errors.FileExpected* – If the path is not a file.
- *fs.errors.FileExists* – If the file exists, and *exclusive mode* is specified (*x* in the mode).
- *fs.errors.ResourceNotFound* – If the path does not exist.

openbin (*path*, *mode='r'*, *buffering=-1*, ***kwargs*)

Open a binary file-like object.

Parameters

- **path** (*str*) – A path on the filesystem.

- **mode** (*str*) – Mode to open file (must be a valid non-text mode, defaults to *r*). Since this method only opens binary files, the *b* in the mode string is implied.
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, or any positive integer to indicate a buffer size).
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (*x* in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

readbytes (*path*)

Get the contents of a file as bytes.

Parameters **path** (*str*) – A path to a readable file on the filesystem.

Returns the file contents.

Return type `bytes`

Raises `fs.errors.ResourceNotFound` – if *path* does not exist.

readtext (*path, encoding=None, errors=None, newline=""*)

Get the contents of a file as a string.

Parameters

- **path** (*str*) – A path to a readable file on the filesystem.
- **encoding** (*str, optional*) – Encoding to use when reading contents in text mode (defaults to `None`, reading in binary mode).
- **errors** (*str, optional*) – Unicode errors parameter.
- **newline** (*str*) – Newlines parameter.

Returns file contents.

Return type `str`

Raises `fs.errors.ResourceNotFound` – If *path* does not exist.

remove (*path*)

Remove a file from the filesystem.

Parameters **path** (*str*) – Path of the file to remove.

Raises

- `fs.errors.FileExpected` – If the path is a directory.
- `fs.errors.ResourceNotFound` – If the path does not exist.

removedir (*path*)

Remove a directory from the filesystem.

Parameters **path** (*str*) – Path of the directory to remove.

Raises

- `fs.errors.DirectoryNotEmpty` – If the directory is not empty (see `removetree` for a way to remove the directory contents.).
- `fs.errors.DirectoryExpected` – If the path does not refer to a directory.
- `fs.errors.ResourceNotFound` – If no resource exists at the given path.
- `fs.errors.RemoveRootError` – If an attempt is made to remove the root directory (i.e. '/')

scandir (*path*, *namespaces=None*, *page=None*)

Get an iterator of resource info.

Parameters

- **path** (*str*) – A path to a directory on the filesystem.
- **namespaces** (*list*, *optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'].
- **page** (*tuple*, *optional*) – May be a tuple of (<start>, <end>) indexes to return an iterator of a subset of the resource info, or `None` to iterate over the entire directory. Paging a directory scan may be necessary for very large directories.

Returns an iterator of `Info` objects.

Return type `Iterator`

Raises

- `fs.errors.DirectoryExpected` – If path is not a directory.
- `fs.errors.ResourceNotFound` – If path does not exist.

setinfo (*path*, *info*)

Set info on a resource.

This method is the complement to `getinfo` and is used to set info values on a resource.

Parameters

- **path** (*str*) – Path to a resource on the filesystem.
- **info** (*dict*) – Dictionary of resource info.

Raises `fs.errors.ResourceNotFound` – If path does not exist on the filesystem

The info dict should be in the same format as the raw info returned by `getinfo(file).raw`.

Example

```
>>> details_info = {"details": {
...     "modified": time.time()
... }}
>>> my_fs.setinfo('file.txt', details_info)
```

upload (*path*, *file*, *chunk_size=None*, ***options*)

Set a file to the contents of a binary file object.

This method copies bytes from an open binary file to a file on the filesystem. If the destination exists, it will first be truncated.

Parameters

- **path** (*str*) – A path on the filesystem.
- **file** (*io.IOBase*) – a file object open for reading in binary mode.
- **chunk_size** (*int, optional*) – Number of bytes to read at a time, if a simple copy is used, or *None* to use sensible default.
- ****options** – Implementation specific options required to open the source file.

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('~/.movies/starwars.mov', 'rb') as read_file:
...     my_fs.upload('starwars.mov', read_file)
```

validatepath (*path*)

Check if a path is valid, returning a normalized absolute path.

Many filesystems have restrictions on the format of paths they support. This method will check that `path` is valid on the underlying storage mechanism and throw a *InvalidPath* exception if it is not.

Parameters `path` (*str*) – A path.

Returns A normalized, absolute path.

Return type `str`

Raises

- *fs.errors.InvalidCharsInPath* – If the path contains invalid characters.
- *fs.errors.InvalidPath* – If the path is invalid.
- *fs.errors.FileSystemClosed* – if the filesystem is closed.

writebytes (*path, contents*)

Copy binary data to a file.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*bytes*) – Data to be written.

Raises `TypeError` – if `contents` is not bytes.

writetext (*path, contents, encoding='utf-8', errors=None, newline=""*)

Create or replace a file with text.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*str*) – Text to be written.
- **encoding** (*str, optional*) – Encoding of destination file (defaults to 'utf-8').
- **errors** (*str, optional*) – How encoding errors should be treated (same as `io.open`).
- **newline** (*str*) – Newline parameter (same as `io.open`).

Raises `TypeError` – if `contents` is not a unicode string.

exception `fs.mountfs.MountError`

Bases: `Exception`

Thrown when mounts conflict.

8.5 Multi Filesystem

A MultiFS is a filesystem composed of a sequence of other filesystems, where the directory structure of each overlays the previous filesystem in the sequence.

One use for such a filesystem would be to selectively override a set of files, to customize behavior. For example, to create a filesystem that could be used to *theme* a web application. We start with the following directories:

```

`-- templates
   |-- snippets
   |   |-- panel.html
   |   |-- index.html
   |   |-- profile.html
   |-- base.html

`-- theme
   |-- snippets
   |   |-- widget.html
   |   |-- extra.html
   |-- index.html
   |-- theme.html

```

And we want to create a single filesystem that will load a file from `templates/` only if it isn't found in `theme/`. Here's how we could do that:

```

from fs.osfs import OSFS
from fs.multifs import MultiFS

theme_fs = MultiFS()
theme_fs.add_fs('templates', OSFS('templates'))
theme_fs.add_fs('theme', OSFS('theme'))

```

Now we have a `theme_fs` filesystem that presents a single view of both directories:

```

|-- snippets
|   |-- panel.html
|   |-- widget.html
|   |-- extra.html
|-- index.html
|-- profile.html
|-- base.html
|-- theme.html

```

class `fs.multifs.MultiFS` (*auto_close=True*)

A filesystem that delegates to a sequence of other filesystems.

Operations on the MultiFS will try each 'child' filesystem in order, until it succeeds. In effect, creating a filesystem that combines the files and dirs of its children.

add_fs (*name, fs, write=False, priority=0*)

Add a filesystem to the MultiFS.

Parameters

- **name** (*str*) – A unique name to refer to the filesystem being added.
- **fs** (*FS or str*) – The filesystem (instance or URL) to add.
- **write** (*bool*) – If this value is True, then the *fs* will be used as the writeable FS (defaults to False).
- **priority** (*int*) – An integer that denotes the priority of the filesystem being added. Filesystems will be searched in descending priority order and then by the reverse order they were added. So by default, the most recently added filesystem will be looked at first.

close()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call `close` multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a `FilesystemClosed` exception will be thrown.

download (*path, file, chunk_size=None, **options*)

Copies a file from the filesystem to a file-like object.

This may be more efficient than opening and copying files manually if the filesystem supplies an optimized method.

Parameters

- **path** (*str*) – Path to a resource.
- **file** (*file-like*) – A file-like object open for writing in binary mode.
- **chunk_size** (*int, optional*) – Number of bytes to read at a time, if a simple copy is used, or `None` to use sensible default.
- ****options** – Implementation specific options required to open the source file.

Note that the file object *file* will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('starwars.mov', 'wb') as write_file:
...     my_fs.download('/movies/starwars.mov', write_file)
```

get_fs (*name*)

Get a filesystem from its name.

Parameters **name** (*str*) – The name of a filesystem previously added.

Returns the filesystem added as *name* previously.

Return type *FS*

Raises `KeyError` – If no filesystem with given name could be found.

getinfo (*path*, *namespaces=None*)

Get information about a resource on a filesystem.

Parameters

- **path** (*str*) – A path to a resource on the filesystem.
- **namespaces** (*list*, *optional*) – Info namespaces to query (defaults to [*basic*]).

Returns resource information object.

Return type *Info*

For more information regarding resource information, see *Resource Info*.

getsize (*path*)

Get the size (in bytes) of a resource.

Parameters **path** (*str*) – A path to a resource.

Returns the *size* of the resource.

Return type `int`

The *size* of a file is the total number of readable bytes, which may not reflect the exact number of bytes of reserved disk space (or other storage medium).

The size of a directory is the number of bytes of overhead use to store the directory entry.

getsyspath (*path*)

Get the *system path* of a resource.

Parameters **path** (*str*) – A path on the filesystem.

Returns the *system path* of the resource, if any.

Return type `str`

Raises `fs.errors.NoSysPath` – If there is no corresponding system path.

A system path is one recognized by the OS, that may be used outside of PyFilesystem (in an application or a shell for example). This method will get the corresponding system path that would be referenced by *path*.

Not all filesystems have associated system paths. Network and memory based filesystems, for example, may not physically store data anywhere the OS knows about. It is also possible for some paths to have a system path, whereas others don't.

This method will always return a `str` on Py3.* and `unicode` on Py2.7. See `getospath` if you need to encode the path as bytes.

If *path* doesn't have a system path, a `NoSysPath` exception will be thrown.

Note: A filesystem may return a system path even if no resource is referenced by that path – as long as it can be certain what that system path would be.

gettype (*path*)

Get the type of a resource.

Parameters **path** (*str*) – A path on the filesystem.

Returns the type of the resource.

Return type *ResourceType*

A type of a resource is an integer that identifies the what the resource references. The standard type integers may be one of the values in the *ResourceType* enumerations.

The most common resource types, supported by virtually all filesystems are `directory` (1) and `file` (2), but the following types are also possible:

ResourceType	value
unknown	0
directory	1
file	2
character	3
block_special_file	4
fifo	5
socket	6
symlink	7

Standard resource types are positive integers, negative values are reserved for implementation specific resource types.

geturl (*path*, *purpose*='download')

Get the URL to a given resource.

Parameters

- **path** (*str*) – A path on the filesystem
- **purpose** (*str*) – A short string that indicates which URL to retrieve for the given path (if there is more than one). The default is 'download', which should return a URL that serves the file. Other filesystems may support other values for *purpose*.

Returns a URL.

Return type *str*

Raises *fs.errors.NoURL* – If the path does not map to a URL.

hassyspath (*path*)

Check if a path maps to a system path.

Parameters **path** (*str*) – A path on the filesystem.

Returns `True` if the resource at *path* has a *syspath*.

Return type *bool*

hasurl (*path*, *purpose*='download')

Check if a path has a corresponding URL.

Parameters

- **path** (*str*) – A path on the filesystem.
- **purpose** (*str*) – A purpose parameter, as given in *geturl*.

Returns `True` if an URL for the given purpose exists.

Return type *bool*

isdir (*path*)

Check if a path maps to an existing directory.

Parameters `path` (*str*) – A path on the filesystem.

Returns `True` if `path` maps to a directory.

Return type `bool`

isfile (*path*)

Check if a path maps to an existing file.

Parameters `path` (*str*) – A path on the filesystem.

Returns `True` if `path` maps to a file.

Return type `bool`

iterate_fs ()

Get iterator that returns (name, fs) in priority order.

listdir (*path*)

Get a list of the resource names in a directory.

This method will return a list of the resources in a directory. A *resource* is a file, directory, or one of the other types defined in *ResourceType*.

Parameters `path` (*str*) – A path to a directory on the filesystem

Returns list of names, relative to `path`.

Return type `list`

Raises

- `fs.errors.DirectoryExpected` – If `path` is not a directory.
- `fs.errors.ResourceNotFound` – If `path` does not exist.

makedir (*path*, *permissions=None*, *recreate=False*)

Make a directory.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (`Permissions`, *optional*) – a `Permissions` instance, or `None` to use default.
- **recreate** (*bool*) – Set to `True` to avoid raising an error if the directory already exists (defaults to `False`).

Returns a filesystem whose root is the new directory.

Return type *SubFS*

Raises

- `fs.errors.DirectoryExists` – If the path already exists.
- `fs.errors.ResourceNotFound` – If the path is not found.

makedirs (*path*, *permissions=None*, *recreate=False*)

Make a directory, and any missing intermediate directories.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (`Permissions`, *optional*) – Initial permissions, or `None` to use defaults.

- **recreate** (*bool*) – If `False` (the default), attempting to create an existing directory will raise an error. Set to `True` to ignore existing directories.

Returns A sub-directory filesystem.

Return type *SubFS*

Raises

- *fs.errors.DirectoryExists* – if the path is already a directory, and `recreate` is `False`.
- *fs.errors.DirectoryExpected* – if one of the ancestors in the path is not a directory.

open (*path*, *mode*='r', *buffering*=-1, *encoding*=None, *errors*=None, *newline*="", ***kwargs*)

Open a file.

Parameters

- **path** (*str*) – A path to a file on the filesystem.
- **mode** (*str*) – Mode to open the file object with (defaults to `r`).
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, 1 to select line buffering, of any positive integer to indicate a buffer size).
- **encoding** (*str*) – Encoding for text files (defaults to `utf-8`)
- **errors** (*str*, *optional*) – What to do with unicode decode errors (see `codecs` module for more information).
- **newline** (*str*) – Newline parameter.
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type *io.IOBase*

Raises

- *fs.errors.FileExpected* – If the path is not a file.
- *fs.errors.FileExists* – If the file exists, and *exclusive mode* is specified (`x` in the mode).
- *fs.errors.ResourceNotFound* – If the path does not exist.

openbin (*path*, *mode*='r', *buffering*=-1, ***options*)

Open a binary file-like object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **mode** (*str*) – Mode to open file (must be a valid non-text mode, defaults to `r`). Since this method only opens binary files, the `b` in the mode string is implied.
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, or any positive integer to indicate a buffer size).
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (x in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

readbytes (*path*)

Get the contents of a file as bytes.

Parameters `path` (*str*) – A path to a readable file on the filesystem.

Returns the file contents.

Return type `bytes`

Raises `fs.errors.ResourceNotFound` – if `path` does not exist.

readtext (*path*, *encoding=None*, *errors=None*, *newline=""*)

Get the contents of a file as a string.

Parameters

- `path` (*str*) – A path to a readable file on the filesystem.
- `encoding` (*str*, *optional*) – Encoding to use when reading contents in text mode (defaults to `None`, reading in binary mode).
- `errors` (*str*, *optional*) – Unicode errors parameter.
- `newline` (*str*) – Newlines parameter.

Returns file contents.

Return type `str`

Raises `fs.errors.ResourceNotFound` – If `path` does not exist.

remove (*path*)

Remove a file from the filesystem.

Parameters `path` (*str*) – Path of the file to remove.

Raises

- `fs.errors.FileExpected` – If the path is a directory.
- `fs.errors.ResourceNotFound` – If the path does not exist.

removedir (*path*)

Remove a directory from the filesystem.

Parameters `path` (*str*) – Path of the directory to remove.

Raises

- `fs.errors.DirectoryNotEmpty` – If the directory is not empty (see `removetree` for a way to remove the directory contents.).
- `fs.errors.DirectoryExpected` – If the path does not refer to a directory.
- `fs.errors.ResourceNotFound` – If no resource exists at the given path.
- `fs.errors.RemoveRootError` – If an attempt is made to remove the root directory (i.e. '/')

scandir (*path*, *namespaces=None*, *page=None*)

Get an iterator of resource info.

Parameters

- **path** (*str*) – A path to a directory on the filesystem.
- **namespaces** (*list*, *optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'].
- **page** (*tuple*, *optional*) – May be a tuple of (<start>, <end>) indexes to return an iterator of a subset of the resource info, or *None* to iterate over the entire directory. Paging a directory scan may be necessary for very large directories.

Returns an iterator of *Info* objects.

Return type *Iterator*

Raises

- *fs.errors.DirectoryExpected* – If *path* is not a directory.
- *fs.errors.ResourceNotFound* – If *path* does not exist.

setinfo (*path*, *info*)

Set info on a resource.

This method is the complement to *getinfo* and is used to set info values on a resource.

Parameters

- **path** (*str*) – Path to a resource on the filesystem.
- **info** (*dict*) – Dictionary of resource info.

Raises *fs.errors.ResourceNotFound* – If *path* does not exist on the filesystem

The *info* dict should be in the same format as the raw info returned by *getinfo(file).raw*.

Example

```
>>> details_info = {"details": {
...     "modified": time.time()
... }}
>>> my_fs.setinfo('file.txt', details_info)
```

upload (*path*, *file*, *chunk_size=None*, ***options*)

Set a file to the contents of a binary file object.

This method copies bytes from an open binary file to a file on the filesystem. If the destination exists, it will first be truncated.

Parameters

- **path** (*str*) – A path on the filesystem.
- **file** (*io.IOBase*) – a file object open for reading in binary mode.
- **chunk_size** (*int*, *optional*) – Number of bytes to read at a time, if a simple copy is used, or *None* to use sensible default.
- ****options** – Implementation specific options required to open the source file.

Note that the file object *file* will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('~/.movies/starwars.mov', 'rb') as read_file:
...     my_fs.upload('starwars.mov', read_file)
```

validatepath (*path*)

Check if a path is valid, returning a normalized absolute path.

Many filesystems have restrictions on the format of paths they support. This method will check that path is valid on the underlying storage mechanism and throw a *InvalidPath* exception if it is not.

Parameters *path* (*str*) – A path.

Returns A normalized, absolute path.

Return type *str*

Raises

- *fs.errors.InvalidCharsInPath* – If the path contains invalid characters.
- *fs.errors.InvalidPath* – If the path is invalid.
- *fs.errors.FilesystemClosed* – if the filesystem is closed.

which (*path*, *mode*='r')

Get a tuple of (name, fs) that the given path would map to.

Parameters

- **path** (*str*) – A path on the filesystem.
- **mode** (*str*) – An *io.open* mode.

writebytes (*path*, *contents*)

Copy binary data to a file.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*bytes*) – Data to be written.

Raises *TypeError* – if contents is not bytes.

writetext (*path*, *contents*, *encoding*='utf-8', *errors*=None, *newline*='')

Create or replace a file with text.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*str*) – Text to be written.
- **encoding** (*str*, *optional*) – Encoding of destination file (defaults to 'utf-8').
- **errors** (*str*, *optional*) – How encoding errors should be treated (same as *io.open*).
- **newline** (*str*) – Newline parameter (same as *io.open*).

Raises *TypeError* – if contents is not a unicode string.

8.6 OS Filesystem

Manage the filesystem provided by your OS.

In essence, an *OSFS* is a thin layer over the `io` and `os` modules of the Python standard library.

class `fs.osfs.OSFS` (*root_path*, *create=False*, *create_mode=511*, *expand_vars=True*)

Create an OSFS.

Parameters

- **root_path** (*str* or *PathLike*) – An OS path or path-like object to the location on your HD you wish to manage.
- **create** (*bool*) – Set to `True` to create the root directory if it does not already exist, otherwise the directory should exist prior to creating the OSFS instance (defaults to `False`).
- **create_mode** (*int*) – The permissions that will be used to create the directory if `create` is `True` and the path doesn't exist, defaults to `0o777`.
- **expand_vars** (*bool*) – If `True` (the default) environment variables of the form `$name` or `${name}` will be expanded.

Raises `fs.errors.CreateFailed` – If `root_path` does not exist, or could not be created.

Examples

```
>>> current_directory_fs = OSFS('.')
>>> home_fs = OSFS('~/')
>>> windows_system32_fs = OSFS('c://system32')
```

copy (*src_path*, *dst_path*, *overwrite=False*)

Copy file contents from `src_path` to `dst_path`.

Parameters

- **src_path** (*str*) – Path of source file.
- **dst_path** (*str*) – Path to destination file.
- **overwrite** (*bool*) – If `True`, overwrite the destination file if it exists (defaults to `False`).

Raises

- `fs.errors.DestinationExists` – If `dst_path` exists, and `overwrite` is `False`.
- `fs.errors.ResourceNotFound` – If a parent directory of `dst_path` does not exist.

getinfo (*path*, *namespaces=None*)

Get information about a resource on a filesystem.

Parameters

- **path** (*str*) – A path to a resource on the filesystem.
- **namespaces** (*list*, *optional*) – Info namespaces to query (defaults to `[basic]`).

Returns resource information object.

Return type *Info*

For more information regarding resource information, see *Resource Info*.

getsyspath (*path*)

Get the *system path* of a resource.

Parameters *path* (*str*) – A path on the filesystem.

Returns the *system path* of the resource, if any.

Return type *str*

Raises *fs.errors.NoSysPath* – If there is no corresponding system path.

A system path is one recognized by the OS, that may be used outside of PyFilesystem (in an application or a shell for example). This method will get the corresponding system path that would be referenced by *path*.

Not all filesystems have associated system paths. Network and memory based filesystems, for example, may not physically store data anywhere the OS knows about. It is also possible for some paths to have a system path, whereas others don't.

This method will always return a *str* on Py3.* and *unicode* on Py2.7. See *getospath* if you need to encode the path as bytes.

If *path* doesn't have a system path, a *NoSysPath* exception will be thrown.

Note: A filesystem may return a system path even if no resource is referenced by that path – as long as it can be certain what that system path would be.

gettype (*path*)

Get the type of a resource.

Parameters *path* (*str*) – A path on the filesystem.

Returns the type of the resource.

Return type *ResourceType*

A type of a resource is an integer that identifies the what the resource references. The standard type integers may be one of the values in the *ResourceType* enumerations.

The most common resource types, supported by virtually all filesystems are *directory* (1) and *file* (2), but the following types are also possible:

ResourceType	value
unknown	0
directory	1
file	2
character	3
block_special_file	4
fifo	5
socket	6
symlink	7

Standard resource types are positive integers, negative values are reserved for implementation specific resource types.

geturl (*path*, *purpose='download'*)

Get the URL to a given resource.

Parameters

- **path** (*str*) – A path on the filesystem
- **purpose** (*str*) – A short string that indicates which URL to retrieve for the given path (if there is more than one). The default is 'download', which should return a URL that serves the file. Other filesystems may support other values for `purpose`.

Returns a URL.

Return type *str*

Raises *fs.errors.NoURL* – If the path does not map to a URL.

islink (*path*)

Check if a path maps to a symlink.

Parameters **path** (*str*) – A path on the filesystem.

Returns `True` if `path` maps to a symlink.

Return type *bool*

listdir (*path*)

Get a list of the resource names in a directory.

This method will return a list of the resources in a directory. A *resource* is a file, directory, or one of the other types defined in *ResourceType*.

Parameters **path** (*str*) – A path to a directory on the filesystem

Returns list of names, relative to `path`.

Return type *list*

Raises

- *fs.errors.DirectoryExpected* – If `path` is not a directory.
- *fs.errors.ResourceNotFound* – If `path` does not exist.

makedir (*path*, *permissions=None*, *recreate=False*)

Make a directory.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (*Permissions*, *optional*) – a *Permissions* instance, or `None` to use default.
- **recreate** (*bool*) – Set to `True` to avoid raising an error if the directory already exists (defaults to `False`).

Returns a filesystem whose root is the new directory.

Return type *SubFS*

Raises

- *fs.errors.DirectoryExists* – If the path already exists.
- *fs.errors.ResourceNotFound* – If the path is not found.

open (*path*, *mode='r'*, *buffering=-1*, *encoding=None*, *errors=None*, *newline=""*, *line_buffering=False*, ***options*)

Open a file.

Parameters

- **path** (*str*) – A path to a file on the filesystem.
- **mode** (*str*) – Mode to open the file object with (defaults to *r*).
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, 1 to select line buffering, of any positive integer to indicate a buffer size).
- **encoding** (*str*) – Encoding for text files (defaults to `utf-8`)
- **errors** (*str*, *optional*) – What to do with unicode decode errors (see `codecs` module for more information).
- **newline** (*str*) – Newline parameter.
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (*x* in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

openbin (*path*, *mode*='r', *buffering*=-1, ***options*)

Open a binary file-like object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **mode** (*str*) – Mode to open file (must be a valid non-text mode, defaults to *r*). Since this method only opens binary files, the `b` in the mode string is implied.
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, or any positive integer to indicate a buffer size).
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (*x* in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

remove (*path*)

Remove a file from the filesystem.

Parameters **path** (*str*) – Path of the file to remove.

Raises

- `fs.errors.FileExpected` – If the path is a directory.

- `fs.errors.ResourceNotFound` – If the path does not exist.

removedir (*path*)

Remove a directory from the filesystem.

Parameters `path` (*str*) – Path of the directory to remove.

Raises

- `fs.errors.DirectoryNotEmpty` – If the directory is not empty (see `removetree` for a way to remove the directory contents.).
- `fs.errors.DirectoryExpected` – If the path does not refer to a directory.
- `fs.errors.ResourceNotFound` – If no resource exists at the given path.
- `fs.errors.RemoveRootError` – If an attempt is made to remove the root directory (i.e. '/')

scandir (*path*, *namespaces=None*, *page=None*)

Get an iterator of resource info.

Parameters

- **path** (*str*) – A path to a directory on the filesystem.
- **namespaces** (*list*, *optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'].
- **page** (*tuple*, *optional*) – May be a tuple of (<start>, <end>) indexes to return an iterator of a subset of the resource info, or `None` to iterate over the entire directory. Paging a directory scan may be necessary for very large directories.

Returns an iterator of `Info` objects.

Return type `Iterator`

Raises

- `fs.errors.DirectoryExpected` – If `path` is not a directory.
- `fs.errors.ResourceNotFound` – If `path` does not exist.

setinfo (*path*, *info*)

Set info on a resource.

This method is the complement to `getinfo` and is used to set info values on a resource.

Parameters

- **path** (*str*) – Path to a resource on the filesystem.
- **info** (*dict*) – Dictionary of resource info.

Raises `fs.errors.ResourceNotFound` – If `path` does not exist on the filesystem

The `info` dict should be in the same format as the raw info returned by `getinfo(file).raw`.

Example

```
>>> details_info = {"details": {
...     "modified": time.time()
... }}
>>> my_fs.setinfo('file.txt', details_info)
```

validatepath (*path*)

Check path may be encoded, in addition to usual checks.

8.7 Sub Filesystem

Manage a directory in a *parent* filesystem.

class `fs.subfs.SubFS` (*parent_fs*, *path*)

A sub-directory on another filesystem.

A SubFS is a filesystem object that maps to a sub-directory of another filesystem. This is the object that is returned by `opendir`.

delegate_fs ()

Get the proxied filesystem.

This method should return a filesystem for methods not associated with a path, e.g. `getmeta`.

delegate_path (*path*)

Encode a path for proxied filesystem.

Parameters `path` (*str*) – A path on the filesystem.

Returns a tuple of (<filesystem>, <new_path>)

Return type (*FS*, *str*)

class `fs.subfs.ClosingSubFS` (*parent_fs*, *path*)

A version of *SubFS* which closes its parent when closed.

close ()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call close multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a `FilesystemClosed` exception will be thrown.

8.8 Tar Filesystem

Manage the filesystem in a Tar archive.

class `fs.tarfs.TarFS` (*wrap_fs*)

Read and write tar files.

There are two ways to open a TarFS for the use cases of reading a tar file, and creating a new one.

If you open the TarFS with `write` set to `False` (the default), then the filesystem will be a read only filesystem which maps to the files and directories within the tar file. Files are decompressed on the fly when you open them.

Here's how you might extract and print a readme from a tar file:

```
with TarFS('foo.tar.gz') as tar_fs:
    readme = tar_fs.readtext('readme.txt')
```

If you open the TarFS with `write` set to `True`, then the TarFS will be an empty temporary filesystem. Any files / directories you create in the TarFS will be written in to a tar file when the TarFS is closed. The compression is set from the new file name but may be set manually with the `compression` argument.

Here's how you might write a new tar file containing a readme.txt file:

```
with TarFS('foo.tar.xz', write=True) as new_tar:
    new_tar.writetext(
        'readme.txt',
        'This tar file was written by PyFilesystem'
    )
```

Parameters

- **file** (*str* or *io.IOBase*) – An OS filename, or an open file handle.
- **write** (*bool*) – Set to `True` to write a new tar file, or use default (`False`) to read an existing tar file.
- **compression** (*str*, *optional*) – Compression to use (one of the formats supported by `tarfile`: `xz`, `gz`, `bz2`, or `None`).
- **temp_fs** (*str*) – An FS URL for the temporary filesystem used to store data prior to tarring.

```
class fs.tarfs.WriteTarFS (file, compression=None, encoding='utf-8',
                           temp_fs='temp://__tartemp__')
```

A writable tar file.

delegate_path (*path*)

Encode a path for proxied filesystem.

Parameters *path* (*str*) – A path on the filesystem.

Returns a tuple of (<filesystem>, <new_path>)

Return type (*FS*, *str*)

delegate_fs ()

Get the proxied filesystem.

This method should return a filesystem for methods not associated with a path, e.g. `getmeta`.

close ()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call `close` multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a `FilesystemClosed` exception will be thrown.

write_tar (*file=None, compression=None, encoding=None*)

Write tar to a file.

Parameters

- **file** (*str* or *io.IOBase*, *optional*) – Destination file, may be a file name or an open file object.
- **compression** (*str*, *optional*) – Compression to use (one of the constants defined in `tarfile` in the `stdlib`).
- **encoding** (*str*, *optional*) – The character encoding to use (default uses the encoding defined in `__init__`).

Note: This is called automatically when the TarFS is closed.

class `fs.tarfs.ReadTarFS` (*file, encoding='utf-8'*)

A readable tar file.

getinfo (*path, namespaces=None*)

Get information about a resource on a filesystem.

Parameters

- **path** (*str*) – A path to a resource on the filesystem.
- **namespaces** (*list*, *optional*) – Info namespaces to query (defaults to `[basic]`).

Returns resource information object.

Return type *Info*

For more information regarding resource information, see [Resource Info](#).

isdir (*path*)

Check if a path maps to an existing directory.

Parameters **path** (*str*) – A path on the filesystem.

Returns `True` if `path` maps to a directory.

Return type `bool`

isfile (*path*)

Check if a path maps to an existing file.

Parameters **path** (*str*) – A path on the filesystem.

Returns `True` if `path` maps to a file.

Return type `bool`

setinfo (*path*, *info*)

Set info on a resource.

This method is the complement to *getinfo* and is used to set info values on a resource.

Parameters

- **path** (*str*) – Path to a resource on the filesystem.
- **info** (*dict*) – Dictionary of resource info.

Raises *fs.errors.ResourceNotFound* – If *path* does not exist on the filesystem

The *info* dict should be in the same format as the raw info returned by *getinfo(file).raw*.

Example

```
>>> details_info = {"details": {
...     "modified": time.time()
... }}
>>> my_fs.setinfo('file.txt', details_info)
```

listdir (*path*)

Get a list of the resource names in a directory.

This method will return a list of the resources in a directory. A *resource* is a file, directory, or one of the other types defined in *ResourceType*.

Parameters **path** (*str*) – A path to a directory on the filesystem

Returns list of names, relative to *path*.

Return type *list*

Raises

- *fs.errors.DirectoryExpected* – If *path* is not a directory.
- *fs.errors.ResourceNotFound* – If *path* does not exist.

makedir (*path*, *permissions=None*, *recreate=False*)

Make a directory.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (*Permissions*, *optional*) – a *Permissions* instance, or *None* to use default.
- **recreate** (*bool*) – Set to *True* to avoid raising an error if the directory already exists (defaults to *False*).

Returns a filesystem whose root is the new directory.

Return type *SubFS*

Raises

- *fs.errors.DirectoryExists* – If the path already exists.
- *fs.errors.ResourceNotFound* – If the path is not found.

openbin (*path*, *mode='r'*, *buffering=-1*, ***options*)

Open a binary file-like object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **mode** (*str*) – Mode to open file (must be a valid non-text mode, defaults to *r*). Since this method only opens binary files, the *b* in the mode string is implied.
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, or any positive integer to indicate a buffer size).
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (*x* in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

remove (*path*)

Remove a file from the filesystem.

Parameters **path** (*str*) – Path of the file to remove.

Raises

- `fs.errors.FileExpected` – If the path is a directory.
- `fs.errors.ResourceNotFound` – If the path does not exist.

removedir (*path*)

Remove a directory from the filesystem.

Parameters **path** (*str*) – Path of the directory to remove.

Raises

- `fs.errors.DirectoryNotEmpty` – If the directory is not empty (see `removetree` for a way to remove the directory contents.).
- `fs.errors.DirectoryExpected` – If the path does not refer to a directory.
- `fs.errors.ResourceNotFound` – If no resource exists at the given path.
- `fs.errors.RemoveRootError` – If an attempt is made to remove the root directory (i.e. '/')

close ()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call `close` multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a `FilesystemClosed` exception will be thrown.

isclosed()

Check if the filesystem is closed.

geturl (*path*, *purpose*='download')

Get the URL to a given resource.

Parameters

- **path** (*str*) – A path on the filesystem
- **purpose** (*str*) – A short string that indicates which URL to retrieve for the given path (if there is more than one). The default is 'download', which should return a URL that serves the file. Other filesystems may support other values for purpose.

Returns a URL.

Return type *str*

Raises `fs.errors.NoURL` – If the path does not map to a URL.

8.9 Temporary Filesystem

Manage filesystems in temporary locations.

A temporary filesystem is stored in a location defined by your OS (/tmp on linux). The contents are deleted when the filesystem is closed.

A `TempFS` is a good way of preparing a directory structure in advance, that you can later copy. It can also be used as a temporary data store.

```
class fs.tempfs.TempFS (identifier='__tempfs__', temp_dir=None, auto_clean=True, ignore_clean_errors=True)
```

A temporary filesystem on the OS.

Parameters

- **identifier** (*str*) – A string to distinguish the directory within the OS temp location, used as part of the directory name.
- **temp_dir** (*str*, *optional*) – An OS path to your temp directory (leave as `None` to auto-detect)
- **auto_clean** (*bool*) – If `True` (the default), the directory contents will be wiped on close.
- **ignore_clean_errors** (*bool*) – If `True` (the default), any errors in the clean process will be suppressed. If `False`, they will be raised.

clean()

Clean (delete) temporary files created by this filesystem.

close()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call close multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a *FilesystemClosed* exception will be thrown.

8.10 Zip Filesystem

Manage the filesystem in a Zip archive.

class `fs.zipfs.ZipFS(wrap_fs)`

Read and write zip files.

There are two ways to open a ZipFS for the use cases of reading a zip file, and creating a new one.

If you open the ZipFS with `write` set to `False` (the default) then the filesystem will be a read only filesystem which maps to the files and directories within the zip file. Files are decompressed on the fly when you open them.

Here's how you might extract and print a readme from a zip file:

```
with ZipFS('foo.zip') as zip_fs:
    readme = zip_fs.readtext('readme.txt')
```

If you open the ZipFS with `write` set to `True`, then the ZipFS will be a empty temporary filesystem. Any files / directories you create in the ZipFS will be written in to a zip file when the ZipFS is closed.

Here's how you might write a new zip file containing a readme.txt file:

```
with ZipFS('foo.zip', write=True) as new_zip:
    new_zip.writetext(
        'readme.txt',
        'This zip file was written by PyFilesystem'
    )
```

Parameters

- **file** (*str* or *io.IOBase*) – An OS filename, or an open file object.
- **write** (*bool*) – Set to `True` to write a new zip file, or `False` (default) to read an existing zip file.
- **compression** (*int*) – Compression to use (one of the constants defined in the `zipfile` module in the `stdlib`).

- **temp_fs** (*str*) – An FS URL for the temporary filesystem used to store data prior to zipping.

class `fs.zipfs.WriteZipFS` (*file*, *compression*=8, *encoding*='utf-8', *temp_fs*='temp://__ziptemp__')

A writable zip file.

delegate_path (*path*)

Encode a path for proxied filesystem.

Parameters *path* (*str*) – A path on the filesystem.

Returns a tuple of (<filesystem>, <new_path>)

Return type (*FS*, *str*)

delegate_fs ()

Get the proxied filesystem.

This method should return a filesystem for methods not associated with a path, e.g. `getmeta`.

close ()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call close multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a `FilesystemClosed` exception will be thrown.

write_zip (*file*=None, *compression*=None, *encoding*=None)

Write zip to a file.

Parameters

- **file** (*str* or *io.IOBase*, *optional*) – Destination file, may be a file name or an open file handle.
- **compression** (*int*, *optional*) – Compression to use (one of the constants defined in the `zipfile` module in the `stdlib`).
- **encoding** (*str*, *optional*) – The character encoding to use (default uses the encoding defined in `__init__`).

Note: This is called automatically when the ZipFS is closed.

class `fs.zipfs.ReadZipFS` (*file*, *encoding*='utf-8')

A readable zip file.

getinfo (*path*, *namespaces*=None)

Get information about a resource on a filesystem.

Parameters

- **path** (*str*) – A path to a resource on the filesystem.
- **namespaces** (*list, optional*) – Info namespaces to query (defaults to *[basic]*).

Returns resource information object.

Return type *Info*

For more information regarding resource information, see *Resource Info*.

setinfo (*path, info*)

Set info on a resource.

This method is the complement to *getinfo* and is used to set info values on a resource.

Parameters

- **path** (*str*) – Path to a resource on the filesystem.
- **info** (*dict*) – Dictionary of resource info.

Raises *fs.errors.ResourceNotFound* – If *path* does not exist on the filesystem

The *info* dict should be in the same format as the raw info returned by *getinfo(file).raw*.

Example

```
>>> details_info = {"details": {
...     "modified": time.time()
... }}
>>> my_fs.setinfo('file.txt', details_info)
```

listdir (*path*)

Get a list of the resource names in a directory.

This method will return a list of the resources in a directory. A *resource* is a file, directory, or one of the other types defined in *ResourceType*.

Parameters **path** (*str*) – A path to a directory on the filesystem

Returns list of names, relative to *path*.

Return type *list*

Raises

- *fs.errors.DirectoryExpected* – If *path* is not a directory.
- *fs.errors.ResourceNotFound* – If *path* does not exist.

makedir (*path, permissions=None, recreate=False*)

Make a directory.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (*Permissions, optional*) – a *Permissions* instance, or *None* to use default.
- **recreate** (*bool*) – Set to *True* to avoid raising an error if the directory already exists (defaults to *False*).

Returns a filesystem whose root is the new directory.

Return type *SubFS*

Raises

- *fs.errors.DirectoryExists* – If the path already exists.
- *fs.errors.ResourceNotFound* – If the path is not found.

openbin (*path*, *mode='r'*, *buffering=-1*, ***kwargs*)

Open a binary file-like object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **mode** (*str*) – Mode to open file (must be a valid non-text mode, defaults to *r*). Since this method only opens binary files, the *b* in the mode string is implied.
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, or any positive integer to indicate a buffer size).
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type *io.IOBase*

Raises

- *fs.errors.FileExpected* – If the path is not a file.
- *fs.errors.FileExists* – If the file exists, and *exclusive mode* is specified (*x* in the mode).
- *fs.errors.ResourceNotFound* – If the path does not exist.

remove (*path*)

Remove a file from the filesystem.

Parameters **path** (*str*) – Path of the file to remove.

Raises

- *fs.errors.FileExpected* – If the path is a directory.
- *fs.errors.ResourceNotFound* – If the path does not exist.

removedir (*path*)

Remove a directory from the filesystem.

Parameters **path** (*str*) – Path of the directory to remove.

Raises

- *fs.errors.DirectoryNotEmpty* – If the directory is not empty (see *removetree* for a way to remove the directory contents.).
- *fs.errors.DirectoryExpected* – If the path does not refer to a directory.
- *fs.errors.ResourceNotFound* – If no resource exists at the given path.
- *fs.errors.RemoveRootError* – If an attempt is made to remove the root directory (i.e. '/')

close ()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call close multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a *FilesystemClosed* exception will be thrown.

readbytes (*path*)

Get the contents of a file as bytes.

Parameters *path* (*str*) – A path to a readable file on the filesystem.

Returns the file contents.

Return type *bytes*

Raises *fs.errors.ResourceNotFound* – if *path* does not exist.

geturl (*path*, *purpose='download'*)

Get the URL to a given resource.

Parameters

- **path** (*str*) – A path on the filesystem
- **purpose** (*str*) – A short string that indicates which URL to retrieve for the given path (if there is more than one). The default is 'download', which should return a URL that serves the file. Other filesystems may support other values for *purpose*.

Returns a URL.

Return type *str*

Raises *fs.errors.NoURL* – If the path does not map to a URL.

Implementing Filesystems

With a little care, you can implement a PyFilesystem interface for any filesystem, which will allow it to work interchangeably with any of the built-in FS classes and tools.

To create a PyFilesystem interface, derive a class from *FS* and implement the *Essential Methods*. This should give you a working FS class.

Take care to copy the method signatures *exactly*, including default values. It is also essential that you follow the same logic with regards to exceptions, and only raise exceptions in *errors*.

9.1 Constructor

There are no particular requirements regarding how a PyFilesystem class is constructed, but be sure to call the base class `__init__` method with no parameters.

9.2 Thread Safety

All Filesystems should be *thread-safe*. The simplest way to achieve that is by using the `_lock` attribute supplied by the *FS* constructor. This is a `RLock` object from the standard library, which you can use as a context manager, so methods you implement will start something like this:

```
with self._lock:
    do_something()
```

You aren't *required* to use `_lock`. Just as long as calling methods on the FS object from multiple threads doesn't break anything.

9.3 Python Versions

PyFilesystem supports Python2.7 and Python3.X. The differences between the two major Python versions are largely managed by the `six` library.

You aren't obligated to support the same versions of Python that PyFilesystem itself supports, but it is recommended if your project is for general use.

9.4 Testing Filesystems

To test your implementation, you can borrow the test suite used to test the built in filesystems. If your code passes these tests, then you can be confident your implementation will work seamlessly.

Here's the simplest possible example to test a filesystem class called `MyFS`:

```
from fs.test import FSTestCases

class TestMyFS(FSTestCases):

    def make_fs(self):
        # Return an instance of your FS object here
        return MyFS()
```

You may also want to override some of the methods in the test suite for more targeted testing:

class `fs.test.FSTestCases`

Basic FS tests.

assert_bytes (*path*, *contents*)

Assert a file contains the given bytes.

Parameters

- **path** (*str*) – A path on the filesystem.
- **contents** (*bytes*) – Bytes to compare.

assert_exists (*path*)

Assert a path exists.

Parameters **path** (*str*) – A path on the filesystem.

assert_isdir (*path*)

Assert a path is a directory.

Parameters **path** (*str*) – A path on the filesystem.

assert_isfile (*path*)

Assert a path is a file.

Parameters **path** (*str*) – A path on the filesystem.

assert_not_exists (*path*)

Assert a path does not exist.

Parameters **path** (*str*) – A path on the filesystem.

assert_text (*path*, *contents*)

Assert a file contains the given text.

Parameters

- **path** (*str*) – A path on the filesystem.
- **contents** (*str*) – Text to compare.

destroy_fs (*fs*)

Destroy a FS instance.

Parameters **fs** (*FS*) – A filesystem instance previously opened by *make_fs*.

make_fs ()

Return an FS instance.

test_geturl_purpose ()

Check an unknown purpose raises a NoURL error.

test_validatepath ()

Check validatepath returns an absolute path.

Note: As of version 2.4.11 this project uses [pytest](#) to run its tests. While it's completely compatible with `unittest`-style tests, it's much more powerful and feature-rich. We suggest you take advantage of it and its plugins in new tests you write, rather than sticking to strict `unittest` features. For benefits and limitations, see [here](#).

9.5 Essential Methods

The following methods **MUST** be implemented in a PyFilesystem interface.

- *getinfo* () Get info regarding a file or directory.
- *listdir* () Get a list of resources in a directory.
- *makedir* () Make a directory.
- *openbin* () Open a binary file.
- *remove* () Remove a file.
- *removedir* () Remove a directory.
- *setinfo* () Set resource information.

9.6 Non - Essential Methods

The following methods **MAY** be implemented in a PyFilesystem interface.

These methods have a default implementation in the base class, but may be overridden if you can supply a more optimal version.

Exactly which methods you should implement depends on how and where the data is stored. For network filesystems, a good candidate to implement, is the `scandir` method which would otherwise call a combination of `listdir` and `getinfo` for each file.

In the general case, it is a good idea to look at how these methods are implemented in *FS*, and only write a custom version if it would be more efficient than the default.

- *appendbytes* ()
- *appendtext* ()
- *close* ()

- `copy()`
- `copydir()`
- `create()`
- `desc()`
- `download()`
- `exists()`
- `filterdir()`
- `getmeta()`
- `getospath()`
- `getsize()`
- `getsyspath()`
- `gettype()`
- `geturl()`
- `hassyspath()`
- `hasurl()`
- `isclosed()`
- `isempty()`
- `isdir()`
- `isfile()`
- `islink()`
- `lock()`
- `makedirs()`
- `move()`
- `movedir()`
- `open()`
- `opendir()`
- `readbytes()`
- `readtext()`
- `removetree()`
- `scandir()`
- `settimes()`
- `touch()`
- `upload()`
- `validatepath()`
- `writebytes()`
- `writefile()`

- `writetext()`

9.7 Helper Methods

These methods SHOULD NOT be implemented.

Implementing these is highly unlikely to be worthwhile.

- `check()`
- `getbasic()`
- `getdetails()`
- `hash()`
- `match()`
- `tree()`

Creating an extension

Once a filesystem has been implemented, it can be integrated with other applications and projects using PyFilesystem.

10.1 Naming Convention

For visibility in PyPi, we recommend that your package be prefixed with `fs-`. For instance if you have implemented an `AwesomeFS` PyFilesystem class, your packaged could be be named `fs-awesome` or `fs-awesomefs`.

10.2 Opener

In order for your filesystem to be opened with an *FS URL* you should define an *Opener* class.

Here's an example taken from an Amazon S3 Filesystem:

```
"""Defines the S3FSOpener."""
__all__ = ['S3FSOpener']

from fs.opener import Opener, OpenerError

from ._s3fs import S3FS

class S3FSOpener(Opener):
    protocols = ['s3']

    def open_fs(self, fs_url, parse_result, writeable, create, cwd):
        bucket_name, _, dir_path = parse_result.resource.partition('/')
        if not bucket_name:
            raise OpenerError(
                "invalid bucket name in '{}'.format(fs_url)
```

(continues on next page)

(continued from previous page)

```

    )
    s3fs = S3FS(
        bucket_name,
        dir_path=dir_path or '/',
        aws_access_key_id=parse_result.username or None,
        aws_secret_access_key=parse_result.password or None,
    )
    return s3fs

```

By convention this would be defined in `opener.py`.

To register the opener you will need to define an `entry point` in your `setup.py`. See below for an example.

10.3 The setup.py file

Refer to the [setuptools documentation](#) to see how to write a `setup.py` file. There are only a few things that should be kept in mind when creating a `Pyfilesystem2` extension. Make sure that:

- `fs` is in the `install_requires` list. You should reference the version number with the `~=` operator which ensures that the install will get any bugfix releases of `PyFilesystem` but not any potentially breaking changes.
- If you created an opener, include it as an `fs.opener` entry point, using the name of the entry point as the protocol to be used.

Here is an minimal `setup.py` for our project:

```

from setuptools import setup
setup(
    name='fs-awesomefs', # Name in PyPi
    author="You !",
    author_email="your.email@domain.ext",
    description="An awesome filesystem for pyfilesystem2 !",
    install_requires=[
        "fs~=2.0.5"
    ],
    entry_points = {
        'fs.opener': [
            'awe = awesomefs.opener:AwesomeFSOpener',
        ]
    },
    license="MY LICENSE",
    packages=['awesomefs'],
    version="X.Y.Z",
)

```

10.4 Good Practices

Keep track of your achievements! Add the following values to your `__init__.py`:

- `__version__` The version of the extension (we recommend following [Semantic Versioning](#)),
- `__author__` Your name(s).
- `__author_email__` Your email(s).

- `__license__` The module's license.

10.5 Let us Know

Contact us to add your filesystem to the [PyFilesystem Wiki](#).

10.6 Live Example

See [fs.sshfs](#) for a functioning PyFilesystem2 extension implementing a Pyfilesystem2 filesystem over SSH.

CHAPTER 11

External Filesystems

See the following wiki page for a list of filesystems not in the core library, and community contributed filesystems.

<https://www.pyfilesystem.org/page/index-of-filesystems/>

If you have developed a filesystem that you would like added to the above page, please let us know by opening a [Github issue](#).

The following is a complete list of methods on PyFilesystem objects.

- *appendbytes()* Append bytes to a file.
- *appendtext()* Append text to a file.
- *check()* Check if a filesystem is open or raise error.
- *close()* Close the filesystem.
- *copy()* Copy a file to another location.
- *copydir()* Copy a directory to another location.
- *create()* Create or truncate a file.
- *desc()* Get a description of a resource.
- *download()* Copy a file on the filesystem to a file-like object.
- *exists()* Check if a path exists.
- *filterdir()* Iterate resources, filtering by wildcard(s).
- *getbasic()* Get basic info namespace for a resource.
- *getdetails()* Get details info namespace for a resource.
- *getinfo()* Get info regarding a file or directory.
- *getmeta()* Get meta information for a resource.
- *getospath()* Get path with encoding expected by the OS.
- *getsize()* Get the size of a file.
- *getsyspath()* Get the system path of a resource, if one exists.
- *gettype()* Get the type of a resource.
- *geturl()* Get a URL to a resource, if one exists.
- *hassyspath()* Check if a resource maps to the OS filesystem.

- *hash()* Get the hash of a file's contents.
- *hasurl()* Check if a resource has a URL.
- *isclosed()* Check if the filesystem is closed.
- *isempty()* Check if a directory is empty.
- *isdir()* Check if path maps to a directory.
- *isfile()* Check if path maps to a file.
- *islink()* Check if path is a link.
- *listdir()* Get a list of resources in a directory.
- *lock()* Get a thread lock context manager.
- *makedir()* Make a directory.
- *makedirs()* Make a directory and intermediate directories.
- *match()* Match one or more wildcard patterns against a path.
- *move()* Move a file to another location.
- *movedir()* Move a directory to another location.
- *open()* Open a file on the filesystem.
- *openbin()* Open a binary file.
- *opendir()* Get a filesystem object for a directory.
- *readbytes()* Read file as bytes.
- *readtext()* Read file as text.
- *remove()* Remove a file.
- *removedir()* Remove a directory.
- *removetree()* Recursively remove file and directories.
- *scandir()* Scan files and directories.
- *setinfo()* Set resource information.
- *settimes()* Set modified times for a resource.
- *touch()* Create a file or update times.
- *tree()* Render a tree view of the filesystem.
- *upload()* Copy a binary file to the filesystem.
- *validatepath()* Check a path is valid and return normalized path.
- *writebytes()* Write a file as bytes.
- *writefile()* Write a file-like object to the filesystem.
- *writetext()* Write a file as text.

13.1 fs.base

PyFilesystem base class.

The filesystem base class is common to all filesystems. If you familiarize yourself with this (rather straightforward) API, you can work with any of the supported filesystems.

class `fs.base.FS`

Base class for FS objects.

`__del__()`

Auto-close the filesystem on exit.

`__enter__()`

Allow use of filesystem as a context manager.

`__exit__(exc_type, exc_value, traceback)`

Close filesystem on exit.

appendbytes (*path*, *data*)

Append bytes to the end of a file, creating it if needed.

Parameters

- **path** (*str*) – Path to a file.
- **data** (*bytes*) – Bytes to append.

Raises

- `TypeError` – If *data* is not a `bytes` instance.
- `fs.errors.ResourceNotFound` – If a parent directory of *path* does not exist.

appendtext (*path*, *text*, *encoding='utf-8'*, *errors=None*, *newline=""*)

Append text to the end of a file, creating it if needed.

Parameters

- **path** (*str*) – Path to a file.
- **text** (*str*) – Text to append.
- **encoding** (*str*) – Encoding for text files (defaults to utf-8).
- **errors** (*str, optional*) – What to do with unicode decode errors (see `codecs` module for more information).
- **newline** (*str*) – Newline parameter.

Raises

- `TypeError` – if `text` is not an unicode string.
- `fs.errors.ResourceNotFound` – if a parent directory of `path` does not exist.

check()

Check if a filesystem may be used.

Raises `fs.errors.FilesystemClosed` – if the filesystem is closed.

close()

Close the filesystem and release any resources.

It is important to call this method when you have finished working with the filesystem. Some filesystems may not finalize changes until they are closed (archives for example). You may call this method explicitly (it is safe to call `close` multiple times), or you can use the filesystem as a context manager to automatically close.

Example

```
>>> with OSFS('~/Desktop') as desktop_fs:
...     desktop_fs.writetext(
...         'note.txt',
...         "Don't forget to tape Game of Thrones"
...     )
```

If you attempt to use a filesystem that has been closed, a `FilesystemClosed` exception will be thrown.

copy(src_path, dst_path, overwrite=False)

Copy file contents from `src_path` to `dst_path`.

Parameters

- **src_path** (*str*) – Path of source file.
- **dst_path** (*str*) – Path to destination file.
- **overwrite** (*bool*) – If `True`, overwrite the destination file if it exists (defaults to `False`).

Raises

- `fs.errors.DestinationExists` – If `dst_path` exists, and `overwrite` is `False`.
- `fs.errors.ResourceNotFound` – If a parent directory of `dst_path` does not exist.

copydir(src_path, dst_path, create=False)

Copy the contents of `src_path` to `dst_path`.

Parameters

- **src_path** (*str*) – Path of source directory.
- **dst_path** (*str*) – Path to destination directory.
- **create** (*bool*) – If `True`, then `dst_path` will be created if it doesn't exist already (defaults to `False`).

Raises `fs.errors.ResourceNotFound` – If the `dst_path` does not exist, and `create` is not `True`.

create (*path*, *wipe=False*)
Create an empty file.

The default behavior is to create a new file if one doesn't already exist. If `wipe` is `True`, any existing file will be truncated.

Parameters

- **path** (*str*) – Path to a new file in the filesystem.
- **wipe** (*bool*) – If `True`, truncate any existing file to 0 bytes (defaults to `False`).

Returns `True` if a new file had to be created.

Return type `bool`

desc (*path*)
Return a short descriptive text regarding a path.

Parameters **path** (*str*) – A path to a resource on the filesystem.

Returns a short description of the path.

Return type `str`

download (*path*, *file*, *chunk_size=None*, ***options*)
Copies a file from the filesystem to a file-like object.

This may be more efficient than opening and copying files manually if the filesystem supplies an optimized method.

Parameters

- **path** (*str*) – Path to a resource.
- **file** (*file-like*) – A file-like object open for writing in binary mode.
- **chunk_size** (*int*, *optional*) – Number of bytes to read at a time, if a simple copy is used, or `None` to use sensible default.
- ****options** – Implementation specific options required to open the source file.

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('starwars.mov', 'wb') as write_file:
...     my_fs.download('/movies/starwars.mov', write_file)
```

exists (*path*)
Check if a path maps to a resource.

Parameters **path** (*str*) – Path to a resource.

Returns `True` if a resource exists at the given path.

Return type `bool`

filterdir (*path*, *files=None*, *dirs=None*, *exclude_dirs=None*, *exclude_files=None*, *namespaces=None*, *page=None*)

Get an iterator of resource info, filtered by patterns.

This method enhances `scandir` with additional filtering functionality.

Parameters

- **path** (*str*) – A path to a directory on the filesystem.
- **files** (*list*, *optional*) – A list of UNIX shell-style patterns to filter file names, e.g. [`*.py`].
- **dirs** (*list*, *optional*) – A list of UNIX shell-style patterns to filter directory names.
- **exclude_dirs** (*list*, *optional*) – A list of patterns used to exclude directories.
- **exclude_files** (*list*, *optional*) – A list of patterns used to exclude files.
- **namespaces** (*list*, *optional*) – A list of namespaces to include in the resource information, e.g. [`basic`, `access`].
- **page** (*tuple*, *optional*) – May be a tuple of (`<start>`, `<end>`) indexes to return an iterator of a subset of the resource info, or `None` to iterate over the entire directory. Paging a directory scan may be necessary for very large directories.

Returns an iterator of `Info` objects.

Return type `Iterator`

getbasic (*path*)

Get the *basic* resource info.

This method is shorthand for the following:

```
fs.getinfo(path, namespaces=['basic'])
```

Parameters **path** (*str*) – A path on the filesystem.

Returns Resource information object for *path*.

Return type `Info`

getbytes (*path*)

Get the contents of a file as bytes.

Parameters **path** (*str*) – A path to a readable file on the filesystem.

Returns the file contents.

Return type `bytes`

Raises `fs.errors.ResourceNotFound` – if *path* does not exist.

Note: Deprecated since version 2.2.0: Please use `readbytes`

getdetails (*path*)

Get the *details* resource info.

This method is shorthand for the following:

```
fs.getinfo(path, namespaces=['details'])
```

Parameters **path** (*str*) – A path on the filesystem.

Returns Resource information object for *path*.

Return type *Info*

getfile (*path, file, chunk_size=None, **options*)

Copies a file from the filesystem to a file-like object.

This may be more efficient than opening and copying files manually if the filesystem supplies an optimized method.

Parameters

- **path** (*str*) – Path to a resource.
- **file** (*file-like*) – A file-like object open for writing in binary mode.
- **chunk_size** (*int, optional*) – Number of bytes to read at a time, if a simple copy is used, or *None* to use sensible default.
- ****options** – Implementation specific options required to open the source file.

Note that the file object *file* will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('starwars.mov', 'wb') as write_file:
...     my_fs.download('/movies/starwars.mov', write_file)
```

Note: Deprecated since version 2.2.0: Please use [download](#)

getinfo (*path, namespaces=None*)

Get information about a resource on a filesystem.

Parameters

- **path** (*str*) – A path to a resource on the filesystem.
- **namespaces** (*list, optional*) – Info namespaces to query (defaults to *[basic]*).

Returns resource information object.

Return type *Info*

For more information regarding resource information, see [Resource Info](#).

getmeta (*namespace='standard'*)

Get meta information regarding a filesystem.

Parameters **namespace** (*str*) – The meta namespace (defaults to "standard").

Returns the meta information.

Return type dict

Meta information is associated with a *namespace* which may be specified with the `namespace` parameter. The default namespace, "standard", contains common information regarding the filesystem's capabilities. Some filesystems may provide other namespaces which expose less common or implementation specific information. If a requested namespace is not supported by a filesystem, then an empty dictionary will be returned.

The "standard" namespace supports the following keys:

key	Description
<code>case_insensitive</code>	<code>True</code> if this filesystem is case insensitive.
<code>invalid_path_chars</code>	A string containing the characters that may not be used on this filesystem.
<code>max_path_length</code>	Maximum number of characters permitted in a path, or <code>None</code> for no limit.
<code>max_sys_path_length</code>	Maximum number of characters permitted in a sys path, or <code>None</code> for no limit.
<code>network</code>	<code>True</code> if this filesystem requires a network.
<code>read_only</code>	<code>True</code> if this filesystem is read only.
<code>supports_rename</code>	<code>True</code> if this filesystem supports an <code>os.rename</code> operation.

Most builtin filesystems will provide all these keys, and third- party filesystems should do so whenever possible, but a key may not be present if there is no way to know the value.

Note: Meta information is constant for the lifetime of the filesystem, and may be cached.

getospath (*path*)

Get a *system path* to a resource, encoded in the operating system's preferred encoding.

Parameters `path` (*str*) – A path on the filesystem.

Returns the *system path* of the resource, if any.

Return type `str`

Raises `fs.errors.NoSysPath` – If there is no corresponding system path.

This method takes the output of `getsyspath` and encodes it to the filesystem's preferred encoding. In Python3 this step is not required, as the `os` module will do it automatically. In Python2.7, the encoding step is required to support filenames on the filesystem that don't encode correctly.

Note: If you want your code to work in Python2.7 and Python3 then use this method if you want to work will the OS filesystem outside of the OSFS interface.

getsize (*path*)

Get the size (in bytes) of a resource.

Parameters `path` (*str*) – A path to a resource.

Returns the *size* of the resource.

Return type `int`

The *size* of a file is the total number of readable bytes, which may not reflect the exact number of bytes of reserved disk space (or other storage medium).

The size of a directory is the number of bytes of overhead use to store the directory entry.

getsyspath (*path*)

Get the *system path* of a resource.

Parameters `path` (*str*) – A path on the filesystem.

Returns the *system path* of the resource, if any.

Return type *str*

Raises `fs.errors.NoSysPath` – If there is no corresponding system path.

A system path is one recognized by the OS, that may be used outside of PyFilesystem (in an application or a shell for example). This method will get the corresponding system path that would be referenced by `path`.

Not all filesystems have associated system paths. Network and memory based filesystems, for example, may not physically store data anywhere the OS knows about. It is also possible for some paths to have a system path, whereas others don't.

This method will always return a *str* on Py3.* and *unicode* on Py2.7. See `getospath` if you need to encode the path as bytes.

If `path` doesn't have a system path, a `NoSysPath` exception will be thrown.

Note: A filesystem may return a system path even if no resource is referenced by that path – as long as it can be certain what that system path would be.

gettext (*path*, *encoding=None*, *errors=None*, *newline=""*)

Get the contents of a file as a string.

Parameters

- **path** (*str*) – A path to a readable file on the filesystem.
- **encoding** (*str*, *optional*) – Encoding to use when reading contents in text mode (defaults to `None`, reading in binary mode).
- **errors** (*str*, *optional*) – Unicode errors parameter.
- **newline** (*str*) – Newlines parameter.

Returns file contents.

Return type *str*

Raises `fs.errors.ResourceNotFound` – If `path` does not exist.

Note: Deprecated since version 2.2.0: Please use `readtext`

gettype (*path*)

Get the type of a resource.

Parameters `path` (*str*) – A path on the filesystem.

Returns the type of the resource.

Return type *ResourceType*

A type of a resource is an integer that identifies the what the resource references. The standard type integers may be one of the values in the *ResourceType* enumerations.

The most common resource types, supported by virtually all filesystems are `directory` (1) and `file` (2), but the following types are also possible:

ResourceType	value
unknown	0
directory	1
file	2
character	3
block_special_file	4
fifo	5
socket	6
symlink	7

Standard resource types are positive integers, negative values are reserved for implementation specific resource types.

geturl (*path*, *purpose*='download')

Get the URL to a given resource.

Parameters

- **path** (*str*) – A path on the filesystem
- **purpose** (*str*) – A short string that indicates which URL to retrieve for the given path (if there is more than one). The default is 'download', which should return a URL that serves the file. Other filesystems may support other values for *purpose*.

Returns a URL.

Return type *str*

Raises *fs.errors.NoURL* – If the path does not map to a URL.

glob

a globber object..

Type *BoundGlobber*

hash (*path*, *name*)

Get the hash of a file's contents.

Parameters

- **path** (*str*) – A path on the filesystem.
- **name** (*str*) – One of the algorithms supported by the hashlib module, e.g. "md5"

Returns The hex digest of the hash.

Return type *str*

Raises *fs.errors.UnsupportedHash* – If the requested hash is not supported.

hassyspath (*path*)

Check if a path maps to a system path.

Parameters **path** (*str*) – A path on the filesystem.

Returns *True* if the resource at *path* has a *syspath*.

Return type *bool*

hasurl (*path*, *purpose*='download')

Check if a path has a corresponding URL.

Parameters

- **path** (*str*) – A path on the filesystem.
- **purpose** (*str*) – A purpose parameter, as given in *geturl*.

Returns `True` if an URL for the given purpose exists.

Return type `bool`

isclosed ()

Check if the filesystem is closed.

isdir (*path*)

Check if a path maps to an existing directory.

Parameters **path** (*str*) – A path on the filesystem.

Returns `True` if *path* maps to a directory.

Return type `bool`

isempty (*path*)

Check if a directory is empty.

A directory is considered empty when it does not contain any file or any directory.

Parameters **path** (*str*) – A path to a directory on the filesystem.

Returns `True` if the directory is empty.

Return type `bool`

Raises

- `errors.DirectoryExpected` – If *path* is not a directory.
- `errors.ResourceNotFound` – If *path* does not exist.

isfile (*path*)

Check if a path maps to an existing file.

Parameters **path** (*str*) – A path on the filesystem.

Returns `True` if *path* maps to a file.

Return type `bool`

islink (*path*)

Check if a path maps to a symlink.

Parameters **path** (*str*) – A path on the filesystem.

Returns `True` if *path* maps to a symlink.

Return type `bool`

listdir (*path*)

Get a list of the resource names in a directory.

This method will return a list of the resources in a directory. A *resource* is a file, directory, or one of the other types defined in *ResourceType*.

Parameters **path** (*str*) – A path to a directory on the filesystem

Returns list of names, relative to *path*.

Return type `list`

Raises

- `fs.errors.DirectoryExpected` – If `path` is not a directory.
- `fs.errors.ResourceNotFound` – If `path` does not exist.

lock()

Get a context manager that *locks* the filesystem.

Locking a filesystem gives a thread exclusive access to it. Other threads will block until the threads with the lock has left the context manager.

Returns a lock specific to the filesystem instance.

Return type `threading.RLock`

Example

```
>>> with my_fs.lock(): # May block
...     # code here has exclusive access to the filesystem
```

It is a good idea to put a lock around any operations that you would like to be *atomic*. For instance if you are copying files, and you don't want another thread to delete or modify anything while the copy is in progress.

Locking with this method is only required for code that calls multiple filesystem methods. Individual methods are thread safe already, and don't need to be locked.

Note: This only locks at the Python level. There is nothing to prevent other processes from modifying the filesystem outside of the filesystem instance.

makedir (*path*, *permissions=None*, *recreate=False*)

Make a directory.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (`Permissions`, *optional*) – a `Permissions` instance, or `None` to use default.
- **recreate** (*bool*) – Set to `True` to avoid raising an error if the directory already exists (defaults to `False`).

Returns a filesystem whose root is the new directory.

Return type *SubFS*

Raises

- `fs.errors.DirectoryExists` – If the path already exists.
- `fs.errors.ResourceNotFound` – If the path is not found.

makedirs (*path*, *permissions=None*, *recreate=False*)

Make a directory, and any missing intermediate directories.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (`Permissions`, *optional*) – Initial permissions, or `None` to use defaults.

- **recreate** (*bool*) – If `False` (the default), attempting to create an existing directory will raise an error. Set to `True` to ignore existing directories.

Returns A sub-directory filesystem.

Return type *SubFS*

Raises

- *fs.errors.DirectoryExists* – if the path is already a directory, and `recreate` is `False`.
- *fs.errors.DirectoryExpected* – if one of the ancestors in the path is not a directory.

match (*patterns, name*)

Check if a name matches any of a list of wildcards.

Parameters

- **patterns** (*list*) – A list of patterns, e.g. [`*.py`]
- **name** (*str*) – A file or directory name (not a path)

Returns `True` if name matches any of the patterns.

Return type `bool`

If a filesystem is case *insensitive* (such as Windows) then this method will perform a case insensitive match (i.e. `*.py` will match the same names as `*.PY`). Otherwise the match will be case sensitive (`*.py` and `*.PY` will match different names).

Example

```
>>> home_fs.match(['*.py'], '__init__.py')
True
>>> home_fs.match(['*.jpg', '*.png'], 'foo.gif')
False
```

Note: If `patterns` is `None` (or [`*`]), then this method will always return `True`.

move (*src_path, dst_path, overwrite=False*)

Move a file from `src_path` to `dst_path`.

Parameters

- **src_path** (*str*) – A path on the filesystem to move.
- **dst_path** (*str*) – A path on the filesystem where the source file will be written to.
- **overwrite** (*bool*) – If `True`, destination path will be overwritten if it exists.

Raises

- *fs.errors.FileExpected* – If `src_path` maps to a directory instead of a file.
- *fs.errors.DestinationExists* – If `dst_path` exists, and `overwrite` is `False`.
- *fs.errors.ResourceNotFound* – If a parent directory of `dst_path` does not exist.

movedir (*src_path*, *dst_path*, *create=False*)

Move directory *src_path* to *dst_path*.

Parameters

- **src_path** (*str*) – Path of source directory on the filesystem.
- **dst_path** (*str*) – Path to destination directory.
- **create** (*bool*) – If `True`, then *dst_path* will be created if it doesn't exist already (defaults to `False`).

Raises `fs.errors.ResourceNotFound` – if *dst_path* does not exist, and *create* is `False`.

open (*path*, *mode='r'*, *buffering=-1*, *encoding=None*, *errors=None*, *newline=""*, ***options*)

Open a file.

Parameters

- **path** (*str*) – A path to a file on the filesystem.
- **mode** (*str*) – Mode to open the file object with (defaults to *r*).
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, 1 to select line buffering, of any positive integer to indicate a buffer size).
- **encoding** (*str*) – Encoding for text files (defaults to `utf-8`)
- **errors** (*str*, *optional*) – What to do with unicode decode errors (see `codecs` module for more information).
- **newline** (*str*) – Newline parameter.
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (*x* in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

openbin (*path*, *mode='r'*, *buffering=-1*, ***options*)

Open a binary file-like object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **mode** (*str*) – Mode to open file (must be a valid non-text mode, defaults to *r*). Since this method only opens binary files, the `b` in the mode string is implied.
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, or any positive integer to indicate a buffer size).
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (x in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

opendir (*path*, *factory=None*)

Get a filesystem object for a sub-directory.

Parameters

- **path** (*str*) – Path to a directory on the filesystem.
- **factory** (*callable*, *optional*) – A callable that when invoked with an FS instance and *path* will return a new FS object representing the sub-directory contents. If no *factory* is supplied then *subfs_class* will be used.

Returns A filesystem representing a sub-directory.

Return type *SubFS*

Raises `fs.errors.DirectoryExpected` – If *dst_path* does not exist or is not a directory.

readbytes (*path*)

Get the contents of a file as bytes.

Parameters **path** (*str*) – A path to a readable file on the filesystem.

Returns the file contents.

Return type `bytes`

Raises `fs.errors.ResourceNotFound` – if *path* does not exist.

readtext (*path*, *encoding=None*, *errors=None*, *newline=""*)

Get the contents of a file as a string.

Parameters

- **path** (*str*) – A path to a readable file on the filesystem.
- **encoding** (*str*, *optional*) – Encoding to use when reading contents in text mode (defaults to `None`, reading in binary mode).
- **errors** (*str*, *optional*) – Unicode errors parameter.
- **newline** (*str*) – Newlines parameter.

Returns file contents.

Return type `str`

Raises `fs.errors.ResourceNotFound` – If *path* does not exist.

remove (*path*)

Remove a file from the filesystem.

Parameters **path** (*str*) – Path of the file to remove.

Raises

- `fs.errors.FileExpected` – If the path is a directory.

- `fs.errors.ResourceNotFound` – If the path does not exist.

removedir (*path*)

Remove a directory from the filesystem.

Parameters `path` (*str*) – Path of the directory to remove.

Raises

- `fs.errors.DirectoryNotEmpty` – If the directory is not empty (see `removetree` for a way to remove the directory contents.).
- `fs.errors.DirectoryExpected` – If the path does not refer to a directory.
- `fs.errors.ResourceNotFound` – If no resource exists at the given path.
- `fs.errors.RemoveRootError` – If an attempt is made to remove the root directory (i.e. '/')

removetree (*dir_path*)

Recursively remove the contents of a directory.

This method is similar to `removedir`, but will remove the contents of the directory if it is not empty.

Parameters `dir_path` (*str*) – Path to a directory on the filesystem.

scandir (*path*, *namespaces=None*, *page=None*)

Get an iterator of resource info.

Parameters

- `path` (*str*) – A path to a directory on the filesystem.
- `namespaces` (*list*, *optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'].
- `page` (*tuple*, *optional*) – May be a tuple of (<start>, <end>) indexes to return an iterator of a subset of the resource info, or `None` to iterate over the entire directory. Paging a directory scan may be necessary for very large directories.

Returns an iterator of `Info` objects.

Return type `Iterator`

Raises

- `fs.errors.DirectoryExpected` – If `path` is not a directory.
- `fs.errors.ResourceNotFound` – If `path` does not exist.

setbinfile (*path*, *file*, *chunk_size=None*, ***options*)

Set a file to the contents of a binary file object.

This method copies bytes from an open binary file to a file on the filesystem. If the destination exists, it will first be truncated.

Parameters

- `path` (*str*) – A path on the filesystem.
- `file` (*io.IOBase*) – a file object open for reading in binary mode.
- `chunk_size` (*int*, *optional*) – Number of bytes to read at a time, if a simple copy is used, or `None` to use sensible default.
- `**options` – Implementation specific options required to open the source file.

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('~/.movies/starwars.mov', 'rb') as read_file:
...     my_fs.upload('starwars.mov', read_file)
```

Note: Deprecated since version 2.2.0: Please use `upload`

setbytes (*path, contents*)
Copy binary data to a file.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*bytes*) – Data to be written.

Raises `TypeError` – if contents is not bytes.

Note: Deprecated since version 2.2.0: Please use `writebytes`

setfile (*path, file, encoding=None, errors=None, newline=""*)
Set a file to the contents of a file object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **file** (*io.IOBase*) – A file object open for reading.
- **encoding** (*str, optional*) – Encoding of destination file, defaults to `None` for binary.
- **errors** (*str, optional*) – How encoding errors should be treated (same as `io.open`).
- **newline** (*str*) – Newline parameter (same as `io.open`).

This method is similar to `upload`, in that it copies data from a file-like object to a resource on the filesystem, but unlike `upload`, this method also supports creating files in text-mode (if the `encoding` argument is supplied).

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('myfile.txt') as read_file:
...     my_fs.writefile('myfile.txt', read_file)
```

Note: Deprecated since version 2.2.0: Please use `writefile`

setinfo (*path*, *info*)

Set info on a resource.

This method is the complement to *getinfo* and is used to set info values on a resource.

Parameters

- **path** (*str*) – Path to a resource on the filesystem.
- **info** (*dict*) – Dictionary of resource info.

Raises *fs.errors.ResourceNotFound* – If *path* does not exist on the filesystem

The *info* dict should be in the same format as the raw info returned by *getinfo(file).raw*.

Example

```
>>> details_info = {"details": {
...     "modified": time.time()
... }}
>>> my_fs.setinfo('file.txt', details_info)
```

settext (*path*, *contents*, *encoding='utf-8'*, *errors=None*, *newline=""*)

Create or replace a file with text.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*str*) – Text to be written.
- **encoding** (*str*, *optional*) – Encoding of destination file (defaults to 'utf-8').
- **errors** (*str*, *optional*) – How encoding errors should be treated (same as *io.open*).
- **newline** (*str*) – Newline parameter (same as *io.open*).

Raises *TypeError* – if *contents* is not a unicode string.

Note: Deprecated since version 2.2.0: Please use *writetext*

settimes (*path*, *accessed=None*, *modified=None*)

Set the accessed and modified time on a resource.

Parameters

- **path** – A path to a resource on the filesystem.
- **accessed** (*datetime*, *optional*) – The accessed time, or *None* (the default) to use the current time.
- **modified** (*datetime*, *optional*) – The modified time, or *None* (the default) to use the same time as the accessed parameter.

touch (*path*)

Touch a file on the filesystem.

Touching a file means creating a new file if *path* doesn't exist, or update accessed and modified times if the path does exist. This method is similar to the linux command of the same name.

Parameters **path** (*str*) – A path to a file on the filesystem.

tree (***kwargs*)

Render a tree view of the filesystem to stdout or a file.

The parameters are passed to `render()`.

Keyword Arguments

- **path** (*str*) – The path of the directory to start rendering from (defaults to root folder, i.e. '/').
- **file** (*io.IOBase*) – An open file-like object to render the tree, or `None` for stdout.
- **encoding** (*str*) – Unicode encoding, or `None` to auto-detect.
- **max_levels** (*int*) – Maximum number of levels to display, or `None` for no maximum.
- **with_color** (*bool*) – Enable terminal color output, or `None` to auto-detect terminal.
- **dirs_first** (*bool*) – Show directories first.
- **exclude** (*list*) – Option list of directory patterns to exclude from the tree render.
- **filter** (*list*) – Optional list of files patterns to match in the tree render.

upload (*path, file, chunk_size=None, **options*)

Set a file to the contents of a binary file object.

This method copies bytes from an open binary file to a file on the filesystem. If the destination exists, it will first be truncated.

Parameters

- **path** (*str*) – A path on the filesystem.
- **file** (*io.IOBase*) – a file object open for reading in binary mode.
- **chunk_size** (*int, optional*) – Number of bytes to read at a time, if a simple copy is used, or `None` to use sensible default.
- ****options** – Implementation specific options required to open the source file.

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('~/.movies/starwars.mov', 'rb') as read_file:
...     my_fs.upload('starwars.mov', read_file)
```

validatepath (*path*)

Check if a path is valid, returning a normalized absolute path.

Many filesystems have restrictions on the format of paths they support. This method will check that `path` is valid on the underlying storage mechanism and throw a `InvalidPath` exception if it is not.

Parameters `path` (*str*) – A path.

Returns A normalized, absolute path.

Return type `str`

Raises

- `fs.errors.InvalidCharsInPath` – If the path contains invalid characters.
- `fs.errors.InvalidPath` – If the path is invalid.

- `fs.errors.FileSystemClosed` – if the filesystem is closed.

walk

a walker bound to this filesystem.

Type `BoundWalker`

walker_class

alias of `fs.walk.Walker`

writebytes (*path, contents*)

Copy binary data to a file.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*bytes*) – Data to be written.

Raises `TypeError` – if contents is not bytes.

writefile (*path, file, encoding=None, errors=None, newline=""*)

Set a file to the contents of a file object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **file** (*io.IOBase*) – A file object open for reading.
- **encoding** (*str, optional*) – Encoding of destination file, defaults to `None` for binary.
- **errors** (*str, optional*) – How encoding errors should be treated (same as `io.open`).
- **newline** (*str*) – Newline parameter (same as `io.open`).

This method is similar to `upload`, in that it copies data from a file-like object to a resource on the filesystem, but unlike `upload`, this method also supports creating files in text-mode (if the `encoding` argument is supplied).

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('myfile.txt') as read_file:
...     my_fs.writefile('myfile.txt', read_file)
```

writetext (*path, contents, encoding='utf-8', errors=None, newline=""*)

Create or replace a file with text.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*str*) – Text to be written.
- **encoding** (*str, optional*) – Encoding of destination file (defaults to `'utf-8'`).
- **errors** (*str, optional*) – How encoding errors should be treated (same as `io.open`).
- **newline** (*str*) – Newline parameter (same as `io.open`).

Raises `TypeError` – if `contents` is not a unicode string.

13.2 fs.compress

Functions to compress the contents of a filesystem.

Currently zip and tar are supported, using the `zipfile` and `tarfile` modules from the standard library.

`fs.compress.write_tar(src_fs, file, compression=None, encoding='utf-8', walker=None)`

Write the contents of a filesystem to a tar file.

Parameters

- **file** (*str* or *io.IOBase*) – Destination file, may be a file name or an open file object.
- **compression** (*str*, *optional*) – Compression to use, or `None` for a plain Tar archive without compression.
- **encoding** (*str*) – The encoding to use for filenames. The default is "utf-8".
- **walker** (*Walker*, *optional*) – A `Walker` instance, or `None` to use default walker. You can use this to specify which files you want to compress.

`fs.compress.write_zip(src_fs, file, compression=8, encoding='utf-8', walker=None)`

Write the contents of a filesystem to a zip file.

Parameters

- **src_fs** (*FS*) – The source filesystem to compress.
- **file** (*str* or *io.IOBase*) – Destination file, may be a file name or an open file object.
- **compression** (*int*) – Compression to use (one of the constants defined in the `zipfile` module in the `stdlib`). Defaults to `zipfile.ZIP_DEFLATED`.
- **encoding** (*str*) – The encoding to use for filenames. The default is "utf-8", use "CP437" if compatibility with WinZip is desired.
- **walker** (*Walker*, *optional*) – A `Walker` instance, or `None` to use default walker. You can use this to specify which files you want to compress.

13.3 fs.copy

Functions for copying resources *between* filesystem.

`fs.copy.copy_dir(src_fs, src_path, dst_fs, dst_path, walker=None, on_copy=None, workers=0)`

Copy a directory from one filesystem to another.

Parameters

- **src_fs** (*FS* or *str*) – Source filesystem (instance or URL).
- **src_path** (*str*) – Path to a directory on the source filesystem.
- **dst_fs** (*FS* or *str*) – Destination filesystem (instance or URL).
- **dst_path** (*str*) – Path to a directory on the destination filesystem.
- **walker** (*Walker*, *optional*) – A walker object that will be used to scan for files in `src_fs`. Set this if you only want to consider a sub-set of the resources in `src_fs`.

- **on_copy** (*callable, optional*) – A function callback called after a single file copy is executed. Expected signature is (*src_fs, src_path, dst_fs, dst_path*).
- **workers** (*int*) – Use `worker` threads to copy data, or 0 (default) for a single-threaded copy.

`fs.copy.copy_dir_if_newer(src_fs, src_path, dst_fs, dst_path, walker=None, on_copy=None, workers=0)`

Copy a directory from one filesystem to another, checking times.

If both source and destination files exist, the copy is executed only if the source file is newer than the destination file. In case modification times of source or destination files are not available, copy is always executed.

Parameters

- **src_fs** (*FS or str*) – Source filesystem (instance or URL).
- **src_path** (*str*) – Path to a directory on the source filesystem.
- **dst_fs** (*FS or str*) – Destination filesystem (instance or URL).
- **dst_path** (*str*) – Path to a directory on the destination filesystem.
- **walker** (*Walker, optional*) – A walker object that will be used to scan for files in `src_fs`. Set this if you only want to consider a sub-set of the resources in `src_fs`.
- **on_copy** (*callable, optional*) – A function callback called after a single file copy is executed. Expected signature is (*src_fs, src_path, dst_fs, dst_path*).
- **workers** (*int*) – Use `worker` threads to copy data, or 0 (default) for a single-threaded copy.

`fs.copy.copy_file(src_fs, src_path, dst_fs, dst_path)`

Copy a file from one filesystem to another.

If the destination exists, and is a file, it will be first truncated.

Parameters

- **src_fs** (*FS or str*) – Source filesystem (instance or URL).
- **src_path** (*str*) – Path to a file on the source filesystem.
- **dst_fs** (*FS or str*) – Destination filesystem (instance or URL).
- **dst_path** (*str*) – Path to a file on the destination filesystem.

`fs.copy.copy_file_if_newer(src_fs, src_path, dst_fs, dst_path)`

Copy a file from one filesystem to another, checking times.

If the destination exists, and is a file, it will be first truncated. If both source and destination files exist, the copy is executed only if the source file is newer than the destination file. In case modification times of source or destination files are not available, copy is always executed.

Parameters

- **src_fs** (*FS or str*) – Source filesystem (instance or URL).
- **src_path** (*str*) – Path to a file on the source filesystem.
- **dst_fs** (*FS or str*) – Destination filesystem (instance or URL).
- **dst_path** (*str*) – Path to a file on the destination filesystem.

Returns `True` if the file copy was executed, `False` otherwise.

Return type `bool`

`fs.copy.copy_file_internal(src_fs, src_path, dst_fs, dst_path)`

Low level copy, that doesn't call `manage_fs` or `lock`.

If the destination exists, and is a file, it will be first truncated.

This method exists to optimize copying in loops. In general you should prefer `copy_file`.

Parameters

- **src_fs** (`FS`) – Source filesystem.
- **src_path** (`str`) – Path to a file on the source filesystem.
- (**FS** (`dst_fs`) – Destination filesystem.
- **dst_path** (`str`) – Path to a file on the destination filesystem.

`fs.copy.copy_fs(src_fs, dst_fs, walker=None, on_copy=None, workers=0)`

Copy the contents of one filesystem to another.

Parameters

- **src_fs** (`FS` or `str`) – Source filesystem (URL or instance).
- **dst_fs** (`FS` or `str`) – Destination filesystem (URL or instance).
- **walker** (`Walker`, *optional*) – A walker object that will be used to scan for files in `src_fs`. Set this if you only want to consider a sub-set of the resources in `src_fs`.
- **on_copy** (*callable*) – A function callback called after a single file copy is executed. Expected signature is (`src_fs`, `src_path`, `dst_fs`, `dst_path`).
- **workers** (`int`) – Use `worker` threads to copy data, or 0 (default) for a single-threaded copy.

`fs.copy.copy_fs_if_newer(src_fs, dst_fs, walker=None, on_copy=None, workers=0)`

Copy the contents of one filesystem to another, checking times.

If both source and destination files exist, the copy is executed only if the source file is newer than the destination file. In case modification times of source or destination files are not available, copy file is always executed.

Parameters

- **src_fs** (`FS` or `str`) – Source filesystem (URL or instance).
- **dst_fs** (`FS` or `str`) – Destination filesystem (URL or instance).
- **walker** (`Walker`, *optional*) – A walker object that will be used to scan for files in `src_fs`. Set this if you only want to consider a sub-set of the resources in `src_fs`.
- **on_copy** (*callable*) – A function callback called after a single file copy is executed. Expected signature is (`src_fs`, `src_path`, `dst_fs`, `dst_path`).
- **workers** (`int`) – Use `worker` threads to copy data, or 0 (default) for a single-threaded copy.

`fs.copy.copy_structure(src_fs, dst_fs, walker=None)`

Copy directories (but not files) from `src_fs` to `dst_fs`.

Parameters

- **src_fs** (`FS` or `str`) – Source filesystem (instance or URL).
- **dst_fs** (`FS` or `str`) – Destination filesystem (instance or URL).
- **walker** (`Walker`, *optional*) – A walker object that will be used to scan for files in `src_fs`. Set this if you only want to consider a sub-set of the resources in `src_fs`.

13.4 fs.enums

Enums used by PyFilesystem.

class `fs.enums.ResourceType`

Resource Types.

Positive values are reserved, negative values are implementation dependent.

Most filesystems will support only `directory(1)` and `file(2)`. Other types exist to identify more exotic resource types supported by Linux filesystems.

unknown = 0

Unknown resource type, used if the filesystem is unable to tell what the resource is.

directory = 1

A directory.

file = 2

A simple file.

character = 3

A character file.

block_special_file = 4

A block special file.

fifo = 5

A first in first out file.

socket = 6

A socket.

symlink = 7

A symlink.

class `fs.enums.Seek`

Constants used by `io.IOBase.seek`.

These match `os.SEEK_CUR`, `os.SEEK_END`, and `os.SEEK_SET` from the standard library.

current = 1

Seek from the current file position.

end = 2

Seek from the end of the file.

set = 0

Seek from the start of the file.

13.5 fs.errors

Exception classes thrown by filesystem operations.

Errors relating to the underlying filesystem are translated in to one of the following exceptions.

All Exception classes are derived from `FSError` which may be used as a catch-all filesystem exception.

exception `fs.errors.BulkCopyFailed` (*errors*)

Bases: `fs.errors.FSError`

A copy operation failed in worker threads.

exception `fs.errors.CreateFailed` (*msg=None, exc=None*)

Bases: `fs.errors.FSError`

Filesystem could not be created.

exception `fs.errors.DestinationExists` (*path, exc=None, msg=None*)

Bases: `fs.errors.ResourceError`

Target destination already exists.

exception `fs.errors.DirectoryExists` (*path, exc=None, msg=None*)

Bases: `fs.errors.ResourceError`

Directory already exists.

exception `fs.errors.DirectoryExpected` (*path, exc=None, msg=None*)

Bases: `fs.errors.ResourceInvalid`

Operation only works on directories.

exception `fs.errors.DirectoryNotEmpty` (*path, exc=None, msg=None*)

Bases: `fs.errors.ResourceError`

Attempt to remove a non-empty directory.

exception `fs.errors.FileExists` (*path, exc=None, msg=None*)

Bases: `fs.errors.ResourceError`

File already exists.

exception `fs.errors.FileExpected` (*path, exc=None, msg=None*)

Bases: `fs.errors.ResourceInvalid`

Operation only works on files.

exception `fs.errors.FilesystemClosed` (*msg=None*)

Bases: `fs.errors.FSError`

Attempt to use a closed filesystem.

exception `fs.errors.FSError` (*msg=None*)

Bases: `Exception`

Base exception for the `fs` module.

`__str__` ()

Return the error message.

exception `fs.errors.IllegalBackReference` (*path*)

Bases: `ValueError`

Too many backrefs exist in a path.

This error will occur if the back references in a path would be outside of the root. For example, `"/foo/../../../../"`, contains two back references which would reference a directory above the root.

Note: This exception is a subclass of `ValueError` as it is not strictly speaking an issue with a filesystem or resource.

exception `fs.errors.InsufficientStorage` (*path=None, exc=None, msg=None*)

Bases: `fs.errors.OperationFailed`

Storage is insufficient for requested operation.

exception `fs.errors.InvalidCharsInPath` (*path*, *msg=None*)

Bases: `fs.errors.InvalidPath`

Path contains characters that are invalid on this filesystem.

exception `fs.errors.InvalidPath` (*path*, *msg=None*)

Bases: `fs.errors.PathError`

Path can't be mapped on to the underlying filesystem.

exception `fs.errors.MissingInfoNamespace` (*namespace*)

Bases: `AttributeError`

An expected namespace is missing.

exception `fs.errors.NoSysPath` (*path*, *msg=None*)

Bases: `fs.errors.PathError`

The filesystem does not provide *sys paths* to the resource.

exception `fs.errors.NoURL` (*path*, *purpose*, *msg=None*)

Bases: `fs.errors.PathError`

The filesystem does not provide an URL for the resource.

exception `fs.errors.OperationFailed` (*path=None*, *exc=None*, *msg=None*)

Bases: `fs.errors.FSError`

A specific operation failed.

exception `fs.errors.OperationTimeout` (*path=None*, *exc=None*, *msg=None*)

Bases: `fs.errors.OperationFailed`

Filesystem took too long.

exception `fs.errors.PathError` (*path*, *msg=None*)

Bases: `fs.errors.FSError`

Base exception for errors to do with a path string.

exception `fs.errors.PermissionDenied` (*path=None*, *exc=None*, *msg=None*)

Bases: `fs.errors.OperationFailed`

Not enough permissions.

exception `fs.errors.RemoteConnectionError` (*path=None*, *exc=None*, *msg=None*)

Bases: `fs.errors.OperationFailed`

Operations encountered remote connection trouble.

exception `fs.errors.RemoveRootError` (*path=None*, *exc=None*, *msg=None*)

Bases: `fs.errors.OperationFailed`

Attempt to remove the root directory.

exception `fs.errors.ResourceError` (*path*, *exc=None*, *msg=None*)

Bases: `fs.errors.FSError`

Base exception class for error associated with a specific resource.

exception `fs.errors.ResourceInvalid` (*path*, *exc=None*, *msg=None*)

Bases: `fs.errors.ResourceError`

Resource has the wrong type.

exception `fs.errors.ResourceLocked` (*path, exc=None, msg=None*)

Bases: `fs.errors.ResourceError`

Attempt to use a locked resource.

exception `fs.errors.ResourceNotFound` (*path, exc=None, msg=None*)

Bases: `fs.errors.ResourceError`

Required resource not found.

exception `fs.errors.ResourceReadOnly` (*path, exc=None, msg=None*)

Bases: `fs.errors.ResourceError`

Attempting to modify a read-only resource.

exception `fs.errors.Unsupported` (*path=None, exc=None, msg=None*)

Bases: `fs.errors.OperationFailed`

Operation not supported by the filesystem.

13.6 fs.glob

class `fs.glob.BoundGlobber` (*fs*)

A *Globber* object bound to a filesystem.

An instance of this object is available on every Filesystem object as `.glob`.

Parameters `fs` (*FS*) – A filesystem object.

__call__ (*pattern, path='/', namespaces=None, case_sensitive=True, exclude_dirs=None*)

Match resources on the bound filesystem againsts a glob pattern.

Parameters

- **pattern** (*str*) – A glob pattern, e.g. `"**/*.py"`
- **namespaces** (*list*) – A list of additional info namespaces.
- **case_sensitive** (*bool*) – If `True`, the path matching will be case *sensitive* i.e. `"FOO.py"` and `"foo.py"` will be different, otherwise path matching will be case **in-sensitive**.
- **exclude_dirs** (*list*) – A list of patterns to exclude when searching, e.g. `["*.git"]`.

Returns An object that may be queried for the glob matches.

Return type *Globber*

class `fs.glob.Counts` (*files, directories, data*)

data

Alias for field number 2

directories

Alias for field number 1

files

Alias for field number 0

class `fs.glob.GlobMatch` (*path, info*)

info

Alias for field number 1

path

Alias for field number 0

```
class fs.glob.Globber(fs, pattern, path='/', namespaces=None, case_sensitive=True, exclude_dirs=None)
```

A generator of glob results.

Parameters

- **fs** (*FS*) – A filesystem object
- **pattern** (*str*) – A glob pattern, e.g. `"**/*.py"`
- **path** (*str*) – A path to a directory in the filesystem.
- **namespaces** (*list*) – A list of additional info namespaces.
- **case_sensitive** (*bool*) – If `True`, the path matching will be *case sensitive* i.e. `"FOO.py"` and `"foo.py"` will be different, otherwise path matching will be *case insensitive*.
- **exclude_dirs** (*list*) – A list of patterns to exclude when searching, e.g. `["*.git"]`.

__iter__()An iterator of `fs.glob.GlobMatch` objects.**count()**

Count files / directories / data in matched paths.

Example

```
>>> import fs
>>> fs.open_fs('~/projects').glob('**/*.py').count()
Counts(files=18519, directories=0, data=206690458)
```

Returns A named tuple containing results.**Return type** `Counts`**count_lines()**

Count the lines in the matched files.

Returns A named tuple containing line counts.**Return type** `LineCounts`**Example**

```
>>> import fs
>>> fs.open_fs('~/projects').glob('**/*.py').count_lines()
LineCounts(lines=5767102, non_blank=4915110)
```

remove()

Removed all matched paths.

Returns Number of file and directories removed.**Return type** `int`

Example

```
>>> import fs
>>> fs.open_fs('~/projects/my_project').glob('**/*.pyc').remove()
29
```

class `fs.glob.LineCounts` (*lines, non_blank*)

lines

Alias for field number 0

non_blank

Alias for field number 1

`fs.glob.imatch` (*pattern, path*)

Compare a glob pattern with a path (case insensitive).

Parameters

- **pattern** (*str*) – A glob pattern.
- **path** (*str*) – A path.

Returns True if the path matches the pattern.

Return type bool

`fs.glob.match` (*pattern, path*)

Compare a glob pattern with a path (case sensitive).

Parameters

- **pattern** (*str*) – A glob pattern.
- **path** (*str*) – A path.

Returns True if the path matches the pattern.

Return type bool

Example

```
>>> from fs.glob import match
>>> match("**/*.py", "/fs/glob.py")
True
```

13.7 fs.info

Container for filesystem resource informations.

class `fs.info.Info` (*raw_info, to_datetime=<function epoch_to_datetime>*)

Container for *Resource Info*.

Resource information is returned by the following methods:

- *getinfo*
- *scandir*

- `filterdir`

Parameters

- **raw_info** (*dict*) – A dict containing resource info.
- **to_datetime** (*callable*) – A callable that converts an epoch time to a datetime object. The default uses `epoch_to_datetime()`.

accessed

the resource last access time, or `None`.

Requires the "details" namespace.

Raises `MissingInfoNamespace` – if the "details" namespace is not in the Info.

Type `datetime`

copy (*to_datetime=None*)

Create a copy of this resource info object.

created

the resource creation time, or `None`.

Requires the "details" namespace.

Raises `MissingInfoNamespace` – if the "details" namespace is not in the Info.

Type `datetime`

get (*namespace, key, default=None*)

Get a raw info value.

Parameters

- **namespace** (*str*) – A namespace identifier.
- **key** (*str*) – A key within the namespace.
- **default** (*object, optional*) – A default value to return if either the namespace or the key within the namespace is not found.

Example

```
>>> info.get('access', 'permissions')
['u_r', 'u_w', '_wx']
```

gid

the group id of the resource, or `None`.

Requires the "access" namespace.

Raises `MissingInfoNamespace` – if the "access" namespace is not in the Info.

Type `int`

group

the group of the resource owner, or `None`.

Requires the "access" namespace.

Raises `MissingInfoNamespace` – if the "access" namespace is not in the Info.

Type `str`

has_namespace (*namespace*)

Check if the resource info contains a given namespace.

Parameters **namespace** (*str*) – A namespace identifier.

Returns `True` if the namespace was found, `False` otherwise.

Return type `bool`

is_dir

`True` if the resource references a directory.

Type `bool`

is_file

`True` if the resource references a file.

Type `bool`

is_link

`True` if the resource is a symlink.

Type `bool`

is_writeable (*namespace, key*)

Check if a given key in a namespace is writable.

Uses `setinfo`.

Parameters

- **namespace** (*str*) – A namespace identifier.
- **key** (*str*) – A key within the namespace.

Returns `True` if the key can be modified, `False` otherwise.

Return type `bool`

make_path (*dir_path*)

Make a path by joining `dir_path` with the resource name.

Parameters **dir_path** (*str*) – A path to a directory.

Returns A path to the resource.

Return type `str`

metadata_changed

the resource metadata change time, or `None`.

Requires the "details" namespace.

Raises `MissingInfoNamespace` – if the "details" namespace is not in the Info.

Type `datetime`

modified

the resource last modification time, or `None`.

Requires the "details" namespace.

Raises `MissingInfoNamespace` – if the "details" namespace is not in the Info.

Type `datetime`

name

the resource name.

Type `str`

permissions

the permissions of the resource, or `None`.

Requires the "access" namespace.

Raises `MissingInfoNamespace` – if the "access" namespace is not in the Info.

Type `Permissions`

size

the size of the resource, in bytes.

Requires the "details" namespace.

Raises `MissingInfoNamespace` – if the "details" namespace is not in the Info.

Type `int`

stem

the name minus any suffixes.

Example

```
>>> info
<info 'foo.tar.gz'>
>>> info.stem
'foo'
```

Type `str`

suffix

the last component of the name (including dot), or an empty string if there is no suffix.

Example

```
>>> info
<info 'foo.py'>
>>> info.suffix
'.py'
```

Type `str`

suffixes

a list of any suffixes in the name.

Example

```
>>> info
<info 'foo.tar.gz'>
>>> info.suffixes
['.tar', '.gz']
```

Type `List`

target

the link target (if resource is a symlink), or `None`.

Requires the "link" namespace.

Raises `MissingInfoNamespace` – if the "link" namespace is not in the Info.

Type `str`

type

the type of the resource.

Requires the "details" namespace.

Raises `MissingInfoNamespace` – if the 'details' namespace is not in the Info.

Type `ResourceType`

uid

the user id of the resource, or `None`.

Requires the "access" namespace.

Raises `MissingInfoNamespace` – if the "access" namespace is not in the Info.

Type `int`

user

the owner of the resource, or `None`.

Requires the "access" namespace.

Raises `MissingInfoNamespace` – if the "access" namespace is not in the Info.

Type `str`

13.8 fs.filesize

Functions for reporting file sizes.

The functions declared in this module should cover the different usecases needed to generate a string representation of a file size using several different units. Since there are many standards regarding file size units, three different functions have been implemented.

See also:

- [Wikipedia: Binary prefix](#)

`fs.filesize.traditional` (*size*)

Convert a filesize in to a string (powers of 1024, JDEC prefixes).

In this convention, $1024 \text{ B} = 1 \text{ KB}$.

This is the format that was used to display the size of DVDs (*700 MB* meaning actually about *734 003 200 bytes*) before standardisation of IEC units among manufacturers, and still used by **Windows** to report the storage capacity of hard drives (*279.4 GB* meaning $279.4 \times 1024^3 \text{ bytes}$).

Parameters `size` (*int*) – A file size.

Returns A string containing an abbreviated file size and units.

Return type `str`

Example

```
>>> filesize.traditional(30000)
'29.3 KB'
```

`fs.filesize.decimal` (*size*)

Convert a filesize in to a string (powers of 1000, SI prefixes).

In this convention, 1000 B = 1 kB.

This is typically the format used to advertise the storage capacity of USB flash drives and the like (*256 MB* meaning actually a storage capacity of more than *256 000 000 B*), or used by **Mac OS X** since v10.6 to report file sizes.

Parameters `int` (*size*) – A file size.

Returns A string containing a abbreviated file size and units.

Return type `str`

Example

```
>>> filesize.decimal(30000)
'30.0 kB'
```

`fs.filesize.binary` (*size*)

Convert a filesize in to a string (powers of 1024, IEC prefixes).

In this convention, 1024 B = 1 KiB.

This is the format that has gained adoption among manufacturers to avoid ambiguity regarding size units, since it explicitly states using a binary base (*KiB = kibi bytes = kilo binary bytes*). This format is notably being used by the **Linux** kernel (see `man 7 units`).

Parameters `int` (*size*) – A file size.

Returns A string containing a abbreviated file size and units.

Return type `str`

Example

```
>>> filesize.binary(30000)
'29.3 KiB'
```

13.9 fs.mirror

Function for *mirroring* a filesystem.

Mirroring will create a copy of a source filesystem on a destination filesystem. If there are no files on the destination, then mirroring is simply a straight copy. If there are any files or directories on the destination they may be deleted or modified to match the source.

In order to avoid redundant copying of files, *mirror* can compare timestamps, and only copy files with a newer modified date. This timestamp comparison is only done if the file sizes are different.

This scheme will work if you have mirrored a directory previously, and you would like to copy any changes. Otherwise you should set the `copy_if_newer` parameter to `False` to guarantee an exact copy, at the expense of potentially copying extra files.

```
fs.mirror.mirror(src_fs, dst_fs, walker=None, copy_if_newer=True, workers=0)
```

Mirror files / directories from one filesystem to another.

Mirroring a filesystem will create an exact copy of `src_fs` on `dst_fs`, by removing any files / directories on the destination that aren't on the source, and copying files that aren't.

Parameters

- **src_fs** (`FS` or `str`) – Source filesystem (URL or instance).
- **dst_fs** (`FS` or `str`) – Destination filesystem (URL or instance).
- **walker** (`Walker`, *optional*) – An optional walker instance.
- **copy_if_newer** (`bool`) – Only copy newer files (the default).
- **workers** (`int`) – Number of worker threads used (0 for single threaded). Set to a relatively low number for network filesystems, 4 would be a good start.

13.10 fs.move

Functions for moving files between filesystems.

```
fs.move.move_dir(src_fs, src_path, dst_fs, dst_path, workers=0)
```

Move a directory from one filesystem to another.

Parameters

- **src_fs** (`FS` or `str`) – Source filesystem (instance or URL).
- **src_path** (`str`) – Path to a directory on `src_fs`
- **dst_fs** (`FS` or `str`) – Destination filesystem (instance or URL).
- **dst_path** (`str`) – Path to a directory on `dst_fs`.
- **workers** (`int`) – Use `worker` threads to copy data, or 0 (default) for a single-threaded copy.

```
fs.move.move_file(src_fs, src_path, dst_fs, dst_path)
```

Move a file from one filesystem to another.

Parameters

- **src_fs** (`FS` or `str`) – Source filesystem (instance or URL).
- **src_path** (`str`) – Path to a file on `src_fs`.
- **dst_fs** (`FS` or `str`); *Destination filesystem (instance or URL)* –
- **dst_path** (`str`) – Path to a file on `dst_fs`.

```
fs.move.move_fs(src_fs, dst_fs, workers=0)
```

Move the contents of a filesystem to another filesystem.

Parameters

- **src_fs** (`FS` or `str`) – Source filesystem (instance or URL).
- **dst_fs** (`FS` or `str`) – Destination filesystem (instance or URL).

- **workers** (*int*) – Use `worker` threads to copy data, or 0 (default) for a single-threaded copy.

13.11 fs.mode

Abstract I/O mode container.

Mode strings are used in `open` and `openbin`.

class `fs.mode.Mode` (*mode*)

An abstraction for I/O modes.

A mode object provides properties that can be used to interrogate the `mode strings` used when opening files.

Parameters `mode` (*str*) – A *mode* string, as used by `io.open`.

Raises `ValueError` – If the mode string is invalid.

Example

```
>>> mode = Mode('rb')
>>> mode.reading
True
>>> mode.writing
False
>>> mode.binary
True
>>> mode.text
False
```

__contains__ (*character*)

Check if a mode contains a given character.

appending

`True` if the mode permits appending.

Type `bool`

binary

`True` if a mode specifies binary.

Type `bool`

create

`True` if the mode would create a file.

Type `bool`

exclusive

`True` if the mode require exclusive creation.

Type `bool`

reading

`True` if the mode permits reading.

Type `bool`

text

`True` if a mode specifies text.

Type `bool`

to_platform()

Get a mode string for the current platform.

Currently, this just removes the 'x' on PY2 because PY2 doesn't support exclusive mode.

to_platform_bin()

Get a *binary* mode string for the current platform.

Currently, this just removes the 'x' on PY2 because PY2 doesn't support exclusive mode.

truncate

`True` if the mode would truncate an existing file.

Type `bool`

updating

`True` if the mode permits both reading and writing.

Type `bool`

validate (*_valid_chars=frozenset({'b', '+', 'w', 'r', 'x', 'a', 't'})*)

Validate the mode string.

Raises `ValueError` – if the mode contains invalid chars.

validate_bin()

Validate a mode for opening a binary file.

Raises `ValueError` – if the mode contains invalid chars.

writing

`True` if the mode permits writing.

Type `bool`

`fs.mode.check_readable(mode)`

Check a mode string allows reading.

Parameters `mode` (*str*) – A mode string, e.g. "rt"

Returns `True` if the mode allows reading.

Return type `bool`

`fs.mode.check_writable(mode)`

Check a mode string allows writing.

Parameters `mode` (*str*) – A mode string, e.g. "wt"

Returns `True` if the mode allows writing.

Return type `bool`

`fs.mode.validate_openbin_mode(mode, _valid_chars=frozenset({'b', '+', 'w', 'r', 'x', 'a'}))`

Check mode parameter of `openbin` is valid.

Parameters `mode` (*str*) – Mode parameter.

Raises `ValueError` if mode is not valid.

13.12 fs.opener

Open filesystems from a URL.

13.12.1 fs.opener.base

Opener abstract base class.

class `fs.opener.base.Opener`

The base class for filesystem openers.

An opener is responsible for opening a filesystem for a given protocol.

open_fs (*fs_url*, *parse_result*, *writeable*, *create*, *cwd*)

Open a filesystem object from a FS URL.

Parameters

- **fs_url** (*str*) – A filesystem URL.
- **parse_result** (*ParseResult*) – A parsed filesystem URL.
- **writeable** (*bool*) – *True* if the filesystem must be writable.
- **create** (*bool*) – *True* if the filesystem should be created if it does not exist.
- **cwd** (*str*) – The current working directory (generally only relevant for OS filesystems).

Raises `fs.opener.errors.OpenerError` – If a filesystem could not be opened for any reason.

Returns A filesystem instance.

Return type *FS*

13.12.2 fs.opener.parse

Function to parse FS URLs in to their constituent parts.

class `fs.opener.parse.ParseResult`

A named tuple containing fields of a parsed FS URL.

protocol

The protocol part of the url, e.g. *osfs* or *ftp*.

Type *str*

username

A username, or *None*.

Type *str*, optional

password

A password, or *None*.

Type *str*, optional

resource

A *resource*, typically a domain and path, e.g. *ftp.example.org/dir*.

Type *str*

params

A dictionary of parameters extracted from the query string.

Type *dict*

path

A path within the filesystem, or *None*.

Type `str`, optional

`fs.opener.parse.parse_fs_url(fs_url)`

Parse a Filesystem URL and return a *ParseResult*.

Parameters `fs_url` (*str*) – A filesystem URL.

Returns a parse result instance.

Return type *ParseResult*

Raises `ParseError` – if the FS URL is not valid.

13.12.3 fs.opener.registry

Registry class mapping protocols and FS URLs to their Opener.

class `fs.opener.registry.Registry` (*default_opener='osfs', load_extern=False*)

A registry for Opener instances.

get_opener (*protocol*)

Get the opener class associated to a given protocol.

Parameters `protocol` (*str*) – A filesystem protocol.

Returns an opener instance.

Return type *Opener*

Raises

- *UnsupportedProtocol* – If no opener could be found for the given protocol.
- *EntryPointLoadingError* – If the returned entry point is not an Opener subclass or could not be loaded successfully.

install (*opener*)

Install an opener.

Parameters `opener` (*Opener*) – an Opener instance, or a callable that returns an opener instance.

Note:

May be used as a class decorator. For example:: `registry = Registry() @registry.install class ArchiveOpener(Opener):`

`protocols = ['zip', 'tar']`

manage_fs (*fs_url, create=False, writeable=False, cwd='.'*)

Get a context manager to open and close a filesystem.

Parameters

- `fs_url` (*FS or str*) – A filesystem instance or a FS URL.
- `create` (*bool, optional*) – If `True`, then create the filesystem if it doesn't already exist.
- `writeable` (*bool, optional*) – If `True`, then the filesystem must be writeable.
- `cwd` (*str*) – The current working directory, if opening a *OSFS*.

Sometimes it is convenient to be able to pass either a FS object *or* an FS URL to a function. This context manager handles the required logic for that.

Example

```
>>> def print_ls(list_fs):
...     '''List a directory.'''
...     with manage_fs(list_fs) as fs:
...         print(' '.join(fs.listdir()))
```

This function may be used in two ways. You may either pass a `str`, as follows:

```
>>> print_list('zip://projects.zip')
```

Or, an filesystem instance:

```
>>> from fs.osfs import OSFS
>>> projects_fs = OSFS('~/')
>>> print_list(projects_fs)
```

open (*fs_url*, *writeable=True*, *create=False*, *cwd='.'*, *default_protocol='osfs'*)

Open a filesystem from a FS URL.

Returns a tuple of a filesystem object and a path. If there is no path in the FS URL, the path value will be `None`.

Parameters

- **fs_url** (*str*) – A filesystem URL.
- **writeable** (*bool*, *optional*) – `True` if the filesystem must be writeable.
- **create** (*bool*, *optional*) – `True` if the filesystem should be created if it does not exist.
- **cwd** (*str*) – The current working directory.

Returns a tuple of (<filesystem>, <path from url>)

Return type (*FS*, *str*)

open_fs (*fs_url*, *writeable=False*, *create=False*, *cwd='.'*, *default_protocol='osfs'*)

Open a filesystem from a FS URL (ignoring the path component).

Parameters

- **fs_url** (*str*) – A filesystem URL.
- **writeable** (*bool*, *optional*) – `True` if the filesystem must be writeable.
- **create** (*bool*, *optional*) – `True` if the filesystem should be created if it does not exist.
- **cwd** (*str*) – The current working directory (generally only relevant for OS filesystems).
- **default_protocol** (*str*) – The protocol to use if one is not supplied in the FS URL (defaults to "osfs").

Returns A filesystem instance.

Return type *FS*

protocols

the list of supported protocols.

Type `list`

13.12.4 fs.opener.errors

Errors raised when attempting to open a filesystem.

exception `fs.opener.errors.EntryPointError`

Bases: `fs.opener.errors.OpenerError`

An entry point could not be loaded.

exception `fs.opener.errors.NotWriteable`

Bases: `fs.opener.errors.OpenerError`

A writable FS could not be created.

exception `fs.opener.errors.OpenerError`

Bases: `Exception`

Base exception for opener related errors.

exception `fs.opener.errors.ParseError`

Bases: `ValueError`

Attempt to parse an invalid FS URL.

exception `fs.opener.errors.UnsupportedProtocol`

Bases: `fs.opener.errors.OpenerError`

No opener found for the given protocol.

13.13 fs.path

Useful functions for working with PyFilesystem paths.

This is broadly similar to the standard `os.path` module but works with paths in the canonical format expected by all FS objects (that is, separated by forward slashes and with an optional leading slash).

See *Paths* for an explanation of PyFilesystem paths.

`fs.path.abspath(path)`

Convert the given path to an absolute path.

Since FS objects have no concept of a *current directory*, this simply adds a leading `/` character if the path doesn't already have one.

Parameters `path` (`str`) – A PyFilesystem path.

Returns An absolute path.

Return type `str`

`fs.path.basename(path)`

Return the basename of the resource referenced by a path.

This is always equivalent to the 'tail' component of the value returned by `split(path)`.

Parameters `path` (`str`) – A PyFilesystem path.

Returns the name of the resource at the given path.

Return type `str`

Example

```
>>> basename('foo/bar/baz')
'baz'
>>> basename('foo/bar')
'bar'
>>> basename('foo/bar/')
''
```

`fs.path.combine(path1, path2)`

Join two paths together.

This is faster than `join()`, but only works when the second path is relative, and there are no back references in either path.

Parameters

- **path1** (`str`) – A PyFilesystem path.
- **path2** (`str`) – A PyFilesystem path.

Returns The joint path.

Return type `str`

Example

```
>>> combine("foo/bar", "baz")
'foo/bar/baz'
```

`fs.path.dirname(path)`

Return the parent directory of a path.

This is always equivalent to the ‘head’ component of the value returned by `split(path)`.

Parameters **path** (`str`) – A PyFilesystem path.

Returns the parent directory of the given path.

Return type `str`

Example

```
>>> dirname('foo/bar/baz')
'foo/bar'
>>> dirname('/foo/bar')
'/foo'
>>> dirname('/foo')
'/'
```

`fs.path.forcedir(path)`

Ensure the path ends with a trailing forward slash.

Parameters **path** (`str`) – A PyFilesystem path.

Returns The path, ending with a slash.

Return type `str`

Example

```
>>> forcedir("foo/bar")
'foo/bar/'
>>> forcedir("foo/bar/")
'foo/bar/'
>>> forcedir("foo/spam.txt")
'foo/spam.txt/'
```

`fs.path.frombase(path1, path2)`

Get the final path of `path2` that isn't in `path1`.

Parameters

- **path1** (`str`) – A PyFilesystem path.
- **path2** (`str`) – A PyFilesystem path.

Returns the final part of `path2`.

Return type `str`

Example

```
>>> frombase('foo/bar/', 'foo/bar/baz/egg')
'baz/egg'
```

`fs.path.isabs(path)`

Check if a path is an absolute path.

Parameters **path** (`str`) – A PyFilesystem path.

Returns `True` if the path is absolute (starts with a `'/'`).

Return type `bool`

`fs.path.isbase(path1, path2)`

Check if `path1` is a base of `path2`.

Parameters

- **path1** (`str`) – A PyFilesystem path.
- **path2** (`str`) – A PyFilesystem path.

Returns `True` if `path2` starts with `path1`

Return type `bool`

Example

```
>>> isbase('foo/bar', 'foo/bar/baz/egg.txt')
True
```

`fs.path.isdotfile` (*path*)

Detect if a path references a dot file.

Parameters `path` (*str*) – Path to check.

Returns `True` if the resource name starts with a `'.'`.

Return type `bool`

Example

```
>>> isdotfile('.baz')
True
>>> isdotfile('foo/bar/.baz')
True
>>> isdotfile('foo/bar.baz')
False
```

`fs.path.isparent` (*path1*, *path2*)

Check if `path1` is a parent directory of `path2`.

Parameters

- `path1` (*str*) – A PyFilesystem path.
- `path2` (*str*) – A PyFilesystem path.

Returns `True` if `path1` is a parent directory of `path2`

Return type `bool`

Example

```
>>> isparent("foo/bar", "foo/bar/spam.txt")
True
>>> isparent("foo/bar/", "foo/bar")
True
>>> isparent("foo/barry", "foo/baz/bar")
False
>>> isparent("foo/bar/baz/", "foo/baz/bar")
False
```

`fs.path.issamedir` (*path1*, *path2*)

Check if two paths reference a resource in the same directory.

Parameters

- `path1` (*str*) – A PyFilesystem path.
- `path2` (*str*) – A PyFilesystem path.

Returns `True` if the two resources are in the same directory.

Return type `bool`

Example

```
>>> issamedir("foo/bar/baz.txt", "foo/bar/spam.txt")
True
>>> issamedir("foo/bar/baz/txt", "spam/eggs/spam.txt")
False
```

`fs.path.iswildcard(path)`

Check if a path ends with a wildcard.

Parameters `path` (*str*) – A PyFilesystem path.

Returns `True` if path ends with a wildcard.

Return type `bool`

Example

```
>>> iswildcard('foo/bar/baz.*')
True
>>> iswildcard('foo/bar')
False
```

`fs.path.iteratepath(path)`

Iterate over the individual components of a path.

Parameters `path` (*str*) – Path to iterate over.

Returns A list of path components.

Return type `list`

Example

```
>>> iteratepath('/foo/bar/baz')
['foo', 'bar', 'baz']
```

`fs.path.join(*paths)`

Join any number of paths together.

Parameters `*paths` (*str*) – Paths to join, given as positional arguments.

Returns The joined path.

Return type `str`

Example

```
>>> join('foo', 'bar', 'baz')
'foo/bar/baz'
>>> join('foo/bar', '../baz')
'foo/baz'
>>> join('foo/bar', '/baz')
'/baz'
```

`fs.path.normpath(path)`

Normalize a path.

This function simplifies a path by collapsing back-references and removing duplicated separators.

Parameters `path` (*str*) – Path to normalize.

Returns A valid FS path.

Return type `str`

Example

```
>>> normpath("/foo//bar/frob/../baz")
'/foo/bar/baz'
>>> normpath("foo/../../bar")
Traceback (most recent call last)
...
IllegalBackReference: path 'foo/../../bar' contains back-references outside of
↳filesystem"
```

`fs.path.parts` (*path*)

Split a path in to its component parts.

Parameters `path` (*str*) – Path to split in to parts.

Returns List of components

Return type `list`

Example

```
>>> parts('/foo/bar/baz')
['/', 'foo', 'bar', 'baz']
```

`fs.path.recursepath` (*path*, *reverse=False*)

Get intermediate paths from the root to the given path.

Parameters

- `path` (*str*) – A PyFilesystem path
- `reverse` (*bool*) – Reverses the order of the paths (default `False`).

Returns A list of paths.

Return type `list`

Example

```
>>> recursepath('a/b/c')
['/', '/a', '/a/b', '/a/b/c']
```

`fs.path.relativefrom` (*base*, *path*)

Return a path relative from a given base path.

Insert backrefs as appropriate to reach the path from the base.

Parameters

- `base` (*str*) – Path to a directory.
- `path` (*str*) – Path to make relative.

Returns the path to base from path.

Return type `str`

```
>>> relativefrom("foo/bar", "baz/index.html")
'../../baz/index.html'
```

`fs.path.relpath` (*path*)

Convert the given path to a relative path.

This is the inverse of `abspath`, stripping a leading `'/'` from the path if it is present.

Parameters `path` (*str*) – A path to adjust.

Returns A relative path.

Return type `str`

Example

```
>>> relpath('/a/b')
'a/b'
```

`fs.path.split` (*path*)

Split a path into (head, tail) pair.

This function splits a path into a pair (head, tail) where ‘tail’ is the last pathname component and ‘head’ is all preceding components.

Parameters `path` (*str*) – Path to split

Returns a tuple containing the head and the tail of the path.

Return type (`str`, `str`)

Example

```
>>> split("foo/bar")
('foo', 'bar')
>>> split("foo/bar/baz")
('foo/bar', 'baz')
>>> split("/foo/bar/baz")
('/foo/bar', 'baz')
```

`fs.path.splitext` (*path*)

Split the extension from the path.

Parameters `path` (*str*) – A path to split.

Returns A tuple containing the path and the extension.

Return type (`str`, `str`)

Example

```
>>> splittext('baz.txt')
('baz', '.txt')
>>> splittext('foo/bar/baz.txt')
('foo/bar/baz', '.txt')
>>> splittext('foo/bar/.foo')
('foo/bar/.foo', '')
```

13.14 fs.permissions

Abstract permissions container.

class `fs.permissions.Permissions` (*names=None, mode=None, user=None, group=None, other=None, sticky=None, setuid=None, setguid=None*)

An abstraction for file system permissions.

Permissions objects store information regarding the permissions on a resource. It supports Linux permissions, but is generic enough to manage permission information from almost any filesystem.

Parameters

- **names** (*list, optional*) – A list of permissions.
- **mode** (*int, optional*) – A mode integer.
- **user** (*str, optional*) – A triplet of *user* permissions, e.g. "rwx" or "r--"
- **group** (*str, optional*) – A triplet of *group* permissions, e.g. "rwx" or "r--"
- **other** (*str, optional*) – A triplet of *other* permissions, e.g. "rwx" or "r--"
- **sticky** (*bool, optional*) – A boolean for the *sticky* bit.
- **setuid** (*bool, optional*) – A boolean for the *setuid* bit.
- **setguid** (*bool, optional*) – A boolean for the *setguid* bit.

Example

```
>>> from fs.permissions import Permissions
>>> p = Permissions(user='rwx', group='rw-', other='r--')
>>> print(p)
rwxrw-r--
>>> p.mode
500
>>> oct(p.mode)
'0764'
```

add (**permissions*)
Add permission(s).

Parameters **permissions* (*str*) – Permission name(s), such as 'u_w' or 'u_x'.

as_str ()
Get a Linux-style string representation of permissions.

check (**permissions*)
Check if one or more permissions are enabled.

Parameters **permissions* (*str*) – Permission name(s), such as 'u_w' or 'u_x'.

Returns `True` if all given permissions are set.

Return type `bool`

copy()

Make a copy of this permissions object.

classmethod create (*init=None*)

Create a permissions object from an initial value.

Parameters *init* (*int or list, optional*) – May be `None` to use `0o777` permissions, a mode integer, or a list of permission names.

Returns mode integer that may be used for instance by `os.mkdir`.

Return type `int`

Example

```
>>> Permissions.create(None)
Permissions(user='rwx', group='rwx', other='rwx')
>>> Permissions.create(0o700)
Permissions(user='rwx', group='', other='')
>>> Permissions.create(['u_r', 'u_w', 'u_x'])
Permissions(user='rwx', group='', other='')
```

dump()

Get a list suitable for serialization.

g_r

Boolean for 'g_r' permission.

g_w

Boolean for 'g_w' permission.

g_x

Boolean for 'g_x' permission.

classmethod get_mode (*init*)

Convert an initial value to a mode integer.

classmethod load (*permissions*)

Load a serialized permissions object.

mode

mode integer.

Type `int`

o_r

Boolean for 'o_r' permission.

o_w

Boolean for 'o_w' permission.

o_x

Boolean for 'o_x' permission.

classmethod parse (*ls*)

Parse permissions in Linux notation.

remove (**permissions*)

Remove permission(s).

Parameters **permissions* (*str*) – Permission name(s), such as 'u_w' or 'u_x'.s

setguid

Boolean for 'setguid' permission.

setuid

Boolean for 'setuid' permission.

sticky

Boolean for 'sticky' permission.

u_r

Boolean for 'u_r' permission.

u_w

Boolean for 'u_w' permission.

u_x

Boolean for 'u_x' permission.

`fs.permissions.make_mode` (*init*)

Make a mode integer from an initial value.

13.15 fs.tools

Miscellaneous tools for operating on filesystems.

`fs.tools.copy_file_data` (*src_file*, *dst_file*, *chunk_size=None*)

Copy data from one file object to another.

Parameters

- **src_file** (*io.IOBase*) – File open for reading.
- **dst_file** (*io.IOBase*) – File open for writing.
- **chunk_size** (*int*) – Number of bytes to copy at a time (or *None* to use sensible default).

`fs.tools.get_intermediate_dirs` (*fs*, *dir_path*)

Get a list of non-existing intermediate directories.

Parameters

- **fs** (*FS*) – A filesystem instance.
- **dir_path** (*str*) – A path to a new directory on the filesystem.

Returns A list of non-existing paths.

Return type *list*

Raises *DirectoryExpected* – If a path component references a file and not a directory.

`fs.tools.is_thread_safe` (**filesystems*)

Check if all filesystems are thread-safe.

Parameters *filesystems* (*FS*) – Filesystems instances to check.

Returns if all filesystems are thread safe.

Return type *bool*

`fs.tools.remove_empty(fs, path)`
Remove all empty parents.

Parameters

- **fs** (`FS`) – A filesystem instance.
- **path** (`str`) – Path to a directory on the filesystem.

13.16 fs.tree

Render a FS object as text tree views.

Color is supported on UNIX terminals.

`fs.tree.render(fs, path='/', file=None, encoding=None, max_levels=5, with_color=None, dirs_first=True, exclude=None, filter=None)`
Render a directory structure in to a pretty tree.

Parameters

- **fs** (`FS`) – A filesystem instance.
- **path** (`str`) – The path of the directory to start rendering from (defaults to root folder, i.e. `'/'`).
- **file** (`io.IOBase`) – An open file-like object to render the tree, or `None` for stdout.
- **encoding** (`str`, *optional*) – Unicode encoding, or `None` to auto-detect.
- **max_levels** (`int`, *optional*) – Maximum number of levels to display, or `None` for no maximum.
- **with_color** (`bool`, *optional*) – Enable terminal color output, or `None` to auto-detect terminal.
- **dirs_first** (`bool`) – Show directories first.
- **exclude** (`list`, *optional*) – Option list of directory patterns to exclude from the tree render.
- **filter** (`list`, *optional*) – Optional list of files patterns to match in the tree render.

Returns A tuple of (<directory count>, <file count>).

Return type (`int`, `int`)

13.17 fs.walk

Machinery for walking a filesystem.

Walking a filesystem means recursively visiting a directory and any sub-directories. It is a fairly common requirement for copying, searching etc. See *Walking* for details.

class `fs.walk.BoundsWalker` (`fs`, `walker_class=<class 'fs.walk.Walker'>`)
A class that binds a *Walker* instance to a FS instance.

Parameters

- **fs** (`FS`) – A filesystem instance.
- **walker_class** (`type`) – A `WalkerBase` sub-class. The default uses *Walker*.

You will typically not need to create instances of this class explicitly. Filesystems have a `walk` property which returns a `BoundWalker` object.

Example

```
>>> import fs
>>> home_fs = fs.open_fs('~/')
>>> home_fs.walk
BoundWalker(OSFS('/Users/will', encoding='utf-8'))
```

A `BoundWalker` is callable. Calling it is an alias for `walk`.

`__call__` (*path*='/', *namespaces*=None, ***kwargs*)

Walk the directory structure of a filesystem.

Parameters

- **path** (*str*) –
- **namespaces** (*list*, *optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'] (defaults to ['basic']).

Keyword Arguments

- **ignore_errors** (*bool*) – If `True`, any errors reading a directory will be ignored, otherwise exceptions will be raised.
- **on_error** (*callable*) – If `ignore_errors` is `False`, then this callable will be invoked with a path and the exception object. It should return `True` to ignore the error, or `False` to re-raise it.
- **search** (*str*) – If 'breadth' then the directory will be walked *top down*. Set to 'depth' to walk *bottom up*.
- **filter** (*list*) – If supplied, this parameter should be a list of file name patterns, e.g. ['*.py']. Files will only be returned if the final component matches one of the patterns.
- **exclude** (*list*, *optional*) – If supplied, this parameter should be a list of filename patterns, e.g. ['~*', '*.']. Files matching any of these patterns will be removed from the walk.
- **filter_dirs** (*list*, *optional*) – A list of patterns that will be used to match directories paths. The walk will only open directories that match at least one of these patterns.
- **exclude_dirs** (*list*) – A list of patterns that will be used to filter out directories from the walk, e.g. ['*.svn', '*.git'].
- **max_depth** (*int*, *optional*) – Maximum directory depth to walk.

Returns an iterator of (<path>, <dirs>, <files>) named tuples, where <path> is an absolute path to a directory, and <dirs> and <files> are a list of `Info` objects for directories and files in <path>.

Return type Iterator

Example

```

>>> home_fs = open_fs('~/')
>>> walker = Walker(filter=['*.py'])
>>> for path, dirs, files in walker.walk(home_fs, namespaces=['details']):
...     print("{} {}".format(path))
...     print("{} directories".format(len(dirs)))
...     total = sum(info.size for info in files)
...     print("{} bytes {}".format(total))

```

This method invokes `Walker.walk` with bound FS object.

dirs (*path*='/', ***kwargs*)

Walk a filesystem, yielding absolute paths to directories.

Parameters *path* (*str*) – A path to a directory.

Keyword Arguments

- **ignore_errors** (*bool*) – If `True`, any errors reading a directory will be ignored, otherwise exceptions will be raised.
- **on_error** (*callable*) – If `ignore_errors` is `False`, then this callable will be invoked with a path and the exception object. It should return `True` to ignore the error, or `False` to re-raise it.
- **search** (*str*) – If 'breadth' then the directory will be walked *top down*. Set to 'depth' to walk *bottom up*.
- **filter_dirs** (*list*, *optional*) – A list of patterns that will be used to match directories paths. The walk will only open directories that match at least one of these patterns.
- **exclude_dirs** (*list*) – A list of patterns that will be used to filter out directories from the walk, e.g. ['*.svn', '*.git'].
- **max_depth** (*int*, *optional*) – Maximum directory depth to walk.

Returns an iterator over directory paths (absolute from the filesystem root).

Return type Iterator

This method invokes `Walker.dirs` with the bound FS object.

files (*path*='/', ***kwargs*)

Walk a filesystem, yielding absolute paths to files.

Parameters *path* (*str*) – A path to a directory.

Keyword Arguments

- **ignore_errors** (*bool*) – If `True`, any errors reading a directory will be ignored, otherwise exceptions will be raised.
- **on_error** (*callable*) – If `ignore_errors` is `False`, then this callable will be invoked with a path and the exception object. It should return `True` to ignore the error, or `False` to re-raise it.
- **search** (*str*) – If 'breadth' then the directory will be walked *top down*. Set to 'depth' to walk *bottom up*.
- **filter** (*list*) – If supplied, this parameter should be a list of file name patterns, e.g. ['*.py']. Files will only be returned if the final component matches one of the patterns.

- **exclude** (*list, optional*) – If supplied, this parameter should be a list of filename patterns, e.g. ['~*', '*.']. Files matching any of these patterns will be removed from the walk.
- **filter_dirs** (*list, optional*) – A list of patterns that will be used to match directories paths. The walk will only open directories that match at least one of these patterns.
- **exclude_dirs** (*list*) – A list of patterns that will be used to filter out directories from the walk, e.g. ['*.svn', '*.git'].
- **max_depth** (*int, optional*) – Maximum directory depth to walk.

Returns An iterator over file paths (absolute from the filesystem root).

Return type Iterator

This method invokes *Walker.files* with the bound FS object.

info (*path='/', namespaces=None, **kwargs*)

Walk a filesystem, yielding path and Info of resources.

Parameters

- **path** (*str*) – A path to a directory.
- **namespaces** (*list, optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'] (defaults to ['basic']).

Keyword Arguments

- **ignore_errors** (*bool*) – If `True`, any errors reading a directory will be ignored, otherwise exceptions will be raised.
- **on_error** (*callable*) – If `ignore_errors` is `False`, then this callable will be invoked with a path and the exception object. It should return `True` to ignore the error, or `False` to re-raise it.
- **search** (*str*) – If 'breadth' then the directory will be walked *top down*. Set to 'depth' to walk *bottom up*.
- **filter** (*list*) – If supplied, this parameter should be a list of file name patterns, e.g. ['*.py']. Files will only be returned if the final component matches one of the patterns.
- **exclude** (*list, optional*) – If supplied, this parameter should be a list of filename patterns, e.g. ['~*', '*.']. Files matching any of these patterns will be removed from the walk.
- **filter_dirs** (*list, optional*) – A list of patterns that will be used to match directories paths. The walk will only open directories that match at least one of these patterns.
- **exclude_dirs** (*list*) – A list of patterns that will be used to filter out directories from the walk, e.g. ['*.svn', '*.git'].
- **max_depth** (*int, optional*) – Maximum directory depth to walk.

Returns an iterable yielding tuples of (<absolute path>, <resource info>).

Return type Iterable

This method invokes *Walker.info* with the bound FS object.

walk (*path='/', namespaces=None, **kwargs*)

Walk the directory structure of a filesystem.

Parameters

- **path** (*str*) –
- **namespaces** (*list, optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'] (defaults to ['basic']).

Keyword Arguments

- **ignore_errors** (*bool*) – If `True`, any errors reading a directory will be ignored, otherwise exceptions will be raised.
- **on_error** (*callable*) – If `ignore_errors` is `False`, then this callable will be invoked with a path and the exception object. It should return `True` to ignore the error, or `False` to re-raise it.
- **search** (*str*) – If 'breadth' then the directory will be walked *top down*. Set to 'depth' to walk *bottom up*.
- **filter** (*list*) – If supplied, this parameter should be a list of file name patterns, e.g. ['*.py']. Files will only be returned if the final component matches one of the patterns.
- **exclude** (*list, optional*) – If supplied, this parameter should be a list of filename patterns, e.g. ['~*', '.*']. Files matching any of these patterns will be removed from the walk.
- **filter_dirs** (*list, optional*) – A list of patterns that will be used to match directories paths. The walk will only open directories that match at least one of these patterns.
- **exclude_dirs** (*list*) – A list of patterns that will be used to filter out directories from the walk, e.g. ['*.svn', '*.git'].
- **max_depth** (*int, optional*) – Maximum directory depth to walk.

Returns an iterator of (<path>, <dirs>, <files>) named tuples, where <path> is an absolute path to a directory, and <dirs> and <files> are a list of *Info* objects for directories and files in <path>.

Return type Iterator

Example

```
>>> home_fs = open_fs('~/')
>>> walker = Walker(filter=['*.py'])
>>> for path, dirs, files in walker.walk(home_fs, namespaces=['details']):
...     print("{}".format(path))
...     print("{} directories".format(len(dirs)))
...     total = sum(info.size for info in files)
...     print("{} bytes {}".format(total))
```

This method invokes *Walker.walk* with bound FS object.

class `fs.walk.Step` (*path, dirs, files*)

type: a *step* in a directory walk.

dirs

Alias for field number 1

files

Alias for field number 2

path

Alias for field number 0

class `fs.walk.Walker` (*ignore_errors=False, on_error=None, search='breadth', filter=None, exclude=None, filter_dirs=None, exclude_dirs=None, max_depth=None*)

A walker object recursively lists directories in a filesystem.

Parameters

- **ignore_errors** (*bool*) – If `True`, any errors reading a directory will be ignored, otherwise exceptions will be raised.
- **on_error** (*callable, optional*) – If `ignore_errors` is `False`, then this callable will be invoked for a path and the exception object. It should return `True` to ignore the error, or `False` to re-raise it.
- **search** (*str*) – If `'breadth'` then the directory will be walked *top down*. Set to `'depth'` to walk *bottom up*.
- **filter** (*list, optional*) – If supplied, this parameter should be a list of filename patterns, e.g. `['*.py']`. Files will only be returned if the final component matches one of the patterns.
- **exclude** (*list, optional*) – If supplied, this parameter should be a list of filename patterns, e.g. `['~*']`. Files matching any of these patterns will be removed from the walk.
- **filter_dirs** (*list, optional*) – A list of patterns that will be used to match directories paths. The walk will only open directories that match at least one of these patterns.
- **exclude_dirs** (*list, optional*) – A list of patterns that will be used to filter out directories from the walk. e.g. `['*.svn', '*.git']`.
- **max_depth** (*int, optional*) – Maximum directory depth to walk.

classmethod `bind` (*fs*)

Bind a `Walker` instance to a given filesystem.

This *binds* in instance of the `Walker` to a given filesystem, so that you won't need to explicitly provide the filesystem as a parameter.

Parameters `fs` (`FS`) – A filesystem object.

Returns a bound walker.

Return type `BoundWalker`

Example

```
>>> from fs import open_fs
>>> from fs.walk import Walker
>>> home_fs = open_fs('~/')
>>> walker = Walker.bind(home_fs)
>>> for path in walker.files(filter=['*.py']):
...     print(path)
```

Unless you have written a customized walker class, you will be unlikely to need to call this explicitly, as filesystem objects already have a `walk` attribute which is a bound walker object.

Example

```

>>> from fs import open_fs
>>> home_fs = open_fs('~/')
>>> for path in home_fs.walk.files(filter=['*.py']):
...     print(path)

```

check_file (*fs, info*)

Check if a filename should be included.

Override to exclude files from the walk.

Parameters

- **fs** (*FS*) – A filesystem instance.
- **info** (*Info*) – A resource info object.

Returns `True` if the file should be included.

Return type `bool`

check_open_dir (*fs, path, info*)

Check if a directory should be opened.

Override to exclude directories from the walk.

Parameters

- **fs** (*FS*) – A filesystem instance.
- **path** (*str*) – Path to directory.
- **info** (*Info*) – A resource info object for the directory.

Returns `True` if the directory should be opened.

Return type `bool`

check_scan_dir (*fs, path, info*)

Check if a directory should be scanned.

Override to omit scanning of certain directories. If a directory is omitted, it will appear in the walk but its files and sub-directories will not.

Parameters

- **fs** (*FS*) – A filesystem instance.
- **path** (*str*) – Path to directory.
- **info** (*Info*) – A resource info object for the directory.

Returns `True` if the directory should be scanned.

Return type `bool`

dirs (*fs, path=''*)

Walk a filesystem, yielding absolute paths to directories.

Parameters

- **fs** (*FS*) – A filesystem instance.
- **path** (*str*) – A path to a directory on the filesystem.

Yields *str* – absolute path to directories on the filesystem found recursively within the given directory.

files (*fs*, *path*='/')

Walk a filesystem, yielding absolute paths to files.

Parameters

- **fs** (*FS*) – A filesystem instance.
- **path** (*str*) – A path to a directory on the filesystem.

Yields *str* – absolute path to files on the filesystem found recursively within the given directory.

info (*fs*, *path*='/', *namespaces*=None)

Walk a filesystem, yielding tuples of (<path>, <info>).

Parameters

- **fs** (*FS*) – A filesystem instance.
- **path** (*str*) – A path to a directory on the filesystem.
- **namespaces** (*list*, *optional*) – A list of additional namespaces to add to the *Info* objects.

Yields (*str*, *Info*) – a tuple of (<absolute path>, <resource info>).

walk (*fs*, *path*='/', *namespaces*=None)

Walk the directory structure of a filesystem.

Parameters

- **fs** (*FS*) – A filesystem instance.
- **path** (*str*) – A path to a directory on the filesystem.
- **namespaces** (*list*, *optional*) – A list of additional namespaces to add to the *Info* objects.

Returns an iterator of *Step* instances.

Return type `collections.Iterator`

The return value is an iterator of (<path>, <dirs>, <files>) named tuples, where <path> is an absolute path to a directory, and <dirs> and <files> are a list of *Info* objects for directories and files in <path>.

Example

```
>>> home_fs = open_fs('~/')
>>> walker = Walker(filter=['*.py'])
>>> namespaces = ['details']
>>> for path, dirs, files in walker.walk(home_fs, namespaces)
...     print("{} {}".format(path))
...     print("{} directories".format(len(dirs)))
...     total = sum(info.size for info in files)
...     print("{} bytes {}".format(total))
```


13.18 fs.wildcard

Match wildcard filenames.

`fs.wildcard.get_matcher(patterns, case_sensitive)`

Get a callable that matches names against the given patterns.

Parameters

- **patterns** (*list*) – A list of wildcard pattern. e.g. `["*.py", "*.pyc"]`
- **case_sensitive** (*bool*) – If `True`, then the callable will be case sensitive, otherwise it will be case insensitive.

Returns a matcher that will return `True` if the name given as an argument matches any of the given patterns.

Return type callable

Example

```
>>> from fs import wildcard
>>> is_python = wildcard.get_matcher(['*.py'], True)
>>> is_python('__init__.py')
True
>>> is_python('foo.txt')
False
```

`fs.wildcard.imatch(pattern, name)`

Test whether a name matches a wildcard pattern (case insensitive).

Parameters

- **pattern** (*str*) – A wildcard pattern, e.g. `"*.py"`.
- **name** (*bool*) – A filename.

Returns `True` if the filename matches the pattern.

Return type `bool`

`fs.wildcard.imatch_any(patterns, name)`

Test if a name matches any of a list of patterns (case insensitive).

Will return `True` if `patterns` is an empty list.

Parameters

- **patterns** (*list*) – A list of wildcard pattern, e.g. `["*.py", "*.pyc"]`
- **name** (*str*) – A filename.

Returns `True` if the name matches at least one of the patterns.

Return type `bool`

`fs.wildcard.match(pattern, name)`

Test whether a name matches a wildcard pattern.

Parameters

- **pattern** (*str*) – A wildcard pattern, e.g. `"*.py"`.
- **name** (*str*) – A filename.

Returns `True` if the filename matches the pattern.

Return type `bool`

`fs.wildcard.match_any` (*patterns*, *name*)

Test if a name matches any of a list of patterns.

Will return `True` if *patterns* is an empty list.

Parameters

- **patterns** (*list*) – A list of wildcard pattern, e.g. `["*.py", "*.pyc"]`
- **name** (*str*) – A filename.

Returns `True` if the name matches at least one of the patterns.

Return type `bool`

13.19 fs.wrap

Collection of useful *WrapFS* subclasses.

Here's an example that opens a filesystem then makes it *read only*:

```
>>> from fs import open_fs
>>> from fs.wrap import read_only
>>> projects_fs = open_fs('~/projects')
>>> read_only_projects_fs = read_only(projects_fs)
>>> read_only_projects_fs.remove('__init__.py')
Traceback (most recent call last):
...
fs.errors.ResourceReadOnly: resource '__init__.py' is read only
```

class `fs.wrap.WrapCachedDir` (*wrap_fs*)

Caches filesystem directory information.

This filesystem caches directory information retrieved from a `scandir` call. This *may* speed up code that calls `isdir`, `isfile`, or `gettype` too frequently.

Note: Using this wrap will prevent changes to directory information being visible to the filesystem object. Consequently it is best used only in a fairly limited scope where you don't expect anything on the filesystem to change.

getinfo (*path*, *namespaces=None*)

Get information about a resource on a filesystem.

Parameters

- **path** (*str*) – A path to a resource on the filesystem.
- **namespaces** (*list*, *optional*) – Info namespaces to query (defaults to `[basic]`).

Returns resource information object.

Return type *Info*

For more information regarding resource information, see *Resource Info*.

isdir (*path*)

Check if a path maps to an existing directory.

Parameters `path` (*str*) – A path on the filesystem.

Returns `True` if `path` maps to a directory.

Return type `bool`

isfile (*path*)

Check if a path maps to an existing file.

Parameters `path` (*str*) – A path on the filesystem.

Returns `True` if `path` maps to a file.

Return type `bool`

scandir (*path*, *namespaces=None*, *page=None*)

Get an iterator of resource info.

Parameters

- **path** (*str*) – A path to a directory on the filesystem.
- **namespaces** (*list*, *optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'].
- **page** (*tuple*, *optional*) – May be a tuple of (<start>, <end>) indexes to return an iterator of a subset of the resource info, or `None` to iterate over the entire directory. Paging a directory scan may be necessary for very large directories.

Returns an iterator of `Info` objects.

Return type `Iterator`

Raises

- `fs.errors.DirectoryExpected` – If `path` is not a directory.
- `fs.errors.ResourceNotFound` – If `path` does not exist.

class `fs.wrap.WrapReadOnly` (*wrap_fs*)

Makes a Filesystem read-only.

Any call that would write data or modify the filesystem in any way will raise a `ResourceReadOnly` exception.

appendbytes (*path*, *data*)

Append bytes to the end of a file, creating it if needed.

Parameters

- **path** (*str*) – Path to a file.
- **data** (*bytes*) – Bytes to append.

Raises

- `TypeError` – If `data` is not a `bytes` instance.
- `fs.errors.ResourceNotFound` – If a parent directory of `path` does not exist.

appendtext (*path*, *text*, *encoding='utf-8'*, *errors=None*, *newline=""*)

Append text to the end of a file, creating it if needed.

Parameters

- **path** (*str*) – Path to a file.
- **text** (*str*) – Text to append.

- **encoding** (*str*) – Encoding for text files (defaults to `utf-8`).
- **errors** (*str*, *optional*) – What to do with unicode decode errors (see `codecs` module for more information).
- **newline** (*str*) – Newline parameter.

Raises

- `TypeError` – if `text` is not an unicode string.
- `fs.errors.ResourceNotFound` – if a parent directory of `path` does not exist.

copy (*src_path*, *dst_path*, *overwrite=False*)

Copy file contents from `src_path` to `dst_path`.

Parameters

- **src_path** (*str*) – Path of source file.
- **dst_path** (*str*) – Path to destination file.
- **overwrite** (*bool*) – If `True`, overwrite the destination file if it exists (defaults to `False`).

Raises

- `fs.errors.DestinationExists` – If `dst_path` exists, and `overwrite` is `False`.
- `fs.errors.ResourceNotFound` – If a parent directory of `dst_path` does not exist.

create (*path*, *wipe=False*)

Create an empty file.

The default behavior is to create a new file if one doesn't already exist. If `wipe` is `True`, any existing file will be truncated.

Parameters

- **path** (*str*) – Path to a new file in the filesystem.
- **wipe** (*bool*) – If `True`, truncate any existing file to 0 bytes (defaults to `False`).

Returns `True` if a new file had to be created.

Return type `bool`

makedir (*path*, *permissions=None*, *recreate=False*)

Make a directory.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (`Permissions`, *optional*) – a `Permissions` instance, or `None` to use default.
- **recreate** (*bool*) – Set to `True` to avoid raising an error if the directory already exists (defaults to `False`).

Returns a filesystem whose root is the new directory.

Return type `SubFS`

Raises

- `fs.errors.DirectoryExists` – If the path already exists.
- `fs.errors.ResourceNotFound` – If the path is not found.

makedirs (*path*, *permissions=None*, *recreate=False*)

Make a directory, and any missing intermediate directories.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (*Permissions*, *optional*) – Initial permissions, or `None` to use defaults.
- **recreate** (*bool*) – If `False` (the default), attempting to create an existing directory will raise an error. Set to `True` to ignore existing directories.

Returns A sub-directory filesystem.

Return type *SubFS*

Raises

- `fs.errors.DirectoryExists` – if the path is already a directory, and `recreate` is `False`.
- `fs.errors.DirectoryExpected` – if one of the ancestors in the path is not a directory.

move (*src_path*, *dst_path*, *overwrite=False*)

Move a file from `src_path` to `dst_path`.

Parameters

- **src_path** (*str*) – A path on the filesystem to move.
- **dst_path** (*str*) – A path on the filesystem where the source file will be written to.
- **overwrite** (*bool*) – If `True`, destination path will be overwritten if it exists.

Raises

- `fs.errors.FileExpected` – If `src_path` maps to a directory instead of a file.
- `fs.errors.DestinationExists` – If `dst_path` exists, and `overwrite` is `False`.
- `fs.errors.ResourceNotFound` – If a parent directory of `dst_path` does not exist.

open (*path*, *mode='r'*, *buffering=-1*, *encoding=None*, *errors=None*, *newline=""*, *line_buffering=False*, ***options*)

Open a file.

Parameters

- **path** (*str*) – A path to a file on the filesystem.
- **mode** (*str*) – Mode to open the file object with (defaults to `r`).
- **buffering** (*int*) – Buffering policy (`-1` to use default buffering, `0` to disable buffering, `1` to select line buffering, of any positive integer to indicate a buffer size).
- **encoding** (*str*) – Encoding for text files (defaults to `utf-8`)
- **errors** (*str*, *optional*) – What to do with unicode decode errors (see `codecs` module for more information).

- **newline** (*str*) – Newline parameter.
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (x in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

openbin (*path*, *mode='r'*, *buffering=-1*, ***options*)

Open a binary file-like object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **mode** (*str*) – Mode to open file (must be a valid non-text mode, defaults to *r*). Since this method only opens binary files, the *b* in the mode string is implied.
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, or any positive integer to indicate a buffer size).
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (x in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

remove (*path*)

Remove a file from the filesystem.

Parameters **path** (*str*) – Path of the file to remove.

Raises

- `fs.errors.FileExpected` – If the path is a directory.
- `fs.errors.ResourceNotFound` – If the path does not exist.

removedir (*path*)

Remove a directory from the filesystem.

Parameters **path** (*str*) – Path of the directory to remove.

Raises

- `fs.errors.DirectoryNotEmpty` – If the directory is not empty (see `removetree` for a way to remove the directory contents.).

- `fs.errors.DirectoryExpected` – If the path does not refer to a directory.
- `fs.errors.ResourceNotFound` – If no resource exists at the given path.
- `fs.errors.RemoveRootError` – If an attempt is made to remove the root directory (i.e. '/')

setinfo (*path*, *info*)

Set info on a resource.

This method is the complement to `getinfo` and is used to set info values on a resource.

Parameters

- **path** (*str*) – Path to a resource on the filesystem.
- **info** (*dict*) – Dictionary of resource info.

Raises `fs.errors.ResourceNotFound` – If `path` does not exist on the filesystem

The `info` dict should be in the same format as the raw info returned by `getinfo(file).raw`.

Example

```
>>> details_info = {"details": {
...     "modified": time.time()
... }}
>>> my_fs.setinfo('file.txt', details_info)
```

settimes (*path*, *accessed=None*, *modified=None*)

Set the accessed and modified time on a resource.

Parameters

- **path** – A path to a resource on the filesystem.
- **accessed** (*datetime*, *optional*) – The accessed time, or `None` (the default) to use the current time.
- **modified** (*datetime*, *optional*) – The modified time, or `None` (the default) to use the same time as the accessed parameter.

touch (*path*)

Touch a file on the filesystem.

Touching a file means creating a new file if `path` doesn't exist, or update accessed and modified times if the path does exist. This method is similar to the linux command of the same name.

Parameters **path** (*str*) – A path to a file on the filesystem.

upload (*path*, *file*, *chunk_size=None*, ***options*)

Set a file to the contents of a binary file object.

This method copies bytes from an open binary file to a file on the filesystem. If the destination exists, it will first be truncated.

Parameters

- **path** (*str*) – A path on the filesystem.
- **file** (*io.IOBase*) – a file object open for reading in binary mode.
- **chunk_size** (*int*, *optional*) – Number of bytes to read at a time, if a simple copy is used, or `None` to use sensible default.

- ****options** – Implementation specific options required to open the source file.

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('~/.movies/starwars.mov', 'rb') as read_file:
...     my_fs.upload('starwars.mov', read_file)
```

writebytes (*path, contents*)

Copy binary data to a file.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*bytes*) – Data to be written.

Raises `TypeError` – if contents is not bytes.

writefile (*path, file, encoding=None, errors=None, newline=""*)

Set a file to the contents of a file object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **file** (*io.IOBase*) – A file object open for reading.
- **encoding** (*str, optional*) – Encoding of destination file, defaults to `None` for binary.
- **errors** (*str, optional*) – How encoding errors should be treated (same as `io.open`).
- **newline** (*str*) – Newline parameter (same as `io.open`).

This method is similar to `upload`, in that it copies data from a file-like object to a resource on the filesystem, but unlike `upload`, this method also supports creating files in text-mode (if the `encoding` argument is supplied).

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('myfile.txt') as read_file:
...     my_fs.writefile('myfile.txt', read_file)
```

writetext (*path, contents, encoding='utf-8', errors=None, newline=""*)

Create or replace a file with text.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*str*) – Text to be written.
- **encoding** (*str, optional*) – Encoding of destination file (defaults to `'utf-8'`).

- **errors** (*str*, *optional*) – How encoding errors should be treated (same as `io.open`).
- **newline** (*str*) – Newline parameter (same as `io.open`).

Raises `TypeError` – if `contents` is not a unicode string.

`fs.wrap.cache_directory` (*fs*)

Make a filesystem that caches directory information.

Parameters **fs** (`FS`) – A filesystem instance.

Returns A filesystem that caches results of `scandir`, `isdir` and other methods which read directory information.

Return type `FS`

`fs.wrap.read_only` (*fs*)

Make a read-only filesystem.

Parameters **fs** (`FS`) – A filesystem instance.

Returns A read only version of `fs`

Return type `FS`

13.20 fs.wrapfs

Base class for filesystem wrappers.

class `fs.wrapfs.WrapFS` (*wrap_fs*)

A proxy for a filesystem object.

This class exposes an filesystem interface, where the data is stored on another filesystem(s), and is the basis for `SubFS` and other *virtual* filesystems.

appendbytes (*path*, *data*)

Append bytes to the end of a file, creating it if needed.

Parameters

- **path** (*str*) – Path to a file.
- **data** (*bytes*) – Bytes to append.

Raises

- `TypeError` – If `data` is not a `bytes` instance.
- `fs.errors.ResourceNotFound` – If a parent directory of `path` does not exist.

appendtext (*path*, *text*, *encoding='utf-8'*, *errors=None*, *newline=""*)

Append text to the end of a file, creating it if needed.

Parameters

- **path** (*str*) – Path to a file.
- **text** (*str*) – Text to append.
- **encoding** (*str*) – Encoding for text files (defaults to `utf-8`).
- **errors** (*str*, *optional*) – What to do with unicode decode errors (see `codecs` module for more information).

- **newline** (*str*) – Newline parameter.

Raises

- `TypeError` – if `text` is not an unicode string.
- `fs.errors.ResourceNotFound` – if a parent directory of `path` does not exist.

copy (*src_path*, *dst_path*, *overwrite=False*)

Copy file contents from `src_path` to `dst_path`.

Parameters

- **src_path** (*str*) – Path of source file.
- **dst_path** (*str*) – Path to destination file.
- **overwrite** (*bool*) – If `True`, overwrite the destination file if it exists (defaults to `False`).

Raises

- `fs.errors.DestinationExists` – If `dst_path` exists, and `overwrite` is `False`.
- `fs.errors.ResourceNotFound` – If a parent directory of `dst_path` does not exist.

copydir (*src_path*, *dst_path*, *create=False*)

Copy the contents of `src_path` to `dst_path`.

Parameters

- **src_path** (*str*) – Path of source directory.
- **dst_path** (*str*) – Path to destination directory.
- **create** (*bool*) – If `True`, then `dst_path` will be created if it doesn't exist already (defaults to `False`).

Raises `fs.errors.ResourceNotFound` – If the `dst_path` does not exist, and `create` is not `True`.

create (*path*, *wipe=False*)

Create an empty file.

The default behavior is to create a new file if one doesn't already exist. If `wipe` is `True`, any existing file will be truncated.

Parameters

- **path** (*str*) – Path to a new file in the filesystem.
- **wipe** (*bool*) – If `True`, truncate any existing file to 0 bytes (defaults to `False`).

Returns `True` if a new file had to be created.

Return type `bool`

delegate_fs ()

Get the proxied filesystem.

This method should return a filesystem for methods not associated with a path, e.g. `getmeta`.

delegate_path (*path*)

Encode a path for proxied filesystem.

Parameters **path** (*str*) – A path on the filesystem.

Returns a tuple of (<filesystem>, <new_path>)

Return type (*FS*, *str*)

desc (*path*)

Return a short descriptive text regarding a path.

Parameters **path** (*str*) – A path to a resource on the filesystem.

Returns a short description of the path.

Return type *str*

download (*path*, *file*, *chunk_size=None*, ***options*)

Copies a file from the filesystem to a file-like object.

This may be more efficient than opening and copying files manually if the filesystem supplies an optimized method.

Parameters

- **path** (*str*) – Path to a resource.
- **file** (*file-like*) – A file-like object open for writing in binary mode.
- **chunk_size** (*int*, *optional*) – Number of bytes to read at a time, if a simple copy is used, or *None* to use sensible default.
- ****options** – Implementation specific options required to open the source file.

Note that the file object *file* will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('starwars.mov', 'wb') as write_file:
...     my_fs.download('/movies/starwars.mov', write_file)
```

exists (*path*)

Check if a path maps to a resource.

Parameters **path** (*str*) – Path to a resource.

Returns *True* if a resource exists at the given path.

Return type *bool*

filterdir (*path*, *files=None*, *dirs=None*, *exclude_dirs=None*, *exclude_files=None*, *namespaces=None*, *page=None*)

Get an iterator of resource info, filtered by patterns.

This method enhances *scandir* with additional filtering functionality.

Parameters

- **path** (*str*) – A path to a directory on the filesystem.
- **files** (*list*, *optional*) – A list of UNIX shell-style patterns to filter file names, e.g. ['*.py'].
- **dirs** (*list*, *optional*) – A list of UNIX shell-style patterns to filter directory names.
- **exclude_dirs** (*list*, *optional*) – A list of patterns used to exclude directories.

- **exclude_files** (*list, optional*) – A list of patterns used to exclude files.
- **namespaces** (*list, optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'].
- **page** (*tuple, optional*) – May be a tuple of (<start>, <end>) indexes to return an iterator of a subset of the resource info, or `None` to iterate over the entire directory. Paging a directory scan may be necessary for very large directories.

Returns an iterator of `Info` objects.

Return type `Iterator`

getinfo (*path, namespaces=None*)

Get information about a resource on a filesystem.

Parameters

- **path** (*str*) – A path to a resource on the filesystem.
- **namespaces** (*list, optional*) – Info namespaces to query (defaults to [*basic*]).

Returns resource information object.

Return type `Info`

For more information regarding resource information, see [Resource Info](#).

getmeta (*namespace='standard'*)

Get meta information regarding a filesystem.

Parameters **namespace** (*str*) – The meta namespace (defaults to "standard").

Returns the meta information.

Return type `dict`

Meta information is associated with a *namespace* which may be specified with the `namespace` parameter. The default namespace, "standard", contains common information regarding the filesystem's capabilities. Some filesystems may provide other namespaces which expose less common or implementation specific information. If a requested namespace is not supported by a filesystem, then an empty dictionary will be returned.

The "standard" namespace supports the following keys:

key	Description
<code>case_insensitive</code>	<code>True</code> if this filesystem is case insensitive.
<code>invalid_path_chars</code>	A string containing the characters that may not be used on this filesystem.
<code>max_path_length</code>	Maximum number of characters permitted in a path, or <code>None</code> for no limit.
<code>max_sys_path_length</code>	Maximum number of characters permitted in a sys path, or <code>None</code> for no limit.
<code>network</code>	<code>True</code> if this filesystem requires a network.
<code>read_only</code>	<code>True</code> if this filesystem is read only.
<code>supports_rename</code>	<code>True</code> if this filesystem supports an <code>os.rename</code> operation.

Most builtin filesystems will provide all these keys, and third- party filesystems should do so whenever possible, but a key may not be present if there is no way to know the value.

Note: Meta information is constant for the lifetime of the filesystem, and may be cached.

getsize (*path*)

Get the size (in bytes) of a resource.

Parameters `path` (*str*) – A path to a resource.

Returns the *size* of the resource.

Return type `int`

The *size* of a file is the total number of readable bytes, which may not reflect the exact number of bytes of reserved disk space (or other storage medium).

The size of a directory is the number of bytes of overhead use to store the directory entry.

getsyspath (*path*)

Get the *system path* of a resource.

Parameters `path` (*str*) – A path on the filesystem.

Returns the *system path* of the resource, if any.

Return type `str`

Raises `fs.errors.NoSysPath` – If there is no corresponding system path.

A system path is one recognized by the OS, that may be used outside of PyFilesystem (in an application or a shell for example). This method will get the corresponding system path that would be referenced by `path`.

Not all filesystems have associated system paths. Network and memory based filesystems, for example, may not physically store data anywhere the OS knows about. It is also possible for some paths to have a system path, whereas others don't.

This method will always return a `str` on Py3.* and `unicode` on Py2.7. See `getospath` if you need to encode the path as bytes.

If `path` doesn't have a system path, a `NoSysPath` exception will be thrown.

Note: A filesystem may return a system path even if no resource is referenced by that path – as long as it can be certain what that system path would be.

gettype (*path*)

Get the type of a resource.

Parameters `path` (*str*) – A path on the filesystem.

Returns the type of the resource.

Return type `ResourceType`

A type of a resource is an integer that identifies the what the resource references. The standard type integers may be one of the values in the `ResourceType` enumerations.

The most common resource types, supported by virtually all filesystems are `directory` (1) and `file` (2), but the following types are also possible:

ResourceType	value
unknown	0
directory	1
file	2
character	3
block_special_file	4
fifo	5
socket	6
symlink	7

Standard resource types are positive integers, negative values are reserved for implementation specific resource types.

geturl (*path*, *purpose*='download')

Get the URL to a given resource.

Parameters

- **path** (*str*) – A path on the filesystem
- **purpose** (*str*) – A short string that indicates which URL to retrieve for the given path (if there is more than one). The default is 'download', which should return a URL that serves the file. Other filesystems may support other values for *purpose*.

Returns a URL.

Return type *str*

Raises *fs.errors.NoURL* – If the path does not map to a URL.

hash (*path*, *name*)

Get the hash of a file's contents.

Parameters

- **path** (*str*) – A path on the filesystem.
- **name** (*str*) – One of the algorithms supported by the hashlib module, e.g. "md5"

Returns The hex digest of the hash.

Return type *str*

Raises *fs.errors.UnsupportedHash* – If the requested hash is not supported.

hasyspath (*path*)

Check if a path maps to a system path.

Parameters **path** (*str*) – A path on the filesystem.

Returns *True* if the resource at *path* has a *syspath*.

Return type *bool*

hasurl (*path*, *purpose*='download')

Check if a path has a corresponding URL.

Parameters

- **path** (*str*) – A path on the filesystem.
- **purpose** (*str*) – A purpose parameter, as given in *geturl*.

Returns *True* if an URL for the given purpose exists.

Return type `bool`

isdir (*path*)

Check if a path maps to an existing directory.

Parameters `path` (*str*) – A path on the filesystem.

Returns `True` if `path` maps to a directory.

Return type `bool`

isfile (*path*)

Check if a path maps to an existing file.

Parameters `path` (*str*) – A path on the filesystem.

Returns `True` if `path` maps to a file.

Return type `bool`

islink (*path*)

Check if a path maps to a symlink.

Parameters `path` (*str*) – A path on the filesystem.

Returns `True` if `path` maps to a symlink.

Return type `bool`

listdir (*path*)

Get a list of the resource names in a directory.

This method will return a list of the resources in a directory. A *resource* is a file, directory, or one of the other types defined in *ResourceType*.

Parameters `path` (*str*) – A path to a directory on the filesystem

Returns list of names, relative to `path`.

Return type `list`

Raises

- `fs.errors.DirectoryExpected` – If `path` is not a directory.
- `fs.errors.ResourceNotFound` – If `path` does not exist.

lock ()

Get a context manager that *locks* the filesystem.

Locking a filesystem gives a thread exclusive access to it. Other threads will block until the threads with the lock has left the context manager.

Returns a lock specific to the filesystem instance.

Return type `threading.RLock`

Example

```
>>> with my_fs.lock(): # May block
...     # code here has exclusive access to the filesystem
```

It is a good idea to put a lock around any operations that you would like to be *atomic*. For instance if you are copying files, and you don't want another thread to delete or modify anything while the copy is in progress.

Locking with this method is only required for code that calls multiple filesystem methods. Individual methods are thread safe already, and don't need to be locked.

Note: This only locks at the Python level. There is nothing to prevent other processes from modifying the filesystem outside of the filesystem instance.

makedir (*path*, *permissions=None*, *recreate=False*)

Make a directory.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (*Permissions*, *optional*) – a *Permissions* instance, or *None* to use default.
- **recreate** (*bool*) – Set to *True* to avoid raising an error if the directory already exists (defaults to *False*).

Returns a filesystem whose root is the new directory.

Return type *SubFS*

Raises

- *fs.errors.DirectoryExists* – If the path already exists.
- *fs.errors.ResourceNotFound* – If the path is not found.

makedirs (*path*, *permissions=None*, *recreate=False*)

Make a directory, and any missing intermediate directories.

Parameters

- **path** (*str*) – Path to directory from root.
- **permissions** (*Permissions*, *optional*) – Initial permissions, or *None* to use defaults.
- **recreate** (*bool*) – If *False* (the default), attempting to create an existing directory will raise an error. Set to *True* to ignore existing directories.

Returns A sub-directory filesystem.

Return type *SubFS*

Raises

- *fs.errors.DirectoryExists* – if the path is already a directory, and *recreate* is *False*.
- *fs.errors.DirectoryExpected* – if one of the ancestors in the path is not a directory.

move (*src_path*, *dst_path*, *overwrite=False*)

Move a file from *src_path* to *dst_path*.

Parameters

- **src_path** (*str*) – A path on the filesystem to move.
- **dst_path** (*str*) – A path on the filesystem where the source file will be written to.
- **overwrite** (*bool*) – If *True*, destination path will be overwritten if it exists.

Raises

- `fs.errors.FileExpected` – If `src_path` maps to a directory instead of a file.
- `fs.errors.DestinationExists` – If `dst_path` exists, and `overwrite` is `False`.
- `fs.errors.ResourceNotFound` – If a parent directory of `dst_path` does not exist.

movedir (`src_path`, `dst_path`, `create=False`)

Move directory `src_path` to `dst_path`.

Parameters

- **src_path** (`str`) – Path of source directory on the filesystem.
- **dst_path** (`str`) – Path to destination directory.
- **create** (`bool`) – If `True`, then `dst_path` will be created if it doesn't exist already (defaults to `False`).

Raises `fs.errors.ResourceNotFound` – if `dst_path` does not exist, and `create` is `False`.

open (`path`, `mode='r'`, `buffering=-1`, `encoding=None`, `errors=None`, `newline=""`, `line_buffering=False`, `**options`)

Open a file.

Parameters

- **path** (`str`) – A path to a file on the filesystem.
- **mode** (`str`) – Mode to open the file object with (defaults to `r`).
- **buffering** (`int`) – Buffering policy (-1 to use default buffering, 0 to disable buffering, 1 to select line buffering, of any positive integer to indicate a buffer size).
- **encoding** (`str`) – Encoding for text files (defaults to `utf-8`)
- **errors** (`str`, `optional`) – What to do with unicode decode errors (see `codecs` module for more information).
- **newline** (`str`) – Newline parameter.
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and `exclusive mode` is specified (`x` in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

openbin (`path`, `mode='r'`, `buffering=-1`, `**options`)

Open a binary file-like object.

Parameters

- **path** (`str`) – A path on the filesystem.

- **mode** (*str*) – Mode to open file (must be a valid non-text mode, defaults to *r*). Since this method only opens binary files, the *b* in the mode string is implied.
- **buffering** (*int*) – Buffering policy (-1 to use default buffering, 0 to disable buffering, or any positive integer to indicate a buffer size).
- ****options** – keyword arguments for any additional information required by the filesystem (if any).

Returns a *file-like* object.

Return type `io.IOBase`

Raises

- `fs.errors.FileExpected` – If the path is not a file.
- `fs.errors.FileExists` – If the file exists, and *exclusive mode* is specified (*x* in the mode).
- `fs.errors.ResourceNotFound` – If the path does not exist.

opendir (*path*, *factory=None*)

Get a filesystem object for a sub-directory.

Parameters

- **path** (*str*) – Path to a directory on the filesystem.
- **factory** (*callable*, *optional*) – A callable that when invoked with an FS instance and *path* will return a new FS object representing the sub-directory contents. If no *factory* is supplied then `subfs_class` will be used.

Returns A filesystem representing a sub-directory.

Return type `SubFS`

Raises `fs.errors.DirectoryExpected` – If *dst_path* does not exist or is not a directory.

readbytes (*path*)

Get the contents of a file as bytes.

Parameters **path** (*str*) – A path to a readable file on the filesystem.

Returns the file contents.

Return type `bytes`

Raises `fs.errors.ResourceNotFound` – if *path* does not exist.

readtext (*path*, *encoding=None*, *errors=None*, *newline=""*)

Get the contents of a file as a string.

Parameters

- **path** (*str*) – A path to a readable file on the filesystem.
- **encoding** (*str*, *optional*) – Encoding to use when reading contents in text mode (defaults to `None`, reading in binary mode).
- **errors** (*str*, *optional*) – Unicode errors parameter.
- **newline** (*str*) – Newlines parameter.

Returns file contents.

Return type `str`

Raises *fs.errors.ResourceNotFound* – If *path* does not exist.

remove (*path*)

Remove a file from the filesystem.

Parameters *path* (*str*) – Path of the file to remove.

Raises

- *fs.errors.FileExpected* – If the path is a directory.
- *fs.errors.ResourceNotFound* – If the path does not exist.

removedir (*path*)

Remove a directory from the filesystem.

Parameters *path* (*str*) – Path of the directory to remove.

Raises

- *fs.errors.DirectoryNotEmpty* – If the directory is not empty (see *removetree* for a way to remove the directory contents.).
- *fs.errors.DirectoryExpected* – If the path does not refer to a directory.
- *fs.errors.ResourceNotFound* – If no resource exists at the given path.
- *fs.errors.RemoveRootError* – If an attempt is made to remove the root directory (i.e. '/')

removetree (*dir_path*)

Recursively remove the contents of a directory.

This method is similar to *removedir*, but will remove the contents of the directory if it is not empty.

Parameters *dir_path* (*str*) – Path to a directory on the filesystem.

scandir (*path*, *namespaces=None*, *page=None*)

Get an iterator of resource info.

Parameters

- **path** (*str*) – A path to a directory on the filesystem.
- **namespaces** (*list*, *optional*) – A list of namespaces to include in the resource information, e.g. ['basic', 'access'].
- **page** (*tuple*, *optional*) – May be a tuple of (<start>, <end>) indexes to return an iterator of a subset of the resource info, or *None* to iterate over the entire directory. Paging a directory scan may be necessary for very large directories.

Returns an iterator of *Info* objects.

Return type *Iterator*

Raises

- *fs.errors.DirectoryExpected* – If *path* is not a directory.
- *fs.errors.ResourceNotFound* – If *path* does not exist.

setinfo (*path*, *info*)

Set info on a resource.

This method is the complement to *getinfo* and is used to set info values on a resource.

Parameters

- **path** (*str*) – Path to a resource on the filesystem.
- **info** (*dict*) – Dictionary of resource info.

Raises `fs.errors.ResourceNotFound` – If `path` does not exist on the filesystem

The `info` dict should be in the same format as the raw info returned by `getinfo(file).raw`.

Example

```
>>> details_info = {"details": {
...     "modified": time.time()
... }}
>>> my_fs.setinfo('file.txt', details_info)
```

settimes (*path*, *accessed=None*, *modified=None*)

Set the accessed and modified time on a resource.

Parameters

- **path** – A path to a resource on the filesystem.
- **accessed** (*datetime*, *optional*) – The accessed time, or `None` (the default) to use the current time.
- **modified** (*datetime*, *optional*) – The modified time, or `None` (the default) to use the same time as the accessed parameter.

touch (*path*)

Touch a file on the filesystem.

Touching a file means creating a new file if `path` doesn't exist, or update accessed and modified times if the path does exist. This method is similar to the linux command of the same name.

Parameters **path** (*str*) – A path to a file on the filesystem.

upload (*path*, *file*, *chunk_size=None*, ***options*)

Set a file to the contents of a binary file object.

This method copies bytes from an open binary file to a file on the filesystem. If the destination exists, it will first be truncated.

Parameters

- **path** (*str*) – A path on the filesystem.
- **file** (*io.IOBase*) – a file object open for reading in binary mode.
- **chunk_size** (*int*, *optional*) – Number of bytes to read at a time, if a simple copy is used, or `None` to use sensible default.
- ****options** – Implementation specific options required to open the source file.

Note that the file object `file` will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('~/.movies/starwars.mov', 'rb') as read_file:
...     my_fs.upload('starwars.mov', read_file)
```

validatepath (*path*)

Check if a path is valid, returning a normalized absolute path.

Many filesystems have restrictions on the format of paths they support. This method will check that *path* is valid on the underlying storage mechanism and throw a *InvalidPath* exception if it is not.

Parameters *path* (*str*) – A path.

Returns A normalized, absolute path.

Return type *str*

Raises

- *fs.errors.InvalidCharsInPath* – If the path contains invalid characters.
- *fs.errors.InvalidPath* – If the path is invalid.
- *fs.errors.FileSystemClosed* – if the filesystem is closed.

walk

a walker bound to this filesystem.

Type *BoundWalker*

writebytes (*path*, *contents*)

Copy binary data to a file.

Parameters

- **path** (*str*) – Destination path on the filesystem.
- **contents** (*bytes*) – Data to be written.

Raises *TypeError* – if contents is not bytes.

writefile (*path*, *file*, *encoding=None*, *errors=None*, *newline=""*)

Set a file to the contents of a file object.

Parameters

- **path** (*str*) – A path on the filesystem.
- **file** (*io.IOBase*) – A file object open for reading.
- **encoding** (*str*, *optional*) – Encoding of destination file, defaults to *None* for binary.
- **errors** (*str*, *optional*) – How encoding errors should be treated (same as *io.open*).
- **newline** (*str*) – Newline parameter (same as *io.open*).

This method is similar to *upload*, in that it copies data from a file-like object to a resource on the filesystem, but unlike *upload*, this method also supports creating files in text-mode (if the *encoding* argument is supplied).

Note that the file object *file* will *not* be closed by this method. Take care to close it after this method completes (ideally with a context manager).

Example

```
>>> with open('myfile.txt') as read_file:
...     my_fs.writefile('myfile.txt', read_file)
```


CHAPTER 14

Indices and tables

- `genindex`
- `modindex`
- `search`

f

fs.appfs, 25
fs.base, 83
fs.compress, 101
fs.copy, 101
fs.enums, 104
fs.errors, 104
fs.filesize, 113
fs.ftpfs, 27
fs.glob, 107
fs.info, 109
fs.memoryfs, 32
fs.mirror, 114
fs.mode, 116
fs.move, 115
fs.opener.base, 118
fs.opener.errors, 121
fs.opener.parse, 118
fs.opener.registry, 119
fs.osfs, 52
fs.path, 121
fs.permissions, 128
fs.subfs, 57
fs.tarfs, 57
fs.tempfs, 62
fs.tools, 130
fs.tree, 131
fs.walk, 131
fs.wildcard, 139
fs.wrap, 140
fs.wrapfs, 147
fs.zipfs, 63

Symbols

__call__() (*fs.glob.BoundGlobber method*), 107
 __call__() (*fs.walk.BoundWalker method*), 132
 __contains__() (*fs.mode.Mode method*), 116
 __del__() (*fs.base.FS method*), 83
 __enter__() (*fs.base.FS method*), 83
 __exit__() (*fs.base.FS method*), 83
 __iter__() (*fs.glob.Globber method*), 108
 __str__() (*fs.errors.FSError method*), 105

A

abspath() (*in module fs.path*), 121
 accessed (*fs.info.Info attribute*), 110
 add() (*fs.permissions.Permissions method*), 128
 add_fs() (*fs.multifs.MultiFS method*), 43
 appendbytes() (*fs.base.FS method*), 83
 appendbytes() (*fs.wrap.WrapReadOnly method*),
 141
 appendbytes() (*fs.wrapfs.WrapFS method*), 147
 appending (*fs.mode.Mode attribute*), 116
 appendtext() (*fs.base.FS method*), 83
 appendtext() (*fs.wrap.WrapReadOnly method*), 141
 appendtext() (*fs.wrapfs.WrapFS method*), 147
 as_str() (*fs.permissions.Permissions method*), 128
 assert_bytes() (*fs.test.FSTestCases method*), 70
 assert_exists() (*fs.test.FSTestCases method*), 70
 assert_isdir() (*fs.test.FSTestCases method*), 70
 assert_isfile() (*fs.test.FSTestCases method*), 70
 assert_not_exists() (*fs.test.FSTestCases method*), 70
 assert_text() (*fs.test.FSTestCases method*), 70

B

basename() (*in module fs.path*), 121
 binary (*fs.mode.Mode attribute*), 116
 binary() (*in module fs.filesize*), 114
 bind() (*fs.walk.Walker class method*), 136
 block_special_file (*fs.enums.ResourceType attribute*), 104

BoundGlobber (*class in fs.glob*), 107
 BoundWalker (*class in fs.walk*), 131
 BulkCopyFailed, 104

C

cache_directory() (*in module fs.wrap*), 147
 character (*fs.enums.ResourceType attribute*), 104
 check() (*fs.base.FS method*), 84
 check() (*fs.permissions.Permissions method*), 128
 check_file() (*fs.walk.Walker method*), 137
 check_open_dir() (*fs.walk.Walker method*), 137
 check_readable() (*in module fs.mode*), 117
 check_scan_dir() (*fs.walk.Walker method*), 137
 check_writable() (*in module fs.mode*), 117
 clean() (*fs.tempfs.TempFS method*), 62
 close() (*fs.base.FS method*), 84
 close() (*fs.ftpfs.FTPFS method*), 27
 close() (*fs.memoryfs.MemoryFS method*), 32
 close() (*fs.mountfs.MountFS method*), 35
 close() (*fs.multifs.MultiFS method*), 44
 close() (*fs.subfs.ClosingSubFS method*), 57
 close() (*fs.tarfs.ReadTarFS method*), 61
 close() (*fs.tarfs.WriteTarFS method*), 58
 close() (*fs.tempfs.TempFS method*), 62
 close() (*fs.zipfs.ReadZipFS method*), 66
 close() (*fs.zipfs.WriteZipFS method*), 64
 ClosingSubFS (*class in fs.subfs*), 57
 combine() (*in module fs.path*), 122
 copy() (*fs.base.FS method*), 84
 copy() (*fs.info.Info method*), 110
 copy() (*fs.osfs.OSFS method*), 52
 copy() (*fs.permissions.Permissions method*), 129
 copy() (*fs.wrap.WrapReadOnly method*), 142
 copy() (*fs.wrapfs.WrapFS method*), 148
 copy_dir() (*in module fs.copy*), 101
 copy_dir_if_newer() (*in module fs.copy*), 102
 copy_file() (*in module fs.copy*), 102
 copy_file_data() (*in module fs.tools*), 130
 copy_file_if_newer() (*in module fs.copy*), 102
 copy_file_internal() (*in module fs.copy*), 102

`copy_fs()` (in module `fs.copy`), 103
`copy_fs_if_newer()` (in module `fs.copy`), 103
`copy_structure()` (in module `fs.copy`), 103
`copydir()` (`fs.base.FS` method), 84
`copydir()` (`fs.wrapfs.WrapFS` method), 148
`count()` (`fs.glob.Globber` method), 108
`count_lines()` (`fs.glob.Globber` method), 108
`Counts` (class in `fs.glob`), 107
`create` (`fs.mode.Mode` attribute), 116
`create()` (`fs.base.FS` method), 85
`create()` (`fs.ftpfs.FTPFS` method), 27
`create()` (`fs.permissions.Permissions` class method), 129
`create()` (`fs.wrap.WrapReadOnly` method), 142
`create()` (`fs.wrapfs.WrapFS` method), 148
`created` (`fs.info.Info` attribute), 110
`CreateFailed`, 105
`current` (`fs.enums.Seek` attribute), 104

D

`data` (`fs.glob.Counts` attribute), 107
`decimal()` (in module `fs.filesize`), 114
`delegate_fs()` (`fs.subfs.SubFS` method), 57
`delegate_fs()` (`fs.tarfs.WriteTarFS` method), 58
`delegate_fs()` (`fs.wrapfs.WrapFS` method), 148
`delegate_fs()` (`fs.zipfs.WriteZipFS` method), 64
`delegate_path()` (`fs.subfs.SubFS` method), 57
`delegate_path()` (`fs.tarfs.WriteTarFS` method), 58
`delegate_path()` (`fs.wrapfs.WrapFS` method), 148
`delegate_path()` (`fs.zipfs.WriteZipFS` method), 64
`desc()` (`fs.base.FS` method), 85
`desc()` (`fs.mountfs.MountFS` method), 36
`desc()` (`fs.wrapfs.WrapFS` method), 149
`DestinationExists`, 105
`destroy_fs()` (`fs.test.FSTestCases` method), 71
`directories` (`fs.glob.Counts` attribute), 107
`directory` (`fs.enums.ResourceType` attribute), 104
`DirectoryExists`, 105
`DirectoryExpected`, 105
`DirectoryNotEmpty`, 105
`dirname()` (in module `fs.path`), 122
`dirs` (`fs.walk.Step` attribute), 135
`dirs()` (`fs.walk.BoundWalker` method), 133
`dirs()` (`fs.walk.Walker` method), 137
`download()` (`fs.base.FS` method), 85
`download()` (`fs.mountfs.MountFS` method), 36
`download()` (`fs.multifs.MultiFS` method), 44
`download()` (`fs.wrapfs.WrapFS` method), 149
`dump()` (`fs.permissions.Permissions` method), 129

E

`end` (`fs.enums.Seek` attribute), 104
`EntryPointError`, 121
`exclusive` (`fs.mode.Mode` attribute), 116

`exists()` (`fs.base.FS` method), 85
`exists()` (`fs.wrapfs.WrapFS` method), 149

F

`features` (`fs.ftpfs.FTPFS` attribute), 28
`fifo` (`fs.enums.ResourceType` attribute), 104
`file` (`fs.enums.ResourceType` attribute), 104
`FileExists`, 105
`FileExpected`, 105
`files` (`fs.glob.Counts` attribute), 107
`files` (`fs.walk.Step` attribute), 135
`files()` (`fs.walk.BoundWalker` method), 133
`files()` (`fs.walk.Walker` method), 138
`FilesystemClosed`, 105
`filterdir()` (`fs.base.FS` method), 86
`filterdir()` (`fs.wrapfs.WrapFS` method), 149
`forcedir()` (in module `fs.path`), 122
`frombase()` (in module `fs.path`), 123
`FS` (class in `fs.base`), 83
`fs.appfs` (module), 25
`fs.base` (module), 83
`fs.compress` (module), 101
`fs.copy` (module), 101
`fs.enums` (module), 104
`fs.errors` (module), 104
`fs.filesize` (module), 113
`fs.ftpfs` (module), 27
`fs.glob` (module), 107
`fs.info` (module), 109
`fs.memoryfs` (module), 32
`fs.mirror` (module), 114
`fs.mode` (module), 116
`fs.move` (module), 115
`fs.opener.base` (module), 118
`fs.opener.errors` (module), 121
`fs.opener.parse` (module), 118
`fs.opener.registry` (module), 119
`fs.osfs` (module), 52
`fs.path` (module), 121
`fs.permissions` (module), 128
`fs.subfs` (module), 57
`fs.tarfs` (module), 57
`fs.tempfs` (module), 62
`fs.tools` (module), 130
`fs.tree` (module), 131
`fs.walk` (module), 131
`fs.wildcard` (module), 139
`fs.wrap` (module), 140
`fs.wrapfs` (module), 147
`fs.zipfs` (module), 63
`FSError`, 105
`FSTestCases` (class in `fs.test`), 70
`ftp` (`fs.ftpfs.FTPFS` attribute), 28
`ftp_url` (`fs.ftpfs.FTPFS` attribute), 28

FTPFS (class in *fs.ftpfs*), 27

G

g_r (*fs.permissions.Permissions* attribute), 129
g_w (*fs.permissions.Permissions* attribute), 129
g_x (*fs.permissions.Permissions* attribute), 129
get() (*fs.info.Info* method), 110
get_fs() (*fs.multifs.MultiFS* method), 44
get_intermediate_dirs() (in module *fs.tools*), 130
get_matcher() (in module *fs.wildcard*), 139
get_mode() (*fs.permissions.Permissions* class method), 129
get_opener() (*fs.opener.registry.Registry* method), 119
getbasic() (*fs.base.FS* method), 86
getbytes() (*fs.base.FS* method), 86
getdetails() (*fs.base.FS* method), 86
getfile() (*fs.base.FS* method), 87
getinfo() (*fs.base.FS* method), 87
getinfo() (*fs.ftpfs.FTPFS* method), 28
getinfo() (*fs.memoryfs.MemoryFS* method), 32
getinfo() (*fs.mountfs.MountFS* method), 36
getinfo() (*fs.multifs.MultiFS* method), 45
getinfo() (*fs.osfs.OSFS* method), 52
getinfo() (*fs.tarfs.ReadTarFS* method), 59
getinfo() (*fs.wrap.WrapCachedDir* method), 140
getinfo() (*fs.wrapfs.WrapFS* method), 150
getinfo() (*fs.zipfs.ReadZipFS* method), 64
getmeta() (*fs.base.FS* method), 87
getmeta() (*fs.ftpfs.FTPFS* method), 28
getmeta() (*fs.wrapfs.WrapFS* method), 150
getospath() (*fs.base.FS* method), 88
getsize() (*fs.base.FS* method), 88
getsize() (*fs.mountfs.MountFS* method), 36
getsize() (*fs.multifs.MultiFS* method), 45
getsize() (*fs.wrapfs.WrapFS* method), 150
getsyspath() (*fs.base.FS* method), 88
getsyspath() (*fs.mountfs.MountFS* method), 36
getsyspath() (*fs.multifs.MultiFS* method), 45
getsyspath() (*fs.osfs.OSFS* method), 53
getsyspath() (*fs.wrapfs.WrapFS* method), 151
gettext() (*fs.base.FS* method), 89
gettype() (*fs.base.FS* method), 89
gettype() (*fs.mountfs.MountFS* method), 37
gettype() (*fs.multifs.MultiFS* method), 45
gettype() (*fs.osfs.OSFS* method), 53
gettype() (*fs.wrapfs.WrapFS* method), 151
geturl() (*fs.base.FS* method), 90
geturl() (*fs.ftpfs.FTPFS* method), 29
geturl() (*fs.mountfs.MountFS* method), 37
geturl() (*fs.multifs.MultiFS* method), 46
geturl() (*fs.osfs.OSFS* method), 53
geturl() (*fs.tarfs.ReadTarFS* method), 62

geturl() (*fs.wrapfs.WrapFS* method), 152
geturl() (*fs.zipfs.ReadZipFS* method), 67
gid (*fs.info.Info* attribute), 110
glob (*fs.base.FS* attribute), 90
Globber (class in *fs.glob*), 108
GlobMatch (class in *fs.glob*), 107
group (*fs.info.Info* attribute), 110

H

has_namespace() (*fs.info.Info* method), 110
hash() (*fs.base.FS* method), 90
hash() (*fs.wrapfs.WrapFS* method), 152
hassyspath() (*fs.base.FS* method), 90
hassyspath() (*fs.multifs.MultiFS* method), 46
hassyspath() (*fs.wrapfs.WrapFS* method), 152
hasurl() (*fs.base.FS* method), 90
hasurl() (*fs.mountfs.MountFS* method), 38
hasurl() (*fs.multifs.MultiFS* method), 46
hasurl() (*fs.wrapfs.WrapFS* method), 152

I

IllegalBackReference, 105
imatch() (in module *fs.glob*), 109
imatch() (in module *fs.wildcard*), 139
imatch_any() (in module *fs.wildcard*), 139
Info (class in *fs.info*), 109
info (*fs.glob.GlobMatch* attribute), 107
info() (*fs.walk.BoundWalker* method), 134
info() (*fs.walk.Walker* method), 138
install() (*fs.opener.registry.Registry* method), 119
InsufficientStorage, 105
InvalidCharsInPath, 105
InvalidPath, 106
is_dir (*fs.info.Info* attribute), 111
is_file (*fs.info.Info* attribute), 111
is_link (*fs.info.Info* attribute), 111
is_thread_safe() (in module *fs.tools*), 130
is_writeable() (*fs.info.Info* method), 111
isabs() (in module *fs.path*), 123
isbase() (in module *fs.path*), 123
isclosed() (*fs.base.FS* method), 91
isclosed() (*fs.tarfs.ReadTarFS* method), 62
isdir() (*fs.base.FS* method), 91
isdir() (*fs.mountfs.MountFS* method), 38
isdir() (*fs.multifs.MultiFS* method), 46
isdir() (*fs.tarfs.ReadTarFS* method), 59
isdir() (*fs.wrap.WrapCachedDir* method), 140
isdir() (*fs.wrapfs.WrapFS* method), 153
isdotfile() (in module *fs.path*), 123
isempty() (*fs.base.FS* method), 91
isfile() (*fs.base.FS* method), 91
isfile() (*fs.mountfs.MountFS* method), 38
isfile() (*fs.multifs.MultiFS* method), 47
isfile() (*fs.tarfs.ReadTarFS* method), 59

`isfile()` (*fs.wrap.WrapCachedDir method*), 141
`isfile()` (*fs.wrapfs.WrapFS method*), 153
`islink()` (*fs.base.FS method*), 91
`islink()` (*fs.osfs.OSFS method*), 54
`islink()` (*fs.wrapfs.WrapFS method*), 153
`isparent()` (*in module fs.path*), 124
`issamedir()` (*in module fs.path*), 124
`iswildcard()` (*in module fs.path*), 125
`iterate_fs()` (*fs.multifs.MultiFS method*), 47
`iteratepath()` (*in module fs.path*), 125

J

`join()` (*in module fs.path*), 125

L

`LineCounts` (*class in fs.glob*), 109
`lines` (*fs.glob.LineCounts attribute*), 109
`listdir()` (*fs.base.FS method*), 91
`listdir()` (*fs.ftpfs.FTPFS method*), 29
`listdir()` (*fs.memoryfs.MemoryFS method*), 32
`listdir()` (*fs.mountfs.MountFS method*), 38
`listdir()` (*fs.multifs.MultiFS method*), 47
`listdir()` (*fs.osfs.OSFS method*), 54
`listdir()` (*fs.tarfs.ReadTarFS method*), 60
`listdir()` (*fs.wrapfs.WrapFS method*), 153
`listdir()` (*fs.zipfs.ReadZipFS method*), 65
`load()` (*fs.permissions.Permissions class method*), 129
`lock()` (*fs.base.FS method*), 92
`lock()` (*fs.wrapfs.WrapFS method*), 153

M

`make_fs()` (*fs.test.FSTestCases method*), 71
`make_mode()` (*in module fs.permissions*), 130
`make_path()` (*fs.info.Info method*), 111
`makedir()` (*fs.base.FS method*), 92
`makedir()` (*fs.ftpfs.FTPFS method*), 29
`makedir()` (*fs.memoryfs.MemoryFS method*), 33
`makedir()` (*fs.mountfs.MountFS method*), 38
`makedir()` (*fs.multifs.MultiFS method*), 47
`makedir()` (*fs.osfs.OSFS method*), 54
`makedir()` (*fs.tarfs.ReadTarFS method*), 60
`makedir()` (*fs.wrap.WrapReadOnly method*), 142
`makedir()` (*fs.wrapfs.WrapFS method*), 154
`makedir()` (*fs.zipfs.ReadZipFS method*), 65
`makedirs()` (*fs.base.FS method*), 92
`makedirs()` (*fs.multifs.MultiFS method*), 47
`makedirs()` (*fs.wrap.WrapReadOnly method*), 143
`makedirs()` (*fs.wrapfs.WrapFS method*), 154
`manage_fs()` (*fs.opener.registry.Registry method*), 119
`match()` (*fs.base.FS method*), 93
`match()` (*in module fs.glob*), 109
`match()` (*in module fs.wildcard*), 139
`match_any()` (*in module fs.wildcard*), 140
`MemoryFS` (*class in fs.memoryfs*), 32

`metadata_changed` (*fs.info.Info attribute*), 111
`mirror()` (*in module fs.mirror*), 115
`MissingInfoNamespace`, 106
`Mode` (*class in fs.mode*), 116
`mode` (*fs.permissions.Permissions attribute*), 129
`modified` (*fs.info.Info attribute*), 111
`mount()` (*fs.mountfs.MountFS method*), 39
`MountError`, 42
`MountFS` (*class in fs.mountfs*), 35
`move()` (*fs.base.FS method*), 93
`move()` (*fs.wrap.WrapReadOnly method*), 143
`move()` (*fs.wrapfs.WrapFS method*), 154
`move_dir()` (*in module fs.move*), 115
`move_file()` (*in module fs.move*), 115
`move_fs()` (*in module fs.move*), 115
`movedir()` (*fs.base.FS method*), 93
`movedir()` (*fs.wrapfs.WrapFS method*), 155
`MultiFS` (*class in fs.multifs*), 43

N

`name` (*fs.info.Info attribute*), 111
`non_blank` (*fs.glob.LineCounts attribute*), 109
`normpath()` (*in module fs.path*), 125
`NoSysPath`, 106
`NotWriteable`, 121
`NoURL`, 106

O

`o_r` (*fs.permissions.Permissions attribute*), 129
`o_w` (*fs.permissions.Permissions attribute*), 129
`o_x` (*fs.permissions.Permissions attribute*), 129
`open()` (*fs.base.FS method*), 94
`open()` (*fs.mountfs.MountFS method*), 39
`open()` (*fs.multifs.MultiFS method*), 48
`open()` (*fs.opener.registry.Registry method*), 120
`open()` (*fs.osfs.OSFS method*), 54
`open()` (*fs.wrap.WrapReadOnly method*), 143
`open()` (*fs.wrapfs.WrapFS method*), 155
`open_fs()` (*fs.opener.base.Opener method*), 118
`open_fs()` (*fs.opener.registry.Registry method*), 120
`openbin()` (*fs.base.FS method*), 94
`openbin()` (*fs.ftpfs.FTPFS method*), 29
`openbin()` (*fs.memoryfs.MemoryFS method*), 33
`openbin()` (*fs.mountfs.MountFS method*), 39
`openbin()` (*fs.multifs.MultiFS method*), 48
`openbin()` (*fs.osfs.OSFS method*), 55
`openbin()` (*fs.tarfs.ReadTarFS method*), 60
`openbin()` (*fs.wrap.WrapReadOnly method*), 144
`openbin()` (*fs.wrapfs.WrapFS method*), 155
`openbin()` (*fs.zipfs.ReadZipFS method*), 66
`opendir()` (*fs.base.FS method*), 95
`opendir()` (*fs.wrapfs.WrapFS method*), 156
`Opener` (*class in fs.opener.base*), 118
`OpenerError`, 121

OperationFailed, 106
 OperationTimeout, 106
 OSFS (class in *fs.osfs*), 52

P

params (*fs.opener.parse.ParseResult* attribute), 118
 parse() (*fs.permissions.Permissions* class method), 129
 parse_fs_url() (in module *fs.opener.parse*), 119
 ParseError, 121
 ParseResult (class in *fs.opener.parse*), 118
 parts() (in module *fs.path*), 126
 password (*fs.opener.parse.ParseResult* attribute), 118
 path (*fs.glob.GlobMatch* attribute), 108
 path (*fs.opener.parse.ParseResult* attribute), 118
 path (*fs.walk.Step* attribute), 135
 PathError, 106
 PermissionDenied, 106
 Permissions (class in *fs.permissions*), 128
 permissions (*fs.info.Info* attribute), 112
 protocol (*fs.opener.parse.ParseResult* attribute), 118
 protocols (*fs.opener.registry.Registry* attribute), 120

R

read_only() (in module *fs.wrap*), 147
 readbytes() (*fs.base.FS* method), 95
 readbytes() (*fs.ftpfs.FTPFS* method), 30
 readbytes() (*fs.mountfs.MountFS* method), 40
 readbytes() (*fs.multifs.MultiFS* method), 49
 readbytes() (*fs.wrapfs.WrapFS* method), 156
 readbytes() (*fs.zipfs.ReadZipFS* method), 67
 reading (*fs.mode.Mode* attribute), 116
 ReadTarFS (class in *fs.tarfs*), 59
 readtext() (*fs.base.FS* method), 95
 readtext() (*fs.mountfs.MountFS* method), 40
 readtext() (*fs.multifs.MultiFS* method), 49
 readtext() (*fs.wrapfs.WrapFS* method), 156
 ReadZipFS (class in *fs.zipfs*), 64
 recursepath() (in module *fs.path*), 126
 Registry (class in *fs.opener.registry*), 119
 relativefrom() (in module *fs.path*), 126
 relpath() (in module *fs.path*), 127
 RemoteConnectionError, 106
 remove() (*fs.base.FS* method), 95
 remove() (*fs.ftpfs.FTPFS* method), 30
 remove() (*fs.glob.Globber* method), 108
 remove() (*fs.memoryfs.MemoryFS* method), 34
 remove() (*fs.mountfs.MountFS* method), 40
 remove() (*fs.multifs.MultiFS* method), 49
 remove() (*fs.osfs.OSFS* method), 55
 remove() (*fs.permissions.Permissions* method), 129
 remove() (*fs.tarfs.ReadTarFS* method), 61
 remove() (*fs.wrap.WrapReadOnly* method), 144
 remove() (*fs.wrapfs.WrapFS* method), 157

remove() (*fs.zipfs.ReadZipFS* method), 66
 remove_empty() (in module *fs.tools*), 130
 removedir() (*fs.base.FS* method), 96
 removedir() (*fs.ftpfs.FTPFS* method), 30
 removedir() (*fs.memoryfs.MemoryFS* method), 34
 removedir() (*fs.mountfs.MountFS* method), 40
 removedir() (*fs.multifs.MultiFS* method), 49
 removedir() (*fs.osfs.OSFS* method), 56
 removedir() (*fs.tarfs.ReadTarFS* method), 61
 removedir() (*fs.wrap.WrapReadOnly* method), 144
 removedir() (*fs.wrapfs.WrapFS* method), 157
 removedir() (*fs.zipfs.ReadZipFS* method), 66
 RemoveRootError, 106
 removetree() (*fs.base.FS* method), 96
 removetree() (*fs.wrapfs.WrapFS* method), 157
 render() (in module *fs.tree*), 131
 resource (*fs.opener.parse.ParseResult* attribute), 118
 ResourceError, 106
 ResourceInvalid, 106
 ResourceLocked, 106
 ResourceNotFound, 107
 ResourceReadOnly, 107
 ResourceType (class in *fs.enums*), 104

S

scandir() (*fs.base.FS* method), 96
 scandir() (*fs.ftpfs.FTPFS* method), 30
 scandir() (*fs.mountfs.MountFS* method), 41
 scandir() (*fs.multifs.MultiFS* method), 49
 scandir() (*fs.osfs.OSFS* method), 56
 scandir() (*fs.wrap.WrapCachedDir* method), 141
 scandir() (*fs.wrapfs.WrapFS* method), 157
 Seek (class in *fs.enums*), 104
 set (*fs.enums.Seek* attribute), 104
 setbinfile() (*fs.base.FS* method), 96
 setbytes() (*fs.base.FS* method), 97
 setfile() (*fs.base.FS* method), 97
 setgid (*fs.permissions.Permissions* attribute), 130
 setinfo() (*fs.base.FS* method), 97
 setinfo() (*fs.ftpfs.FTPFS* method), 31
 setinfo() (*fs.memoryfs.MemoryFS* method), 34
 setinfo() (*fs.mountfs.MountFS* method), 41
 setinfo() (*fs.multifs.MultiFS* method), 50
 setinfo() (*fs.osfs.OSFS* method), 56
 setinfo() (*fs.tarfs.ReadTarFS* method), 59
 setinfo() (*fs.wrap.WrapReadOnly* method), 145
 setinfo() (*fs.wrapfs.WrapFS* method), 157
 setinfo() (*fs.zipfs.ReadZipFS* method), 65
 settext() (*fs.base.FS* method), 98
 settimes() (*fs.base.FS* method), 98
 settimes() (*fs.wrap.WrapReadOnly* method), 145
 settimes() (*fs.wrapfs.WrapFS* method), 158
 setuid (*fs.permissions.Permissions* attribute), 130
 SiteConfigFS (class in *fs.appfs*), 26

SiteDataFS (class in *fs.appfs*), 26
size (*fs.info.Info* attribute), 112
socket (*fs.enums.ResourceType* attribute), 104
split() (in module *fs.path*), 127
splitext() (in module *fs.path*), 127
stem (*fs.info.Info* attribute), 112
Step (class in *fs.walk*), 135
sticky (*fs.permissions.Permissions* attribute), 130
SubFS (class in *fs.subfs*), 57
suffix (*fs.info.Info* attribute), 112
suffixes (*fs.info.Info* attribute), 112
supports_mlst (*fs.ftpfs.FTPFS* attribute), 31
symlink (*fs.enums.ResourceType* attribute), 104

T

TarFS (class in *fs.tarfs*), 57
target (*fs.info.Info* attribute), 113
TempFS (class in *fs.tempfs*), 62
test_geturl_purpose() (*fs.test.FSTestCases* method), 71
test_validatepath() (*fs.test.FSTestCases* method), 71
text (*fs.mode.Mode* attribute), 116
to_platform() (*fs.mode.Mode* method), 117
to_platform_bin() (*fs.mode.Mode* method), 117
touch() (*fs.base.FS* method), 98
touch() (*fs.wrap.WrapReadOnly* method), 145
touch() (*fs.wrapfs.WrapFS* method), 158
traditional() (in module *fs.filesize*), 113
tree() (*fs.base.FS* method), 98
truncate (*fs.mode.Mode* attribute), 117
type (*fs.info.Info* attribute), 113

U

u_r (*fs.permissions.Permissions* attribute), 130
u_w (*fs.permissions.Permissions* attribute), 130
u_x (*fs.permissions.Permissions* attribute), 130
uid (*fs.info.Info* attribute), 113
unknown (*fs.enums.ResourceType* attribute), 104
Unsupported, 107
UnsupportedProtocol, 121
updating (*fs.mode.Mode* attribute), 117
upload() (*fs.base.FS* method), 99
upload() (*fs.fipfs.FTPFS* method), 31
upload() (*fs.mountfs.MountFS* method), 41
upload() (*fs.multifs.MultiFS* method), 50
upload() (*fs.wrap.WrapReadOnly* method), 145
upload() (*fs.wrapfs.WrapFS* method), 158
user (*fs.info.Info* attribute), 113
UserCacheFS (class in *fs.appfs*), 26
UserConfigFS (class in *fs.appfs*), 25
UserDataFS (class in *fs.appfs*), 25
UserLogFS (class in *fs.appfs*), 26
username (*fs.opener.parse.ParseResult* attribute), 118

V

validate() (*fs.mode.Mode* method), 117
validate_bin() (*fs.mode.Mode* method), 117
validate_openbin_mode() (in module *fs.mode*), 117
validatepath() (*fs.base.FS* method), 99
validatepath() (*fs.mountfs.MountFS* method), 42
validatepath() (*fs.multifs.MultiFS* method), 51
validatepath() (*fs.osfs.OSFS* method), 56
validatepath() (*fs.wrapfs.WrapFS* method), 158

W

walk (*fs.base.FS* attribute), 100
walk (*fs.wrapfs.WrapFS* attribute), 159
walk() (*fs.walk.BoundWalker* method), 134
walk() (*fs.walk.Walker* method), 138
Walker (class in *fs.walk*), 136
walker_class (*fs.base.FS* attribute), 100
which() (*fs.multifs.MultiFS* method), 51
WrapCachedDir (class in *fs.wrap*), 140
WrapFS (class in *fs.wrapfs*), 147
WrapReadOnly (class in *fs.wrap*), 141
write_tar() (*fs.tarfs.WriteTarFS* method), 59
write_tar() (in module *fs.compress*), 101
write_zip() (*fs.zipfs.WriteZipFS* method), 64
write_zip() (in module *fs.compress*), 101
writebytes() (*fs.base.FS* method), 100
writebytes() (*fs.ftpfs.FTPFS* method), 31
writebytes() (*fs.mountfs.MountFS* method), 42
writebytes() (*fs.multifs.MultiFS* method), 51
writebytes() (*fs.wrap.WrapReadOnly* method), 146
writebytes() (*fs.wrapfs.WrapFS* method), 159
writefile() (*fs.base.FS* method), 100
writefile() (*fs.wrap.WrapReadOnly* method), 146
writefile() (*fs.wrapfs.WrapFS* method), 159
WriteTarFS (class in *fs.tarfs*), 58
writetext() (*fs.base.FS* method), 100
writetext() (*fs.mountfs.MountFS* method), 42
writetext() (*fs.multifs.MultiFS* method), 51
writetext() (*fs.wrap.WrapReadOnly* method), 146
WriteZipFS (class in *fs.zipfs*), 64
writing (*fs.mode.Mode* attribute), 117

Z

ZipFS (class in *fs.zipfs*), 63